

# Smart Inventory & Sales Tracker (S.I.S.T.)

## 1) Story

A mid-sized retail chain, **NeoMart**, runs 8 local stores. They currently track products, stock, and sales in Excel. This causes issues:

- Wrong stock counts → lost sales
- No audit trail of who changed what
- No simple way to view daily sales or low-stock alerts
- Data inconsistencies due to manual edits

NeoMart wants a **Java-based Inventory & Sales Tracker** that uses a relational DB, supports **role-based actions** (Admin vs Cashier), logs all operations, and produces basic business reports

You are hired as the backend team to build the **first working version**.

---

## 2) What you will build

A **console-based Java application** (no UI frameworks required) that:

- Manages **Products, Stock, Customers, Orders, and Payments**
  - Persists data in **MySQL / PostgreSQL** using **SQL + JDBC**
  - Uses **layered architecture**
  - Has **JUnit tests** for core services/validations
  - Uses **Log4j** logging for audit/debug
  - Uses **Git** with proper branching + commit discipline
- 

## 3) Mandatory Tech/Concept Coverage

### Core Java (must use)

- OOP (encapsulation, abstraction, interfaces)
- Collections (List/Map usage in service layer + validations)
- Enums (roles, order status, payment mode/status)
- Java Time API (**LocalDateTime** for timestamps)
- Custom exceptions + proper handling

- Input validation and defensive programming

## SQL + JDBC (must use)

- Normalized schema (min 3NF where reasonable)
- CRUD using `PreparedStatement`
- Transactions (`commit/rollback`) in order placement
- Joins & aggregations for reporting queries
- Constraints: PK, FK, UNIQUE, NOT NULL, CHECK (if supported)

## Git (must use)

- Feature branches
- Meaningful commits
- PR-style workflow even if solo (merge feature branch to main)

## JUnit (must use)

- Unit tests for service-layer logic
- DAO tests optional (bonus)
- Assertions verifying behavior + edge cases

## Log4j (must use)

- Separate loggers for app flow + DB errors (or separate categories)
- Levels: INFO/WARN/ERROR/DEBUG
- Log file output + console output
- **No `System.out.println()` for application flow** (only menu prompts / final display outputs)

## Architecture + Quality (must use)

- Layered design + clean separation
  - Centralized exception strategy
  - **No SQL inside service classes** (DAO only)
  - Config via properties file
  - Code quality: naming, SRP, no massive classes
- 

# 4) Functional Requirements

## A) User Roles

### ADMIN

- Add/update/deactivate products
- Stock adjustments (add/remove stock + reason)
- View reports

## CASHIER

- Search products
- Create customer (optional)
- Create order + payment
- Print invoice (console output)

**Authentication can be simple:** username + role input (not full security).

**Role gating:** show/hide menu actions based on role.

---

## B) Product Management

Each product must have:

- `productId` (auto)
- `sku` (unique)
- `name`
- `category`
- `unitPrice`
- `active` (true/false)
- `createdAt`, `updatedAt`

Operations:

- Create product
  - Update product details
  - Deactivate product (soft delete)
  - Search product by name/category/sku
- 

## C) Inventory / Stock

Track stock per product:

- `productId` FK
- `availableQuantity`
- `reorderLevel`

Operations

- Increase stock (admin)
- Reduce stock (admin adjustment OR order placement)
- Low stock report: products where `availableQuantity <= reorderLevel`

**Audit requirement:** every admin stock change must also insert a row in `stock_adjustments` with `deltaQty` and `reason`.

---

## D) Order Placement (Core Workflow)

An order includes:

- `orderId`
- customer info (name + phone OR anonymous)
- items (`productId`, `quantity`, `unitPriceAtPurchase`)
- `orderTotal`
- `status` (CREATED, PAID, CANCELLED)
- `createdAt`

Rules:

- Cannot order inactive products
- Cannot order quantity > available stock
- Must update stock when order is successfully placed
- Payment marks order as PAID
- **Must be transactional:** if any step fails → rollback everything

### Design rule (to avoid inconsistent implementations)

✓ **Stock is decremented only after payment is SUCCESS.**

If payment fails → order remains CREATED and stock remains unchanged.

---

## E) Payments

Payment details:

- `paymentId`
- `orderId` FK
- `mode` (CASH, CARD, UPI)
- `amount`
- `status` (SUCCESS, FAILED)
- `paidAt`

## Rules

- Amount must equal orderTotal (v1)
- 

## F) Reporting Requirements (SQL-heavy)

Implement as menu options:

1. **Daily Sales Summary**
  - Date → total orders, total revenue, top 3 sold products
2. **Product Sales Report**
  - product-wise quantity sold + revenue (date range)
3. **Low Stock Report**
4. **Inactive Products List**
5. **Order Lookup**
  - by orderId OR by customer phone (sorted by `created_at` DESC)

Reports must use SQL joins/aggregations.

---

## 5) Layered Architecture (Required)

Use this structure (or very close):

- presentation/controller (console menus, input)
- service (business rules, validation, transactions)
- dao (JDBC code only)
- model (POJOs/entities)
- exception (custom exceptions)
- util (DB connection, validators, helpers)
- config/resources (db.properties, log4j2.xml)

**Rule:** UI layer never directly calls DAO.

---

## 6) Exception Handling Rules (Non-negotiable)

Create custom exceptions such as:

- `ValidationException`
- `EntityNotFoundException`
- `InsufficientStockException`
- `DatabaseOperationException`

Guidelines:

- Validate early in service layer
  - Catch SQLExceptions in DAO and wrap into `DatabaseOperationException`
  - Log errors with stack traces at ERROR level
  - Show user-friendly message in console (no stack trace in UI)
- 

## 7) JUnit Testing Requirements (Must Have)

You must include **at least 12 meaningful tests**, including these **minimum required** tests:

1. `shouldRejectNegativePrice()`
2. `shouldRejectPriceWithMoreThan2Decimals()`
3. `shouldRejectEmptySku()`
4. `shouldRejectDuplicateSku()`
5. `shouldDeactivateProductAndPreventOrdering()`
6. `shouldRejectOrderWithZeroItems()`
7. `shouldRejectOrderItemWithNonPositiveQty()`
8. `shouldThrowInsufficientStockWhenQuantityExceedsAvailable()`
9. `shouldComputeOrderTotalUsingUnitPriceAtSale()`
10. `shouldFailPaymentWhenAmountMismatch()`
11. `shouldRollbackWhenAnyStepFailsDuringPlaceOrder()` (*bonus if done via fake DAO / controlled failure*)
12. `shouldNormalizePhoneAndCreateOrFetchCustomer()`

Clear naming example:

- `shouldThrowInsufficientStockWhenQuantityExceedsAvailable()`
- 

## 8) Git Requirements

Repository must show:

- main branch protected in spirit (don't commit directly)
- Feature branches like:
  - `feature/product-management`
  - `feature/order-flow`
  - `feature/report`

- **At least 20 commits** with meaningful messages
    - ✓ Add ProductService validation and exceptions
    - ✗ final code, done, changes
- 

## 9) Submission Deliverables

You must submit:

- Source code (Git repo)
  - README.md
  - schema.sql
  - db.properties template (no passwords committed)
  - log4j2.xml or log4j2.properties
  - JUnit test output (screenshots or console output)
- 

## 10) Evaluation Rubric

- Architecture & separation of concerns: **25%**
- SQL schema + query quality + JDBC correctness: **20%**
- Order transaction correctness + rollback safety: **15%**
- Testing quality (JUnit): **15%**
- Logging & exception handling: **10%**
- Git hygiene + README quality: **10%**
- Code cleanliness (naming, SRP, duplication): **5%**

# Starter Kit

None

```
neomart-sist/
├─ README.md
│   └─ HINT: Setup, DB steps, how to run, sample menu flows, and design decisions (esp. transaction timing).
├─ schema.sql
│   └─ HINT: Tables + constraints + seed data (8+ products). Normalize and enforce FK/UNIQUE/NOT NULL.
├─ pom.xml (or build.gradle)
│   └─ HINT: Dependencies: JDBC driver, Log4j2, JUnit5 + Surefire plugin.
├─ src/
│   └─ main/
│       ├── java/com/neomart/sist/
│       │   ├── App.java
│       │   │   └─ HINT: Entry point. Show main menu, route to controllers, handle global errors.
│       │   ├── controller/
│       │   │   ├── ProductController.java
│       │   │   │   └─ HINT: Read input, call ProductService/InventoryService, print results. No SQL here.
│       │   │   ├── OrderController.java
│       │   │   │   └─ HINT: Cashier flow: phone/anonymous → add items by SKU → checkout → invoice print.
│       │   │   └─ ReportController.java
│       │   │       └─ HINT: Read date/range input, call ReportService, print tabular report output.
│       │   └─ service/
│       │       ├── ProductService.java
│       │       │   └─ HINT: Validations + uniqueness + orchestration. No SQL strings.
│       │       ├── InventoryService.java
│       │       │   └─ HINT: Admin stock adjust must update inventory + insert stock_adjustments with reason.
│       │       ├── CustomerService.java
│       │       │   └─ HINT: Normalize phone, create/find customer, support getOrCreate by phone.
│       │       ├── OrderService.java
│       │       │   └─ HINT: Transaction boundary: lock inventory, validate, insert order+items, payment, stock decrement,
│       │       └─ ReportService.java
│       │           └─ HINT: Validate date/range, call ReportDao queries, return DTOs/rows for printing.
│       └─ dao/
│           ├── ProductDao.java
│           │   └─ HINT: CRUD/search only. No validation.
│           ├── InventoryDao.java
│           │   └─ HINT: Stock reads/updates. Ensure no negative quantity.
│           ├── CustomerDao.java
│           │   └─ HINT: Create/find/search. Phone is UNIQUE.
│           ├── OrderDao.java
│           │   └─ HINT: Insert order header + items + update status/total + fetch for invoice.
│           ├── PaymentDao.java
│           │   └─ HINT: Insert payment + fetch by orderId.
│           ├── StockAdjustmentDao.java
│           │   └─ HINT: Insert adjustment records (delta+reason). Optional query history (bonus).
│           └─ impl/
│               ├── JdbcProductDao.java
│               ├── JdbcInventoryDao.java
│               ├── JdbcCustomerDao.java
│               ├── JdbcOrderDao.java
│               ├── JdbcPaymentDao.java
│               └── JdbcStockAdjustmentDao.java
│                   └─ HINT: JDBC only. Catch SQLException and throw DatabaseOperationException.
└─ model/
    ├── Product.java
    ├── Inventory.java
    └── Customer.java
```



1. *Journal of Management Studies*, 1997, 34, 10, 1039-1052.

```

log.info("AutoCare WMS started");

BookingController bookingController = new BookingController();
InvoiceController invoiceController = new InvoiceController();
PartController partController = new PartController();
ReportController reportController = new ReportController();

while (true) {
    System.out.println("\n=== AutoCare WMS ===");
    System.out.println("1. Bookings");
    System.out.println("2. Invoices");
    System.out.println("3. Parts (Admin)");
    System.out.println("4. Reports");
    System.out.println("0. Exit");

    int choice = InputUtil.readInt("Choose: ");
    switch (choice) {
        case 1 -> bookingController.menu();
        case 2 -> invoiceController.menu();
        case 3 -> partController.menu();
        case 4 -> reportController.menu();
        case 0 -> {
            log.info("AutoCare WMS stopped");
            System.out.println("Bye!");
            return;
        }
        default -> System.out.println("Invalid option.");
    }
}
}
}

```

## DbConnectionFactory.java (single place for connections)

```

Java
package com.neomart.sist.util;

import java.io.InputStream;
import java.sql.Connection;
import java.sql.DriverManager;
import java.util.Properties;

public final class DbConnectionFactory {
    private static final Properties props = new Properties();

    static {
        try (InputStream in =
            DbConnectionFactory.class.getClassLoader().getResourceAsStream("db.properties")) {
            if (in == null) throw new IllegalStateException("db.properties
            not found in resources/");
            props.load(in);
        } catch (Exception e) {

```

```

        throw new ExceptionInInitializerError("Failed to load
db.properties: " + e.getMessage());
    }
}

private DbConnectionFactory() {}

public static Connection getConnection() {
    try {
        return DriverManager.getConnection(
            props.getProperty("db.url"),
            props.getProperty("db.username"),
            props.getProperty("db.password")
        );
    } catch (Exception e) {
        throw new RuntimeException("DB connection failed: " +
e.getMessage(), e);
    }
}
}

```

## db.properties (template)

```

db.url=jdbc:mysql://localhost:3306/autocare_wms
db.username=root
db.password=YOUR_PASSWORD

```

## DB Schema

None

Save as **schema.sql**.

```

-- Create DB
CREATE DATABASE IF NOT EXISTS neomart_sist;
USE neomart_sist;

-- Products
CREATE TABLE products (
    product_id    BIGINT PRIMARY KEY AUTO_INCREMENT,
    sku           VARCHAR(50) NOT NULL UNIQUE,
    name          VARCHAR(120) NOT NULL,
    category      VARCHAR(60) NOT NULL,
    unit_price    DECIMAL(10,2) NOT NULL,
    active        BOOLEAN NOT NULL DEFAULT TRUE,

```

```

        created_at      DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
        updated_at      DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP
    );

-- Inventory (1 row per product)
CREATE TABLE inventory (
    product_id          BIGINT PRIMARY KEY,
    available_quantity  INT NOT NULL,
    reorder_level       INT NOT NULL DEFAULT 5,
    updated_at          DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
    CONSTRAINT fk_inventory_product
        FOREIGN KEY (product_id) REFERENCES products(product_id)
        ON DELETE RESTRICT
);

-- Customers (optional for cashier, allow null customer on order by design
choice)
CREATE TABLE customers (
    customer_id BIGINT PRIMARY KEY AUTO_INCREMENT,
    name        VARCHAR(120) NOT NULL,
    phone       VARCHAR(20) NOT NULL UNIQUE,
    created_at  DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP
);

-- Orders
CREATE TABLE orders (
    order_id      BIGINT PRIMARY KEY AUTO_INCREMENT,
    customer_id   BIGINT NULL,
    order_total   DECIMAL(12,2) NOT NULL,
    status        VARCHAR(20) NOT NULL, -- CREATED, PAID, CANCELLED
    created_at    DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
    CONSTRAINT fk_orders_customer
        FOREIGN KEY (customer_id) REFERENCES customers(customer_id)
        ON DELETE SET NULL
);

-- Order items
CREATE TABLE order_items (
    order_item_id    BIGINT PRIMARY KEY AUTO_INCREMENT,
    order_id         BIGINT NOT NULL,
    product_id       BIGINT NOT NULL,
    quantity         INT NOT NULL,
    unit_price_at_sale DECIMAL(10,2) NOT NULL,
    line_total       DECIMAL(12,2) NOT NULL,
    CONSTRAINT fk_items_order
        FOREIGN KEY (order_id) REFERENCES orders(order_id)
        ON DELETE CASCADE,
    CONSTRAINT fk_items_product
        FOREIGN KEY (product_id) REFERENCES products(product_id)
        ON DELETE RESTRICT
);

-- Payments (1 payment per order in v1)

```

```

CREATE TABLE payments (
  payment_id    BIGINT PRIMARY KEY AUTO_INCREMENT,
  order_id      BIGINT NOT NULL UNIQUE,
  mode          VARCHAR(20) NOT NULL, -- CASH, CARD, UPI
  amount        DECIMAL(12,2) NOT NULL,
  status        VARCHAR(20) NOT NULL, -- SUCCESS, FAILED
  paid_at       DATETIME NULL,
  CONSTRAINT fk_payments_order
    FOREIGN KEY (order_id) REFERENCES orders(order_id)
    ON DELETE CASCADE
);

-- Stock adjustment audit (admin stock changes with reason)
CREATE TABLE stock_adjustments (
  adjustment_id BIGINT PRIMARY KEY AUTO_INCREMENT,
  product_id    BIGINT NOT NULL,
  delta_qty     INT NOT NULL, -- + for add, - for reduce
  reason        VARCHAR(200) NOT NULL,
  created_at    DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
  CONSTRAINT fk_adj_product
    FOREIGN KEY (product_id) REFERENCES products(product_id)
    ON DELETE RESTRICT
);

-- Seed sample products (8)
INSERT INTO products (sku, name, category, unit_price, active) VALUES
('SKU-1001', 'Eco Bottle 1L', 'Kitchen', 399.00, true),
('SKU-1002', 'Bamboo Toothbrush', 'Personal Care', 99.00, true),
('SKU-1003', 'Organic Cotton Towel', 'Home', 599.00, true),
('SKU-1004', 'LED Desk Lamp', 'Electronics', 1299.00, true),
('SKU-1005', 'Ceramic Mug', 'Kitchen', 249.00, true),
('SKU-1006', 'Yoga Mat', 'Fitness', 899.00, true),
('SKU-1007', 'Notebook A5', 'Stationery', 149.00, true),
('SKU-1008', 'Reusable Straw Set', 'Kitchen', 199.00, true);

-- Seed inventory
INSERT INTO inventory (product_id, available_quantity, reorder_level)
SELECT product_id, 25, 5 FROM products;

```

## Sample menu flow (console UX)

### Main

```

=== NeoMart S.I.S.T. ===
1. Products
2. Orders
3. Reports
0. Exit

```

## Products Menu

--- Products ---

1. Add product (ADMIN)
2. Update product (ADMIN)
3. Deactivate product (ADMIN)
4. Search product (name/category/sku)
5. View product by SKU
6. Stock adjustment (ADMIN)
0. Back

## Orders Menu

--- Orders ---

1. Create order (CASHIER)
2. Add item to order (during creation)
3. Checkout + payment
4. Find order by ID
5. Find orders by customer phone
0. Back

## Reports Menu

--- Reports ---

1. Daily sales summary (date)
2. Sales by product (date range)
3. Low stock report
4. Inactive products
0. Back

## Recommended flow for “Create order”:

1. ask phone (or choose “anonymous”)
2. show product search
3. add items (sku + qty) in a loop
4. show cart preview + total
5. select payment mode + confirm
6. place order transactionally (insert order + items + reduce stock + insert payment + update order status)