

Java Stream API – Complete Practice Workbook

Dataset: Employee Management System

1 Data Model

```
public class Employee {

    private int id;
    private String empCode;
    private String fullName;
    private String email;
    private String department;
    private double salary;

    public Employee(int id, String empCode, String fullName,
                    String email, String department, double salary)
    {
        this.id = id;
        this.empCode = empCode;
        this.fullName = fullName;
        this.email = email;
        this.department = department;
        this.salary = salary;
    }

    public int getId() { return id; }
    public String getEmpCode() { return empCode; }
    public String getFullName() { return fullName; }
    public String getEmail() { return email; }
    public String getDepartment() { return department; }
    public double getSalary() { return salary; }

    @Override
    public String toString() {
        return fullName + " (" + department + ") - " + salary;
    }
}
```

```
}  
}
```

2 Dataset

```
List<Employee> employees = List.of(  
    new Employee(1, "EMP-1001", "Aarav Sharma",  
        "aarav.sharma@example.com", "Engineering", 120000.00),  
    new Employee(2, "EMP-1002", "Vishal Shah",  
        "vishal-shah@example.com", "Chemical", 150000.00),  
    new Employee(3, "EMP-1003", "Samiksha", "samiksha@example.com",  
        "Engineering", 90000.00),  
    new Employee(4, "EMP-1004", "Tushar", "tushar@example.com",  
        "Chemical", 140000.00),  
    new Employee(5, "EMP-1005", "Siddhant", "siddhant@example.com",  
        "Engineering", 80000.00)  
);
```

3 Stream API Refresher

A Stream pipeline consists of:

Source → Intermediate Operations → Terminal Operation

Example:

```
employees.stream()  
    .filter(e -> e.getSalary() > 100000)  
    .map(Employee::getFullName)  
    .forEach(System.out::println);
```

4 Basic Filtering

4.1 Employees with salary > 100000

```
employees.stream()
    .filter(e -> e.getSalary() > 100000)
    .forEach(System.out::println);
```

4.2 Employees in Engineering department

```
employees.stream()
    .filter(e -> e.getDepartment().equals("Engineering"))
    .forEach(System.out::println);
```

4.3 Employees whose name starts with 'S'

```
employees.stream()
    .filter(e -> e.getFullName().startsWith("S"))
    .forEach(System.out::println);
```

5 Mapping Operations

5.1 Get all employee emails

```
employees.stream()
    .map(Employee::getEmail)
    .forEach(System.out::println);
```

5.2 Get salary list

```
employees.stream()
    .map(Employee::getSalary)
    .forEach(System.out::println);
```

5.3 Convert names to uppercase

```
employees.stream()
    .map(e -> e.getFullName().toUpperCase())
    .forEach(System.out::println);
```

6 Primitive Streams

6.1 Total salary

```
double totalSalary = employees.stream()
    .mapToDouble(Employee::getSalary)
    .sum();
```

6.2 Average salary

```
double avgSalary = employees.stream()
    .mapToDouble(Employee::getSalary)
    .average()
    .orElse(0);
```

6.3 Highest salary

```
double maxSalary = employees.stream()
    .mapToDouble(Employee::getSalary)
    .max()
    .orElse(0);
```

7 Sorting

7.1 Sort by salary ascending

```
employees.stream()
    .sorted(Comparator.comparing(Employee::getSalary))
    .forEach(System.out::println);
```

7.2 Sort by salary descending

```
employees.stream()

    .sorted(Comparator.comparing(Employee::getSalary).reversed())
```

```
.forEach(System.out::println);
```

7.3 Sort by department then salary

```
employees.stream()  
    .sorted(Comparator.comparing(Employee::getDepartment)  
                .thenComparing(Employee::getSalary))  
    .forEach(System.out::println);
```

8 Limit & Skip

8.1 Top 2 highest paid

```
employees.stream()  
  
    .sorted(Comparator.comparing(Employee::getSalary).reversed())  
    .limit(2)  
    .forEach(System.out::println);
```

8.2 Skip first 2 employees (after sorting)

```
employees.stream()  
    .sorted(Comparator.comparing(Employee::getSalary))  
    .skip(2)  
    .forEach(System.out::println);
```

9 Distinct

9.1 Get distinct departments

```
employees.stream()  
    .map(Employee::getDepartment)  
    .distinct()  
    .forEach(System.out::println);
```

Matching Operations

10.1 Any employee earning above 200000?

```
boolean highEarner = employees.stream()
    .anyMatch(e -> e.getSalary() > 200000);
```

10.2 All employees earn above 50000?

```
boolean allAbove50k = employees.stream()
    .allMatch(e -> e.getSalary() > 50000);
```

10.3 None belong to HR?

```
boolean noHR = employees.stream()
    .noneMatch(e -> e.getDepartment().equals("HR"));
```

Find Operations (Optional Handling)

11.1 Find first Engineering employee

```
Optional<Employee> eng = employees.stream()
    .filter(e -> e.getDepartment().equals("Engineering"))
    .findFirst();

eng.ifPresent(System.out::println);
```

11.2 Find highest paid employee

```
Optional<Employee> maxEmp = employees.stream()
    .max(Comparator.comparing(Employee::getSalary));
```

Collectors

12.1 Collect to List

```
List<Employee> highEarners = employees.stream()
    .filter(e -> e.getSalary() > 100000)
    .collect(Collectors.toList());
```

12.2 Collect to Map (empCode → Employee)

```
Map<String, Employee> empMap = employees.stream()
    .collect(Collectors.toMap(Employee::getEmpCode, e -> e));
```

12.3 Group by Department

```
Map<String, List<Employee>> byDept =
    employees.stream()

    .collect(Collectors.groupingBy(Employee::getDepartment));
```

12.4 Count employees per department

```
Map<String, Long> countByDept =
    employees.stream()
        .collect(Collectors.groupingBy(
            Employee::getDepartment,
            Collectors.counting()));
```

12.5 Average salary per department

```
Map<String, Double> avgByDept =
    employees.stream()
        .collect(Collectors.groupingBy(
            Employee::getDepartment,
            Collectors.averagingDouble(Employee::getSalary)));
```

12.6 Partition by salary > 100000

```
Map<Boolean, List<Employee>> partition =
```

```
employees.stream()  
    .collect(Collectors.partitioningBy(  
        e -> e.getSalary() > 100000));
```

12.7 Join all employee names

```
String names = employees.stream()  
    .map(Employee::getFullName)  
    .collect(Collectors.joining(", "));
```

13 Reduce

13.1 Sum salaries using reduce

```
double sum = employees.stream()  
    .map(Employee::getSalary)  
    .reduce(0.0, Double::sum);
```

13.2 Highest salary using reduce

```
Optional<Employee> highest =  
    employees.stream()  
        .reduce((e1, e2) ->  
            e1.getSalary() > e2.getSalary() ? e1 : e2);
```

14 flatMap Example

Suppose each employee has multiple skills:

```
List<List<String>> skills = List.of(  
    List.of("Java", "Spring"),  
    List.of("Chemistry", "Lab"),  
    List.of("React", "Java"),  
    List.of("Process Design"),  
    List.of("Testing", "Automation"))
```



```
);  
  
skills.stream()  
    .flatMap(List::stream)  
    .distinct()  
    .forEach(System.out::println);
```

15 Parallel Stream

```
employees.parallelStream()  
    .map(Employee::getSalary)  
    .forEach(System.out::println);
```

⚠ Avoid parallel for small datasets.

16 Stream Pitfalls

1. Streams cannot be reused.
 2. Avoid side effects inside `forEach`.
 3. Handle Optional properly.
 4. `toMap()` needs merge function if keys duplicate.
 5. Parallel streams + mutable state = danger.
-

17 Advanced Challenge Tasks

1. Find 2nd highest salary.
2. Find department with highest average salary.

3. Create Map<Department, Set<Names>>.

Create summary statistics:

`DoubleSummaryStatistics`

- 4.
 5. Find employee with longest name.
 6. Check if all emails contain "@example.com".
 7. Convert employee list into JSON-like string using joining.
-

18 Summary of What This Workbook Covered

- ✓ filter
- ✓ map
- ✓ mapToDouble
- ✓ flatMap
- ✓ sorted
- ✓ limit
- ✓ skip
- ✓ distinct
- ✓ findFirst / findAny
- ✓ anyMatch / allMatch / noneMatch
- ✓ collect
- ✓ groupingBy
- ✓ partitioningBy
- ✓ joining
- ✓ reduce (all versions)
- ✓ Optional handling
- ✓ parallelStream
- ✓ summary statistics