

PRACTICAL-07

AIM:Implementation of making a change problem using dynamic programming

PROGRAM:

```
#include <iostream>

#include <vector>

#include <climits> using
namespace std;

int main() {
int n, amount;

    cout << "Enter number of coin denominations: ";
cin >> n;

    vector<int> coins(n);

    cout << "Enter coin denominations: ";
for (int i = 0; i < n; i++) {      cin >>
coins[i];
    }

    cout << "Enter amount: ";
cin >> amount;

    vector<int> dp(amount + 1, INT_MAX);
dp[0] = 0;


    for (int i = 1; i <= amount; i++) {
for (int coin : coins) {
```

```
if (coin <= i && dp[i - coin] != INT_MAX) {           dp[i] = min(dp[i], dp[i - coin] + 1);
    }
}
}

if (dp[amount] == INT_MAX)    cout << "It is not
possible to make the amount." << endl;
else
    cout << "Minimum number of coins required: " << dp[amount] << endl;

return 0;
}
```

OUTPUT:



```
Enter number of coin denominations: 3
Enter coin denominations: 23
21
Enter amount: 100
Minimum number of coins required: 8

*** Code Execution Successful ***
```

CONCLUSION:

Dynamic programming solves the making-change problem by storing the minimum coins needed for every amount from 0 to the target. This avoids repeated calculations and gives the minimum number of coins efficiently.