



# PAYE Modernisation

## REST Web Service Integration Guide

## Contents

Audience .....	4
Document context .....	4
<b>1. Introduction .....</b>	<b>5</b>
<b>2. Calling the Services .....</b>	<b>6</b>
2.1. REST Endpoints .....	6
2.1.1. Additional Information	8
2.2. Digital Signatures .....	8
<b>3. Interpreting the Responses .....</b>	<b>9</b>
3.1. Validation Errors .....	9
3.1.1. Request Validation	9
3.1.2. Line Item Validation	9
3.2. Lookup Revenue Payroll Notification (RPN) Web Service .....	10
3.3. New RPN Web Service .....	10
3.4. Payroll Submission Web Service .....	10
3.5. Check Payroll Submission Web Service .....	10
3.6. Check Payroll Run Web Service .....	10
3.7. Enhanced Reporting Submission Web Service .....	11
3.8. Check ERR Run Web Service .....	11
3.9. Check ERR Submission Web Service .....	11
3.10. Lookup ERN Web Service .....	11
<b>4. Digital Signatures .....</b>	<b>12</b>
4.1. HTTP Signatures .....	12
4.1.1. HTTP Signature Sample	12
4.1.2. HTTP Signature Components	12
4.1.3. Signature String Construction	13
4.1.4. Signature Creation	15
<b>5. Example Messages .....</b>	<b>15</b>
<b>Appendix A – Extracting from a .p12 File .....</b>	<b>15</b>

**Version**  
**Version Date**

**ERR Milestone 1**  
**04/05/2023**

Version History			
Version	Change Date	Section	Change Description
V 1.0 Milestone 1	17/11/2017	All	Document published.
			<b>Audience</b> and <b>Document Context</b> sections added.
			Link sources changed
	06/04/2018	4.1.3	Additional information added in relation to digest algorithms used for 'Digest' HTTP header.
1.0 Release Candidate 2	24/05/2018	4.1.3	Additional information added in relation to Content-Type for POST requests.
		2.1.1	HTTP request example Content-Type value changed from 'application/json;charset=UTF-8' to application/x-www-form-urlencoded
	19/06/2018	Payslip	Changed to 'Submission Item'
		4.1.3	(Request-target) updated
	20/07/2018	2.1.1	HTTP request example updated to include Digest and Signature elements.
	21/09/2018	2.1	Endpoints corrected from 'paye/employers' to 'paye-employers'
		4.1.3	Sample request-target corrected from 'softwareused' to 'softwareUsed'
	28/09/2018	4.1.3	Accepted Date formats added
	12/10/2018	4.1.3	Accepted Date specification updated
	22/11/2018	4.1.2	Specified digest field required for POST
	14/11/2018	2.1	Specified that Agent Tain is conditionally optional
	08/01/2019	4.1.3	Date timeout changed from 60 seconds to 90 minutes
	09/04/2019	4.1.3	Added example string to be signed.
	07/10/2019	2.1	Updated Example hyperlinks
ERR Milestone 1	06/04/2023	1, 2.1, 3.1, 3.7	Added Enhanced Reporting Web Service

	04/05/2023	1, 2.1, 3.8, 3.9	Added Enhanced Reporting Check Run and Check Submission Web Services
	04/05/2023	1, 2.1, 2.1.1, 3.10	Added Lookup ERN Web Service

### ***Audience***

This document is for any software provider who has chosen to build or update their products to allow for PAYE Modernisation.

### ***Document context***

This document provides a technical overview of how to integrate with Revenue's REST web services including how to sign requests validly. This document is designed to be read in conjunction with the REST/JSON example files as well as the rest of the Revenue Commissioners' PAYE Modernisation documentation suite including the relevant technical documents.

Document References	
Reference	Document Link
1. Documents Homepage	<a href="#">Documents Homepage</a>

### 1. Introduction

This document details the REST PAYE Modernisation web services specification for the following web services:

- Lookup Revenue Payroll Notification (RPN) by Employer web service
- Lookup Revenue Payroll Notification (RPN) by Employee web service
- New RPN web service
- Payroll Submission web service
- Check Payroll Submission web service
- Check Payroll Run web service
- Enhanced Reporting Submission web service
- Enhanced Reporting Check Run web service
- Enhanced Reporting Check Submission web service
- Lookup Enhanced Reporting Request (ERN) web service

The Documents Homepage specified in [Document References](#) is the home to all technical documentation, specification, and examples for the above web services which has been made available to enable payroll software developers' to update their software packages to be compatible with PAYE reporting obligations from January 2019. Path locations specified in this document are relative to this Homepage.

This document assumes familiarity with the REST web services above. A full description of each of these can be found in the 'PAYE Modernisation Description Of Web Service Examples' Document under 'PAYE Web Service Examples' on the Documents Homepage.

The OpenAPI Specification, originally known as the Swagger Specification, is a specification for machine-readable interface files for describing, producing, consuming, and visualizing RESTful Web services. The specification can be described using the YAML or JSON format. Revenue provides the specification in JSON format or, alternatively, it can be viewed using the ReDoc UI framework. The JSON file can be downloaded and imported into any Open API UI framework such as the Swagger UI framework. Links are provided for both the JSON format file and the ReDoc UI framework under 'PAYE Web Service Specifications (REST/JSON)' on the Documents Homepage. The URL for each web service will use the HTTPS protocol to ensure the privacy of all communication between ROS and the web service client.

## 2. Calling the Services

The web services for the PAYE Modernisation messages are described in the REST OpenAPI Specification JSON file provided under 'PAYE Web Service Specifications (REST/JSON)' on the Documents Homepage.

The OpenAPI, REST Security version specifications we are following include:

Open API Specification Version 3.0: <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>

HTTP Signatures Version 08: <https://tools.ietf.org/html/draft-cavage-http-signatures-08>

### 2.1. REST Endpoints

The PAYE Modernisation web service endpoints are detailed below.

Description	HTTP Method	Endpoint URL	Additional Information	Links
* Look Up RPN By Employer and optionally filter by date last updated and/or employee id's web service	GET	<a href="https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}">https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}</a>	Query Parameters <ul style="list-style-type: none"> <li>softwareUsed</li> <li>softwareVersion</li> <li>AgentTain (optional*)</li> <li>employeeIDs (optional)</li> <li>dateLastUpdated (optional)</li> </ul>	<a href="#">lookUpRPNByEmployer</a>
Lookup RPN by Employee web service	GET	<a href="https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}/{employeeid}">https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}/{employeeid}</a>	Query Parameters <ul style="list-style-type: none"> <li>softwareUsed</li> <li>softwareVersion</li> <li>AgentTain (optional*)</li> </ul>	<a href="#">lookUpRPNByEmployee</a>
New RPN web service	POST	<a href="https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}">https://www.ros.ie/payee-employers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear}</a>	Query Parameters <ul style="list-style-type: none"> <li>softwareUsed</li> <li>softwareVersion</li> <li>AgentTain (optional*)</li> </ul>	<a href="#">createNewRPN</a>
Payroll Submission web service	POST	<a href="https://www.ros.ie/payee-employers/v1/rest/payroll/{employerRegistrationNumber}">https://www.ros.ie/payee-employers/v1/rest/payroll/{employerRegistrationNumber}</a>	Query Parameters <ul style="list-style-type: none"> <li>softwareUsed</li> <li>softwareVersion</li> </ul>	<a href="#">createPayrollSubmission</a>

## REST Web Service Integration Guide

		r}/{taxYear}/{payrollRunReference}/{submissionID}	<ul style="list-style-type: none"> <li>○ AgentTain (optional*)</li> </ul>	
Check Payroll Submission web service	GET	https://www.ros.ie/pay-employers/v1/rest/payroll/{employerRegistrationNumber}/{taxYear}/{payrollRunReference}/{submissionID}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> </ul>	<a href="#">checkPayrollSubmissionComplete</a>
Check Payroll Run web service	GET	https://www.ros.ie/pay-employers/v1/rest/payroll/{employerRegistrationNumber}/{taxYear}/{payrollRunReference}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> </ul>	<a href="#">checkPayrollRunComplete</a>
Enhanced Reporting Submission web service	POST	https://www.ros.ie/pay-employers/v1/rest/enhanced_reporting/{employerRegistrationNumber}/{taxYear}/{enhancedReportingRunReference}/{submissionID}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> </ul>	<a href="#">submitEmployerReportingSubmission</a>
Check ERR Submission web service	GET	https://www.ros.ie/pay-employers/v1/rest/enhanced_reporting/{employerRegistrationNumber}/{taxYear}/{runReference}/{submissionID}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> </ul>	<a href="#">checkEnhancedReportingRequirementsSubmission</a>
Check ERR Run web service	GET	https://www.ros.ie/pay-employers/v1/rest/enhanced_reporting/{employerRegistrationNumber}/{taxYear}/{runReference}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> </ul>	<a href="#">checkEnhancedReportingRequirementsRun</a>

* Look Up ERN web service	GET	https://www.ros.ie/payemployers/v1/rest/ern/{employerRegistrationNumber}/{taxYear}	Query Parameters <ul style="list-style-type: none"> <li>○ softwareUsed</li> <li>○ softwareVersion</li> <li>○ AgentTain (optional*)</li> <li>○ PPSNs</li> </ul>	<a href="#">lookUpERN</a>
---------------------------	-----	--	--	---------------------------

\*Agent Tain is conditionally optional. It is required when using an Agent Cert

### 2.1.1. Additional Information

\* If large amounts of employee Id's are being looked up in one request, there is the possibility of URL truncation. In this case integrators should switch from GET to POST, use the 'X-HTTP-Method-Override' HTTP header and use 'Content-Type=application/x-www-form-urlencoded' when calling the https://www.ros.ie/payemployers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear} endpoint or the https://www.ros.ie/payemployers/v1/rest/rpn/{employerRegistrationNumber}/{taxYear} endpoint.

Although the 'X-HTTP-Method-Override' HTTP header is not currently a standard, this is the approach taken by Google for the Google Data API. The X-HTTP-Method-Override header tells the PAYE Modernisation API to treat the request as a GET request, even though it is being conducted as a POST request.

The 'Content-Type' header must be set to 'application/x-www-form-urlencoded' and the request body must meet the 'application/x-www-form-urlencoded' standard. See below HTTP request example

```
POST v1/rest/rpn/0000001W/2019/1/1?agentTain=11221w&softwareUsed=SoftwareXYZ
&softwareVersion=1.0 HTTP/1.1
Host: www.ros.ie
Date: Wed Oct 04 16:35:51 BST 2017
Content-Type: application/x-www-form-urlencoded
X-HTTP-Method-Override: GET
Digest: 1fNNQYeUZW2laoZkOF4ssnkzFJ83MRsz4H+fIpLrIvkBH0Zdy2G85OQSYGoHRqvyL6jVn8xJW
0pW91/AYV6FEpw==
Signature: keyId="MIIEmTCCA4GgAwIBAgIRA0zckV67HlvuS0..." //truncated
```

```
// Request Body
employeeIDs={employmentID-1}&employeeIDs={employmentID-2}&employeeIDs={
employmentID-3}
```

### 2.2. Digital Signatures

The PAYE Modernisation web services will require a digital signature. This will be the digital signature of the declarant.



### 3. Interpreting the Responses

Each web service will return a response message to the client as outlined below.

#### 3.1. Validation Errors

##### 3.1.1. Request Validation

When a request is made to a PAYE Modernisation web service three checks are carried out before any processing can occur. These include:

1. Authentication
2. Authorisation
3. JSON API validation

Step 1 of the validation process tries to verify the authenticity of the message by checking it has been signed with a valid digital signature. Step 2 focuses on authorising the credentials and finally, step 3 checks the message is valid using JSON API validation.

If there are any errors encountered during the above processes, the response will include a HTTP status code of either 401 (Unauthorised) if authentication fails, 403 if authorisation fails and 400 (Bad Request) if JSON API validation fails. The message body will provide more information on the details of the problem. Where an error code is returned to the client, no processing will occur for that message.

If the message passes JSON API validation, authentication, and authorisation but the resource cannot be found the response will include a HTTP status code of 404. If the resources query parameters are not as required or are missing, the response will include a HTTP status code of 400. Where an error code is returned to the client, no processing will occur for that message.

##### 3.1.2. Line Item Validation

Once the message passes JSON API validation, authentication, and authorisation, lower level line item validation is carried out on the following requests:

- Lookup RPN
- New RPN
- Payroll Submission Request
- Enhanced Reporting Submission Request
- Lookup ERN

A successful response is sent back to the client, detailing any validation errors that occurred on the request. The code i.e. the technical error code used for mapping to the error message, the path to the error in the schema and the description of the error is detailed in the response.

A list of all validation rules carried out for each request can be found in the Validation Rules document on the [Documents Homepage](#) under 'Supporting Documentation'.

### **3.2. Lookup Revenue Payroll Notification (RPN) Web Service**

The “Lookup RPN by Employer”, “Lookup RPN by Employee” and “Lookup RPN using multiple Employee Id’s” web service Response will return the most up to date RPN details for employees listed in the request, if the employee has an RPN associated with the employer. Employees that do not have an RPN associated with the employer are returned in the response with no RPN details. A New RPN needs to be requested for these employees using the New RPN Request Web Service.

A list of validation errors (if any) on the Lookup RPN Request is also included in the response. Please refer back to [Section 3.1](#) for more information on Validation Errors.

### **3.3. New RPN Web Service**

The Employer’s New RPN response will return new RPN details for the employees requested (there is an upper limit of 1,000 PPSNs per request). PPSN and Employment ID of employees are returned with no RPN details where new RPN details could not be created.

A list of validation errors (if any) on the New RPN Request is also included in the response.

### **3.4. Payroll Submission Web Service**

The Payroll Submission response returns an acknowledgement status for the Employer’s PAYE Payroll Submission Request.

If validation failed a list of the Submission validation errors are returned in this response.

### **3.5. Check Payroll Submission Web Service**

Check Payroll Submission will return the current status of an employer’s PAYE payroll submission. The possible status values are Pending or Completed.

If the status is completed, the response includes summary totals of valid submission items. If the status is pending the response does not contain any summary totals. Validation errors for any invalid submission items are listed as well as any validation errors on the Check Payroll Submission Request. Invalid submission items are not saved therefore their amounts do not feed into the employer liability.

### **3.6. Check Payroll Run Web Service**

Check Payroll Run will return the current status of an Employer’s PAYE payroll run. The possible status values are Pending or Processed. If any submissions making up the payroll run are at a status of Pending then the status of the payroll run response will also be at Pending.

If the status is Processed the response includes a list of submissions that make up the payroll run and includes summary details of all processed submissions.

A list of validation errors (if any) on the Check Payroll Run Request is also included in the response.

### ***3.7. Enhanced Reporting Submission Web Service***

The Enhanced Reporting Submission response returns an acknowledgement status for the Employer's PAYE Enhanced Reporting Submission Request.

If validation failed a list of the Submission validation errors are returned in this response.

### ***3.8. Check ERR Run Web Service***

Check ERR Run will return the current status of an Employer's ERR run. The possible status values are Pending or Processed.

If the status is Processed the response includes a list of submissions that make up the ERR run and includes summary details of all processed submissions.

A list of validation errors (if any) on the Check ERR Run Request is also included in the response.

### ***3.9. Check ERR Submission Web Service***

Check ERR Submission will return the current status of an employer's PAYE ERR submission. The possible status values are Pending or Completed.

If the status is completed, the response includes summary totals of valid submission items. If the status is pending the response does not contain any summary totals. Validation errors for any invalid submission items are listed as well as any validation errors on the Check ERR Submission Request.

### ***3.10. Lookup ERN Web Service***

The Employer's Lookup ERN Response will return the most up to date ERN details for those employees listed in the request.

### 4. Digital Signatures

Any ROS web service request that either returns confidential information or accepts submission of information must be digitally signed. This must be done using a digital certificate that has been previously retrieved from ROS.

The digital signature must be applied to the message in accordance with the HTTP Signatures specification as specified in [Section 4.1](#).

The digital signature ensures the integrity of the document. By signing the document we can ensure that no malicious intruder has altered the document in any way. It can also be used for non-repudiation purposes.

If a valid digital signature is not attached, a HTTP status code of 401 (Unauthorised) will be returned. The message body will provide more information on the details of the problem.

#### 4.1. HTTP Signatures

The HTTP signatures protocol is intended to provide a simple and standard way for clients to sign HTTP requests. A summary of the structure of a HTTP Signature is outlined below. This is a simplified explanation of the HTTP Signatures specification. The full specification can be found at [Signing HTTP Messages](#) and should be read in full. The specification defines two approaches to building a HTTP signature, [“The 'Signature' HTTP Authentication Scheme”](#) and [“The 'Signature' HTTP Header”](#), Revenue uses the latter.

At a high level, a HTTP Signature is a HTTP header that is added to a HTTP request. It is comprised of a set of components that were used to generate a digital signature and the digital signature itself.

##### 4.1.1. HTTP Signature Sample

Below is a sample HTTP Signature header.

```
Signature: keyId="MIICfzCCAeigAwIBAgIJ... // truncated",
algorithm="rsa-sha512",
headers="(request-target) host date digest",
signature="GdUqDgy94Z8mSYUjr/rL6qrLX/jmudS... // truncated"
```

##### 4.1.2. HTTP Signature Components

The Signature HTTP header contains four components, keyId, algorithm, headers and signature. Below is a description of each.

**keyId:** The keyId field must contain a Base64 encoded version of the X509 certificate that accompanies the private key used to sign the message. This field is required.

**algorithm:** The `algorithm` parameter is used to specify the digital signature algorithm to use when generating the signature. Revenue expects this to be `rsa-sha512`. This field is required.

**headers:** The `headers` parameter specifies the list of headers used when generating the signature for the message. The parameter must be a lowercased, quoted list of HTTP header fields, separated by a single space character. The list order is important, and **MUST** be specified in the order the HTTP header field-value pairs are concatenated together during signing. For POST requests, the digest field must be included.

**signature:** The signature component is a base 64 encoded digital signature. The implementer uses the `algorithm` and `headers` field to form a canonicalized `signing string`. This `signing string` is then signed with the private key that accompanies the X509 certificate associated with the `keyId` field and the algorithm corresponding to the `algorithm` field. The `signature` field is then base 64 encoded.

### 4.1.3. Signature String Construction

In order to generate the string to be signed, the implementer **MUST** use the values of each HTTP header defined in the `headers` signature field, to build the signature string. Values must be in the order they appear in the `headers` signature field. If the associated HTTP header does not exist, it should be added to the HTTP request **BEFORE** attempting to construct this string.

#### Date:

The GMT time zone is enforced. Requests expire after 90 minutes has elapsed based on the timestamp received on the date/x-date header. Requests made up to 90 minutes before the revenue server time are also accepted to counteract the potential for server time discrepancies and daylight savings. For example:

A message with the timestamp in ISO\_8601 ("yyyy-MM-dd'T'HH:mm:ss.SSSX") format is received as follows:

2018-01-01T12:00:00.000Z

This message is valid for 90 minutes either side of it.

i.e. from 2018-01-01T10:30:00.000Z to 2018-01-01T13:30:00.000Z

Values for days and months should be two digits. As such, in the case where either the day or the month is a single digit, such as 2018-1-1, the single digit value should be prepended with a zero to make it 2018-01-01.

- The accepted formats for date are:
  - ISO 8601
  - RFC 822, updated by RFC 1123
  - RFC 850, obsoleted by RFC 1036
  - ANSI C's time format

Allowable values in the headers field are outlined in the table below.

Value	Mandatory
* (request-target)	Yes

host	Yes
date	Yes
** x-date	Yes, if date header cannot be added.
*** digest	Yes, if HTTP method is of type POST
**** content-type	No
content-length	No
x-http-method-override	If HTTP method is of type POST, HTTP header 'X-HTTP-Method-Override' exists and 'Content-Type=application/x-www-form-urlencoded'. See <a href="#">Section 2.1.1</a> for more detail.

\* The `(request-target)` header field is a special header field in that its value is comprised of 2 HTTP headers. It is generated by concatenating the lowercase HTTP method, an ASCII space, and the request path headers. See below for sample

`(request-target): post /paye-employers/v1/rest/rpn/{ employerRegistrationNumber }/{taxYear}?softwareUsed=XYZ&softwareVersion=1.0`

\*\* The 'x-date' headers field value should ONLY be used in conjunction with the X-Date HTTP header if a Date HTTP header cannot be added to the HTTP request programmatically. The Date header has a limitation when using javascript in a browser to build and send a HTTP signature. The limitation is that you cannot add a 'Date' HTTP header when executing javascript in a browser. The native XMLHttpRequest object prohibits addition of a 'Date' HTTP header. Building the signature string that will be signed with an 'x-date' header instead of a 'date' header removes this restriction.

\*\*\* The 'Digest' HTTP header is created using the POST body/payload. The payload should be converted to a byte array, hashed using the SHA-512 algorithm and finally base64 encoded before adding it as a HTTP header.

\*\*\*\* Although Content-Type does not have to be part of the Signature string, it is required as a HTTP Header if HTTP Method Type is POST. If the request is a standard POST (i.e. not a header 'X-HTTP-Method-Override' POST, then the Content-Type should be set to 'application/json' or 'application/json; charset=UTF-8'

All other header field values are created by concatenating the lowercase header field name followed by an ASCII colon `:`; an ASCII space ` `, and the header field value. Leading and trailing whitespace in the header field value MUST be omitted. If the header field is not the last value defined in the `headers` signature field, then append an ASCII newline `\n`. See sample below.

`(request-target): get /paye-employers/v1/rest/rpn/{employerReg}/{taxYear}?softwareUsed=XYZ&softwareVersion=1.0`  
`host: softwaretestnextversion.ros.ie`

date: yyyy-MM-ddTHH:mm:ss.SSSX  
content-type: application/json; charset=utf-8

### 4.1.4. Signature Creation

The signature component is a base 64 encoded digital signature. The implementer uses the `algorithm` and constructed Signature String. The Signature String is signed with the private key that accompanies the X509 certificate associated with the `keyId` field and the algorithm corresponding to the `algorithm` field. The `signature` field is then base 64 encoded.

## 5. Example Messages

There is an adjoining file 'REST\_Web\_Service\_Integration\_Guide\_Sample\_Http\_Messages.txt' that contains HTTP Request/Response samples describing the structure of the request and outlining the possible responses a client can expect. Monetary figures in all examples are for illustrative purposes only.

## Appendix A – Extracting from a .p12 File

Each customer of ROS will have a digital certificate and private key stored in an industry standard PKCS#12 file.

In order to create a digital signature, the private key of the customer must be accessed. A password is required to retrieve the private key from the P12 file. This password can be obtained by prompting the user for their password.

The password on the P12 is not the same as the password entered by the customer. It is in fact the MD5 hash of that password, followed by the Base64-encoding of the resultant bytes.

To calculate the hashed password, follow these steps:

1. First get the bytes of the original password, assuming a "Latin-1" encoding. For the password "Password123", these bytes are: 80 97 115 115 119 111 114 100 49 50 51 (i.e. the value of "P" is 80, "a" is 97, etc.).
2. Then get the MD5 hash of these bytes. MD5 is a standard, public algorithm. Once again, for the password "Password123" these bytes work out as: 66 -9 73 -83 -25 -7 -31 -107 -65 71 95 55 -92 76 -81 -53.
3. Finally, create the new password by Base64-encoding the bytes from the previous step. For example, the password, "Password123" this is "QvdJref54ZW/R183pEyyvw==".

This new password can then be used to open a standard ROS P12 file.