

Q1 to Q11 have only one correct answer. Choose the correct option to answer your question.

1. Movie Recommendation systems are an example of:

- i) Classification
- ii) Clustering
- iii) Regression

Options:

- a) 2 Only
- b) 1 and 2
- c) 1 and 3
- d) 2 and 3

ANS: a)2 only

2. Sentiment Analysis is an example of:

- i) Regression
- ii) Classification
- iii) Clustering
- iv) Reinforcement

- Options:
- a) 1 Only
 - b) 1 and 2
 - c) 1 and 3
 - d) 1, 2 and 4

ANS: d)1,2 and 4

3. Can decision trees be used for performing clustering?

- a) True
- b) False

ANS: a)True

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points:

i) Capping and flooring of variables

ii) Removal of outliers

- Options:
- a) 1 only
 - b) 2 only
 - c) 1 and 2
 - d) None of the above

ANS: a) 1 only

5. What is the minimum no. of variables/ features required to perform clustering?

- a) 0
- b) 1
- c) 2
- d) 3

ANS: b) 1

6. For two runs of K-Mean clustering is it expected to get same clustering results?

- a) Yes
- b) No

ANS: b) No

7. Is it possible that Assignment of observations to clusters does not change between successive iterations in K-Means?

- a) Yes
- b) No
- c) Can't say
- d) None of these

MACHINE LEARNING

8. Which of the following can act as possible termination conditions in K-Means?
- i) For a fixed number of iterations.
 - ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
 - iii) Centroids do not change between successive iterations.
 - iv) Terminate when RSS falls below a threshold. Options:
 - a) 1, 3 and 4
 - b) 1, 2 and 3
 - c) 1, 2 and 4
 - d) All of the above

ANS: d) All of the above

9. Which of the following algorithms is most sensitive to outliers?
- a) K-means clustering algorithm
 - b) K-medians clustering algorithm
 - c) K-modes clustering algorithm
 - d) K-medoids clustering algorithm

ANS: a

10. How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):
- i) Creating different models for different cluster groups.
 - ii) Creating an input feature for cluster ids as an ordinal variable.
 - iii) Creating an input feature for cluster centroids as a continuous variable.
 - iv) Creating an input feature for cluster size as a continuous variable. Options:
 - a) 1 only
 - b) 2 only
 - c) 3 and 4
 - d) All of the above

ANS : d)

11. What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?
- a) Proximity function used
 - b) of data points used
 - c) of variables used
 - d) All of the above

ANS: d

Q12 to Q14 are subjective answers type questions, Answers them in their own words briefly

12. Is K sensitive to outliers?

Sol: The *K*-means clustering algorithm is sensitive to outliers, because a mean is easily influenced by extreme values. *K*-medoids clustering is a variant of *K*-means that is more robust to noises and outliers. Instead of using the mean point as the

center of a cluster, *K*-medoids uses an actual point in the cluster to represent it. Medoid is the most centrally located object of the cluster, with minimum sum of distances to other points.

13. Why is K means better?

Sol:

- Relatively simple to implement.
- Scales to large data sets.
- Guarantees convergence.
- Can warm-start the positions of centroids.
- Easily adapts to new examples.
- Generalizes to clusters of different shapes and sizes, such as elliptical clusters.

14. Is K means a deterministic algorithm?

Sol: This is non-deterministic nature of algorithms such as the K-Means clustering algorithm limits their applicability in areas such as cancer subtype prediction using gene expression data. It is hard to sensibly compare the results of such algorithms with those of other algorithms. The non-deterministic nature of K-Means is due to its random selection of data points as *initial centroids*.