


CNG Solutions – Range Comparison

Compare CNG dispensers, the daughter station and storage tubes at a glance

CNG DISPENSERS

Shared across this group: Refilling dispensers: 2–30 kg/min · $\pm 0.5\%$ accuracy · up to 25 MPa. The three configurations differ by nozzle count and body design only. The Offloading Dispenser is a different product with its own flow and accuracy figures, shown separately.

Photo	Product	Key specifications
	CNG Dispenser – Single Nozzle	Nozzle: Single (serves one vehicle at a time)
	CNG Dispenser – Double Nozzle	Nozzle: Double (serves two vehicles at once)
	CNG Dispenser – Double Nozzle (2)	Nozzle: Double, alternative body design, same performance. Choose based on your station's layout and look.
	CNG Offloading Dispenser	Flow: 1–70 kg/min · Accuracy: $\pm 1\%$ For bulk transfer into station storage, not customer refuelling

CNG DAUGHTER STATION & STORAGE

**CNG Daughter Station**

Compressor: 1200 Nm³/h, 380V · Cylinder group: 180L × 36 (6,480L)

Complete pipeline-independent system: receives, stores and dispenses

**CNG Storage Tubes (40ft)**

Capacity: up to 7,800 Nm³ · Working pressure: 20–25 MPa
20-year working life

Ready to talk through your requirement? Message or call our team on [+234 904 315 4982](tel:+2349043154982). We reply within 24 hours.
No pressure to buy, just honest, straightforward advice from our team.