

MT PLUS – Double Nozzle (TB-D1)

Double-nozzle fuel dispenser · Bennett meter, Tokheim unit



NMDPRA-compliant



Calibrated before delivery



Assembled & tested in Nigeria



Spare parts always available

Our most popular double-nozzle dispenser, and it earns that spot every day on Nigeria's busiest forecourts. The MT Plus Double (TB-D1) serves two vehicles at once with two Bennett meters and a shared Tokheim unit, cutting queue time and moving more fuel without compromising accuracy. Calibrated to $\pm 0.3\%$, assembled and tested in Nigeria, and backed by spare parts that are always available.

Compatible fuels

PMS, AGO or DPK

TECHNICAL PARAMETERS		OPERATING CONDITIONS	
Nozzle	2	Flow rate	5 to 50 L/min
Hose	2	Meter accuracy	$\pm 0.3\%$
Display	4	Working pressure	0.3 MPA
Product suction	2	Suction distance	Min 30m · Max 35m
Bennett meter	2	Ambient temperature	-20°C to +80°C
Tokheim unit	1	Relative humidity	45% – 85%
Electric motor	1	Noise	Very low, under 72 dB

SPECIFICATIONS

Nozzle	O.P.W 1" · blue or red guard
Hose	4m flexible, wire reinforced, oil resistant, 1" dia.
Hose hanger	Attached to the frame, retractable
Control valve	In-line valves
Meter	4-piston positive displacement · aluminium alloy frame
Pump unit	Self-priming gear pump with oil separator and air eliminator
Electric motor	Single phase, flame proof, 220V 50Hz 1kW
Totalizer	Electronic / mechanical, visible from outside
Frame	White (other colours available on request)
Money calculating range	000-00009999.99 MU
Register range	000-00009999.99 / L
Unit price setting range	000-0009999.99 / L
Totalizer range	0.009,999,999.99 L
Memory storage & backup	10-minute backup · over 7 years memory storage
Security	Electronic
Manual	Maintenance and installation included

Ready to order, or need advice? Message or call our technical team on **+234 904 315 4982**. We reply within 24 hours. No pressure to buy, just honest, straightforward advice from our team.