

MT PRO – Double Nozzle (TB-D2)

Double-nozzle fuel dispenser · Bennett meter, Tokheim unit



NMDPRA-compliant



Calibrated before delivery



Assembled & tested in Nigeria



Spare parts always available

A dependable double-nozzle dispenser built on a Bennett meter with a Tokheim unit in the refined MT Pro body. It serves two vehicles at once, keeping busy forecourts moving. Two meters and two units give each side fully independent metering for maximum throughput. Calibrated to $\pm 0.3\%$ before delivery, assembled and tested in Nigeria on openly available components, and serviceable by any engineer nationwide, so spare parts are never a problem.

Compatible fuels

PMS, AGO or DPK

TECHNICAL PARAMETERS		OPERATING CONDITIONS	
Nozzle	2	Flow rate	5 to 50 L/min
Hose	2	Meter accuracy	$\pm 0.3\%$
Display	4	Working pressure	0.3 MPA
Product suction	2	Suction distance	Min 30m · Max 35m
Bennett meter	2	Ambient temperature	-20°C to +80°C
Tokheim unit	2	Relative humidity	45% – 85%
Electric motor	2	Noise	Very low, under 72 dB

SPECIFICATIONS

Nozzle	O.P.W 1" · blue or red guard
Hose	4m flexible, wire reinforced, oil resistant, 1" dia.
Hose hanger	Attached to the frame, retractable
Control valve	In-line valves
Meter	4-piston positive displacement · aluminium alloy frame
Pump unit	Self-priming gear pump with oil separator and air eliminator
Electric motor	Single phase, flame proof, 220V 50Hz 1kW
Totalizer	Electronic / mechanical, visible from outside
Frame	White (other colours available on request)
Money calculating range	000-00009999.99 MU
Register range	000-00009999.99 / L
Unit price setting range	000-0009999.99 / L
Totalizer range	0.009,999,999.99 L
Memory storage & backup	10-minute backup · over 7 years memory storage
Security	Electronic
Manual	Maintenance and installation included

Ready to order, or need advice? Message or call our technical team on **+234 904 315 4982**. We reply within 24 hours. No pressure to buy, just honest, straightforward advice from our team.