HTML Elements

<html> - Defines you are creating an html page

<head> - Where information that will not be displayed on your site is stored. Ex: Meta tag, title tags, link tags (CSS, Javascript)

<body> - Content that will be seen in a browser are within the body tag

Block Elements:

<header> - Used for your displaying header

<nav> - Used for your navigation

<main> - Main content area

<footer> - Footer content area

<section> - Used to divide content into sections

 - Used to divide content areas

<h1>-<h6> - Used for text headings. Size will vary based on what number you use (1-6)

<p> - Paragraph tag

<ol> - Ordered list - 1,2,3,4 etc

<ul> - Unordered list - Bullet points

<li> - List items - Used within an <ol> or <ul> ex: <ul><li>Content Here</li></ul>

<dl> - Description List

<dt> - Description Title

<dd> - Description Data

Inline Elements:

<img> - Display an images ex: <img src="folder/filename.jpg" alt="description">

<a> - Used to create a link ex: <a href="path/for/link.html">Text or Image here</a>

<b> - Bold

 - Break tag. Does not need a closing tag

<blockquote> - Indicates that a paragraph of text is a quote from another source

 - Emphasize tag. Similar to italics tag

<i> - Italics

<input> - Used in a web form to collect data

<label> - Create labels and associate them with other elements

<small> - Creates small text

 - Inline container

 - Bolds text

<sub> - Sub script

<sup> - Super script

<textarea> - Used in forms. Similar to input tag, but give more room to add paragraphs of text

<time> - Defines a specific time

CSS Rules

This is called a CSS Rule:

h1 { - this is the selector

font-size:24px; - this is the declaration, with font-size being the declaration property and 24px being the declaration value.

}

Classes are referenced by using a period

Ex:

.myclass {
Some declaration
}

ID's are referenced by using a #

Ex:

#myid {
some declaration
}

DECLARATIONS

color:#ffffff; - Changes the color of text. Can use #FFFFFF, rgb(255, 255, 255), rgba(255,255,255,0.3), hsl(120, 100%, 50%), hsla(120, 100%, 50%, 0.3) rgb(0, 255, 0)

background-color:#ffffff; - Changes the color of the background

background-image:url("images/image.jpg"); - Adds an image to the background of the sector. Can also use gradients. Ex: background-image: linear-gradient(to bottom, #eeeeee, #FFFFFF);

background-position: center; - Sets the starting position of a background image. Can be left, right, top, bottom, center, %, xpos or ypos.

background-repeat: no-repeat; - Sets if/how a background image will be repeated. Values can be repeat, no-repeat, repeat-x, repeat-y, space or round.

background-size: cover; - Specifies the size of the background images. Values can be auto, length (200px), %, cover, contain.

background-attachment: fixed; - Sets whether a background image scrolls with the rest of the page, or is fixed.

font-size: 1rem; - Controls the font size of the selector. Popular units of measure: px, em, rem, vh, %

font-family: verdana, “Times New Roman”, sans-serif; - specifies the font of an element

font-weight: bold; - Sets the boldness of the text

width: 100%; - controls the width of the sector (doesn't with with inline elements)

height: 100px; - controls the height of the sector (doesn't with with inline elements)

padding: 2px 3px 4px 5px; - controls the padding around the content of a selector. Works like a clock, top, right, bottom, left. Can also use padding-top, padding-right, padding-bottom, padding-left.

margin: 2px 3px 4px 5px; - controls the margins around an element. Works like a clock, top, right, bottom, left. Can also use margin-top, margin-right, margin-bottom, margin-left.

box-sizing: border-box; - defines how the width and height of an element are calculated: should they include padding and borders, or not. Values can be content-box or border-box.

position:relative; - specifies the type of positioning method used for an element. Values can be static, relative, absolute, fixed or sticky). Relative positioning is positioned relative to its normal position. Absolute positions is positioned relative to its first positioned ancestor element. Fixed positioning is positioned relative to the browser window. Sticky positioning is positioned based on the user’s scroll position.

display:block; - Specifies the display behavior (the type of rendering box) of an element. Values can be inline, inline-block, flex, grid. Give you the ability to change a block tag to an inline tag, or an inline tag to a block tag.

list-style-type:none; - Specifies the type of list-item marker in a list. An example would be to change the unordered list bullet point to a square or to not display at all.

float:left; - specifies how an element should float. Values can be none, left, right. Ex: if you applied a float left to an image, that would float to the left of your website.

clear:both; - specifies on which sides of an element floating elements are not allowed to float. You almost always want to make sure you use clears after you use floats. Values can be none, left, right, both.

opacity:0.5; - Controls the opacity of an element.

Flex Box

display:flex; - Changes element into flexbox.

flex-direction: - Specifies the direction of the flexible items

flex-wrap: wrap; - Specifies whether the flexible items should wrap or not.

flex-flow: row nowrap; - shorthand property for flex-direction and flex-wrap

flex-grow: 1; - Specifies how much the item will grow relative to the rest of the flexible items inside the same container.

flex-shrink: 2; - Specifies how the item will shrink relative to the rest of the flexible items inside the same container.

flex-basis: 100px; - Specifies the initial length of a flexible item.

Grid

display:grid – Change element into grid

grid-template-columns: minmax(0, 1fr) repeat(6, minmax(0, 200px)) minmax(0, 1fr); - Specifies the number (and the widths) of columns in a grid layout. Can set a minmax and repeat. Fr stand for fraction.

grid-template-rows: auto auto; Specifies the number (and the heights) of the rows in a grid layout.

grid-auto-rows: 150px; - Sets a size for the rows in a grid container

grid-area: 2 / 1 / 2 / 3; - Specifies a grid item’s size and location in a grid layout, and is a shorthand property for the following: grid-row-start, grid-column-start, grid-row-end, grid-column-end.

grid-column: 1 / -1; - Specifies a grid item’s size and location in a grid layout.

grid-row: 1 / 2; Specifies a grid item’s size and location in a grid layout.

grid-gap: 50px; - Defines the size of the gap between the rows and columns in a grid layout.