

Replication 2026

Download the employee_burnout_turnover_prediction.zip from Canvas. Use mongoimport command to import the data into the employee_burnout collection of the employeesdb database with the following syntax:

```
C:\Users\jing>C:\Users\jing\Downloads\mongodb-database-tools-windows-x86_64-100.14.0\mongodb-database-tools-windows-x86_64-100.14.0\bin\mongoimport.exe --db=employeesdb --collection=employee_burnout --file=C:\Users\jing\Dropbox\cit\nosql\dataset\synthetic-employee-dataset.json --jsonArray
```

Complete the following tasks and screenshot each command and its output.

Stress level: high -> 76% – 100%

medium -> 51% – 75%

low -> 26% – 50%

resting -> 0% – 25%

Burnout risk level: high -> 76% - 100%

moderate -> 50% - 75%

low -> 0% - 49%

Task

We plan to build a data center in Cork to store the burnout and stress data for the above employees. This data center has 5 nodes in a PSA architecture. Create a replica set for this data center. This replica set should be named according to the location of this data center. To ease the whole task, keep all replica sets in the minimum recommended configuration.

1. Create this replica set manually, then take a screenshot of every step you perform in the process. You need to import your dataset into the primary node in the replica set.
2. With the replica set you have just created, explain how this replica set behaves in terms of automated failover and how to increase the size of each oplog to 25Gb.
3. How do you verify and globally reconfigure the write operation so that it is completed with two data-bearing members before returning? How do you reconfigure the read operation so that the replica set returning the most recent data when we perform a read operation?
4. How to support geographically local read operations in this replica set?
5. How do you remove this replica set for this data centre?