

# RWorksheet\_Salinas#4c.Rmd.

Reysa Marie S. Salinas

2023-11-22

1. a. Show your solutions on how to import a csv file into the environment.

```
library(readr)
mpg <- read_csv("mpg.csv")
```

```
## New names:
## Rows: 234 Columns: 12
## -- Column specification
## ----- Delimiter: "," chr
## (6): manufacturer, model, trans, drv, fl, class dbl (6): ...1, displ, year,
## cyl, cty, hwy
## i Use `spec()` to retrieve the full column specification for this data. i
## Specify the column types or set `show_col_types = FALSE` to quiet this message.
## * `` -> `...1`
```

```
head(mpg)
```

```
## # A tibble: 6 x 12
##   ...1 manufacturer model displ year   cyl trans drv   cty   hwy fl   class
##   <dbl> <chr>         <chr> <dbl> <dbl> <dbl> <chr> <chr> <dbl> <dbl> <chr> <chr>
## 1     1 audi         a4     1.8 1999     4 auto~ f     18    29 p    comp~
## 2     2 audi         a4     1.8 1999     4 manu~ f     21    29 p    comp~
## 3     3 audi         a4     2    2008     4 manu~ f     20    31 p    comp~
## 4     4 audi         a4     2    2008     4 auto~ f     21    30 p    comp~
## 5     5 audi         a4     2.8 1999     6 auto~ f     16    26 p    comp~
## 6     6 audi         a4     2.8 1999     6 manu~ f     18    26 p    comp~
```

- 1b. Which variables from mpg dataset are categorical?

```
str(mpg)
```

```
## spc_tbl_ [234 x 12] (S3: spec_tbl_df/tbl_df/tbl/data.frame)
## $ ...1      : num [1:234] 1 2 3 4 5 6 7 8 9 10 ...
## $ manufacturer: chr [1:234] "audi" "audi" "audi" "audi" ...
## $ model       : chr [1:234] "a4" "a4" "a4" "a4" ...
## $ displ      : num [1:234] 1.8 1.8 2 2 2.8 2.8 3.1 1.8 1.8 2 ...
## $ year       : num [1:234] 1999 1999 2008 2008 1999 ...
## $ cyl        : num [1:234] 4 4 4 4 6 6 6 4 4 4 ...
## $ trans      : chr [1:234] "auto(l5)" "manual(m5)" "manual(m6)" "auto(av)" ...
## $ drv        : chr [1:234] "f" "f" "f" "f" ...
## $ cty        : num [1:234] 18 21 20 21 16 18 18 18 16 20 ...
## $ hwy        : num [1:234] 29 29 31 30 26 26 27 26 25 28 ...
## $ fl         : chr [1:234] "p" "p" "p" "p" ...
## $ class      : chr [1:234] "compact" "compact" "compact" "compact" ...
## - attr(*, "spec")=
## .. cols(
```

```
##   ..   ...1 = col_double(),
##   ..   manufacturer = col_character(),
##   ..   model = col_character(),
##   ..   displ = col_double(),
##   ..   year = col_double(),
##   ..   cyl = col_double(),
##   ..   trans = col_character(),
##   ..   drv = col_character(),
##   ..   cty = col_double(),
##   ..   hwy = col_double(),
##   ..   fl = col_character(),
##   ..   class = col_character()
##   .. )
## - attr(*, "problems")=<externalptr>
```

*#The categorical variables are the manufacturer,model, year,cyl,trans,drv,fl and class*

1c. Which are continuous variables?

```
summary(mpg)
```

```
##           ...1      manufacturer      model      displ
##  Min.   : 1.00    Length:234      Length:234    Min.   :1.600
## 1st Qu.: 59.25    Class :character  Class :character 1st Qu.:2.400
## Median :117.50    Mode  :character  Mode  :character Median :3.300
## Mean   :117.50                                Mean   :3.472
## 3rd Qu.:175.75                                3rd Qu.:4.600
## Max.   :234.00                                Max.   :7.000
##           year      cyl      trans      drv
##  Min.   :1999    Min.   :4.000    Length:234    Length:234
## 1st Qu.:1999    1st Qu.:4.000    Class :character  Class :character
## Median :2004    Median :6.000    Mode  :character  Mode  :character
## Mean   :2004    Mean   :5.889
## 3rd Qu.:2008    3rd Qu.:8.000
## Max.   :2008    Max.   :8.000
##           cty      hwy      fl      class
##  Min.   : 9.00    Min.   :12.00    Length:234    Length:234
## 1st Qu.:14.00    1st Qu.:18.00    Class :character  Class :character
## Median :17.00    Median :24.00    Mode  :character  Mode  :character
## Mean   :16.86    Mean   :23.44
## 3rd Qu.:19.00    3rd Qu.:27.00
## Max.   :35.00    Max.   :44.00
```

*#The continious variablesa are the , manufacturer, model, disply, year , cyl, cty ,hwy, fl, trans, drv*

2. Which manufacturer has the most models in this data set? Which model has the most variations? Show your answer.

```
library(magrittr)
library(dplyr)
```

```
##
## Attaching package: 'dplyr'
##
## The following objects are masked from 'package:stats':
##
##   filter, lag
```

```
## The following objects are masked from 'package:base':
##
## intersect, setdiff, setequal, union
```

```
model <- mpg %>%
  group_by(manufacturer) %>%
  summarise(count = n()) %>%
  arrange(desc(count))

print(model)
```

```
## # A tibble: 15 x 2
##   manufacturer count
##   <chr>          <int>
## 1 dodge           37
## 2 toyota          34
## 3 volkswagen      27
## 4 ford            25
## 5 chevrolet       19
## 6 audi            18
## 7 hyundai         14
## 8 subaru          14
## 9 nissan           13
## 10 honda           9
## 11 jeep            8
## 12 pontiac         5
## 13 land rover      4
## 14 mercury         4
## 15 lincoln         3
```

*#The manufacturer with the most models is dodge.*

```
count <- mpg %>%
  group_by(model) %>%
  summarise(variation = n()) %>%
  arrange(desc(variation))

print(count)
```

```
## # A tibble: 38 x 2
##   model                variation
##   <chr>                <int>
## 1 caravan 2wd           11
## 2 ram 1500 pickup 4wd    10
## 3 civic                 9
## 4 dakota pickup 4wd      9
## 5 jetta                 9
## 6 mustang                9
## 7 a4 quattro             8
## 8 grand cherokee 4wd      8
## 9 impreza awd            8
## 10 a4                    7
## # i 28 more rows
```

*#The model with most variation is caravan 2wd.*

2.1 a. Group the manufacturers and find the unique models. Show your codes and result.

```
library(dplyr)

manumodel <- mpg %>%
  group_by(manufacturer) %>%
  summarise(unique_models = n_distinct(model))

print(manumodel)
```

```
## # A tibble: 15 x 2
##   manufacturer unique_models
##   <chr>          <int>
## 1 audi           3
## 2 chevrolet      4
## 3 dodge          4
## 4 ford           4
## 5 honda          1
## 6 hyundai        2
## 7 jeep           1
## 8 land rover     1
## 9 lincoln        1
## 10 mercury       1
## 11 nissan         3
## 12 pontiac       1
## 13 subaru        2
## 14 toyota        6
## 15 volkswagen    4
```


2.1 b. Graph the result by using plot() and ggplot(). Write the codes and its result.

```
library(ggplot2)

##
## Attaching package: 'ggplot2'
##
## The following object is masked _by_ '.GlobalEnv':
##
##   mpg

plot(ggplot(manumodel, aes(x = reorder(manufacturer, -unique_models), y = unique_models, fill = unique_models)) +
  geom_bar(stat = "identity", width = 0.8) +
  labs(title = "Number of Manufacturer's Unique Models",
    x = "Manufacturer",
    y = "Number of Unique Models") +


  theme_minimal() +
  scale_fill_gradient(low = "black", high = "pink") +
  theme(axis.text.x = element_text(angle = 90, vjust = 0.5, hjust=1)))
```



2. Same dataset will be used. You are going to show the relationship of the model and the manufacturer
  - a. What does `ggplot(mpg, aes(model, manufacturer)) + geom_point()` show?

Interpret: This generate a scatter plot showing the relationship between car models and their respective manufacturers using points but the car models are not readable, leads to uninformative data.


```
ggplot(mpg, aes(model, manufacturer)) + geom_point()
```



b. For you, is it useful? If not, how could you modify the data to make it more informative?

Answer: No, The code given is just a basic structure. In modifying this to make it informative I will add color for that will differentiate points based on different variables then a legend to guide viewer to avoid confusion, and adjust the size of variable names with its angle to make it more readable.

```
#like this code
ggplot(mpg, aes(x = model, y = manufacturer, color = class)) +
  geom_point() +
  labs(title = "Car Models and Manufacturers",
       cex = 3,
       x = "Car Model",
       y = "Manufacturer",
       color = "Vehicle Class") +
  theme_minimal() +
  theme(legend.position = "right", axis.text.x = element_text(angle = 90, hjust = 1),
        plot.title = element_text(hjust = 0.5))
```



3. Plot the model and the year using ggplot(). Use only the top 20 observations. Write the codes and its results.

```
library(ggplot2)
library(dplyr)

data(mpg)

mean_displ_df <- mpg %>%
  group_by(year, model) %>%
  summarise(mean_displ = mean(displ)) %>%
  arrange(desc(mean_displ)) %>%
  filter(row_number() < 20)


## `summarise()` has grouped output by 'year'. You can override using the
## `.groups` argument.

plot <- ggplot(mean_displ_df, aes(x = year, y = mean_displ, fill = model)) +
  geom_bar(stat = "identity", position = "dodge") +
  theme_minimal() +
  guides(fill = guide_legend(ncol = 2))
labs(title = "Average Engine Displacement over the years for the top 20 models",
     x = "Year",
     y = "Engine Displacement",
     fill = "Model")

## $x
```

```
## [1] "Year"
##
## $y
## [1] "Engine Displacement"
##
## $fill
## [1] "Model"
##
## $title
## [1] "Average Engine Displacement over the years for the top 20 models"
##
## attr(,"class")
## [1] "labels"

print(plot)
```



4. Using the pipe (`%>%`), group the model and get the number of cars per model. Show codes and its result

```
library(dplyr)
data(mpg)

carcountpermodel <- mpg %>%
  group_by(model) %>%
  summarise(num_cars = n())
```



```
print(carcountpermodel)
```

```
## # A tibble: 38 x 2
##   model          num_cars
##   <chr>          <int>
## 1 4runner 4wd             6
## 2 a4                   7
## 3 a4 quattro            8
## 4 a6 quattro            3
## 5 altima                6
## 6 c1500 suburban 2wd     5
## 7 camry                 7
## 8 camry solara           7
## 9 caravan 2wd           11
## 10 civic                 9
## # i 28 more rows
```

- a. Plot using `geom_bar()` using the top 20 observations only. The graphs should have a title, labels and colors. Show code and results.

```
library(ggplot2)
library(dplyr)


data(mpg)

summary_data <- mpg %>%
  count(model) %>%
  arrange(desc(n)) %>%
  slice(1:20)

top_models <- summary_data$model
palette <- scales::hue_pal()(length(top_models))

summary_data <- summary_data %>%
  mutate(color = palette[match(model, top_models)])

ggplot(summary_data, aes(x = reorder(model, n), y = n, fill = model)) +
  geom_bar(stat = "identity") +
  labs(
    title = "Top 20 Car Models by Count",
    x = "Car Models",
    y = "Total Cars"
  ) +
  scale_fill_manual(values = palette, name = "Car Models", breaks = summary_data$model) +
  theme_minimal() +
  theme(
    axis.text.x = element_text(angle = 45, hjust = 1),
    legend.key.size = unit(0.1, "cm"),
    plot.title = element_text(hjust = 0.5)
  )
```



b.

Plot using the `geom_bar()` + `coord_flip()` just like what is shown below. Show codes and its result.

```
library(ggplot2)
library(dplyr)

data(mpg)


summary_data <- mpg %>%
  count(model) %>%
  arrange(desc(n)) %>%
  slice(1:20)

top_models <- summary_data$model
palette <- scales::hue_pal()(length(top_models))

summary_data <- summary_data %>%
  mutate(color = palette[match(model, top_models)])

ggplot(summary_data, aes(x = reorder(model, n), y = n, fill = model)) +
  geom_bar(stat = "identity") +
  labs(
    title = "Top 20 Car Models by Count",
    y = "Car Models",
    x = "Total Cars"
  ) +
  scale_fill_manual(values = palette, name = "Car Models", breaks = summary_data$model) +
  coord_flip() +
```

```
theme_minimal() +
theme(
  legend.key.size = unit(0.1, "cm"),
  plot.title = element_text(hjust = 0.5)
)
```




- Plot the relationship between cyl - number of cylinders and displ - engine displacement using `geom_point` with aesthetic color = engine displacement. Title should be "Relationship between No. of Cylinders and Engine Displacement".

```
library(ggplot2)
library(dplyr)

data(mpg)

ggplot(mpg, aes(x = cyl, y = displ, color = displ)) +
  geom_point(size = 3, alpha = 0.7) +
  labs(
    title = "Relationship between No. of Cylinders and Engine Displacement",
    x = "Number of Cylinders",
    y = "Engine Displacement"
  )
```



How would you describe its relationship? Show the codes and its result.


Describe: Using the line regression to visualize the relationship of the No. of cyl and displ so as the number of cylinders goes up, the engine size tends to increase too.

```
library(ggplot2)
library(dplyr)

data(mpg)

ggplot(mpg, aes(x = cyl, y = displ, color = displ)) +
  geom_point(size = 3, alpha = 0.7) +
  geom_smooth(method = "lm", se = FALSE, color = "black") +
  labs(
    title = "Relationship between No. of Cylinders and Engine Displacement",
    x = "Number of Cylinders",
    y = "Engine Displacement"
  )
```

```
## `geom_smooth()` using formula = 'y ~ x'
```



6. Plot the relationship between `displ` (engine displacement) and `hwy` (highway miles per gallon). Mapped it with a continuous variable you have identified in #1-c. What is its result? Why it produced such output?

Answer: The scatter plot displays engine displacement (`displ`) against highway miles per gallon (`hwy`), while using the color gradient of city miles per gallon (`cty`) to represent a continuous variable across the points.


Answer: The color gradient based on city miles per gallon (`cty`) doesn't indicate a direct relationship with engine displacement and highway miles per gallon (`displ` and `hwy`), serving instead to visualize the variation in city MPG across the scatter plot.

```
library(ggplot2)
library(dplyr)

data(mpg)

ggplot(mpg, aes(x = displ, y = hwy, color = cty)) +
  geom_point() +
  labs(
    title = "Relationship between Engine Displacement and Highway MPG",
    x = "Engine Displacement",
    y = "Highway MPG"
  ) +
  scale_color_gradient(low = "black", high = "pink")
```

Relationship between Engine Displacement and Highway MPG



6. Import the traffic.csv onto your R environment.

```
traffic <- read_csv("traffic.csv")
```

```
## Rows: 48120 Columns: 4
## -- Column specification -----
## Delimiter: ","
## dbl (3): Junction, Vehicles, ID
## dtm (1): DateTime
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
head(traffic)
```

```
## # A tibble: 6 x 4
##   DateTime      Junction Vehicles      ID
##   <dtm>         <dbl>    <dbl>    <dbl>
## 1 2015-11-01 00:00:00      1      15 20151101001
## 2 2015-11-01 01:00:00      1      13 20151101011
## 3 2015-11-01 02:00:00      1      10 20151101021
## 4 2015-11-01 03:00:00      1       7 20151101031
## 5 2015-11-01 04:00:00      1       9 20151101041
## 6 2015-11-01 05:00:00      1       6 20151101051
```

a. How many numbers of observation does it have? What are the variables of the traffic dataset the Show your answer.

```

observations <- nrow(traffic)
variables <- names(traffic)

cat("Number of observations:", observations, "\n")

```

```
## Number of observations: 48120
```

```
cat("The variables are:", variables, "\n")
```

```
## The variables are: DateTime Junction Vehicles ID
```

b. subset the traffic dataset into junctions. What is the R codes and its output?

```

junctions1 <- subset(traffic, Junction == 1)
junctions2 <- subset(traffic, Junction == 2)
junctions3 <- subset(traffic, Junction == 3)
junctions4 <- subset(traffic, Junction == 4)

```

*#The output are:*

```
junctions1
```

```

## # A tibble: 14,592 x 4
##   DateTime          Junction Vehicles      ID
##   <dtm>              <dbl>    <dbl>    <dbl>
## 1 2015-11-01 00:00:00         1        15 20151101001
## 2 2015-11-01 01:00:00         1        13 20151101011
## 3 2015-11-01 02:00:00         1        10 20151101021
## 4 2015-11-01 03:00:00         1         7 20151101031
## 5 2015-11-01 04:00:00         1         9 20151101041
## 6 2015-11-01 05:00:00         1         6 20151101051
## 7 2015-11-01 06:00:00         1         9 20151101061
## 8 2015-11-01 07:00:00         1         8 20151101071
## 9 2015-11-01 08:00:00         1        11 20151101081
## 10 2015-11-01 09:00:00        1        12 20151101091
## # i 14,582 more rows

```

```
junctions2
```

```

## # A tibble: 14,592 x 4
##   DateTime          Junction Vehicles      ID
##   <dtm>              <dbl>    <dbl>    <dbl>
## 1 2015-11-01 00:00:00         2         6 20151101002
## 2 2015-11-01 01:00:00         2         6 20151101012
## 3 2015-11-01 02:00:00         2         5 20151101022
## 4 2015-11-01 03:00:00         2         6 20151101032
## 5 2015-11-01 04:00:00         2         7 20151101042
## 6 2015-11-01 05:00:00         2         2 20151101052
## 7 2015-11-01 06:00:00         2         4 20151101062
## 8 2015-11-01 07:00:00         2         4 20151101072
## 9 2015-11-01 08:00:00         2         3 20151101082
## 10 2015-11-01 09:00:00         2         3 20151101092
## # i 14,582 more rows

```

```
junctions3
```

```

## # A tibble: 14,592 x 4
##   DateTime          Junction Vehicles      ID

```

```
##      <dtm>                <dbl>    <dbl>      <dbl>
## 1 2015-11-01 00:00:00         3        9 20151101003
## 2 2015-11-01 01:00:00         3        7 20151101013
## 3 2015-11-01 02:00:00         3        5 20151101023
## 4 2015-11-01 03:00:00         3        1 20151101033
## 5 2015-11-01 04:00:00         3        2 20151101043
## 6 2015-11-01 05:00:00         3        2 20151101053
## 7 2015-11-01 06:00:00         3        3 20151101063
## 8 2015-11-01 07:00:00         3        4 20151101073
## 9 2015-11-01 08:00:00         3        3 20151101083
## 10 2015-11-01 09:00:00        3        6 20151101093
## # i 14,582 more rows
```


```
junctions4
```

```
## # A tibble: 4,344 x 4
##   DateTime      Junction Vehicles      ID
##   <dtm>        <dbl>    <dbl>    <dbl>
## 1 2017-01-01 00:00:00         4        3 20170101004
## 2 2017-01-01 01:00:00         4        1 20170101014
## 3 2017-01-01 02:00:00         4        4 20170101024
## 4 2017-01-01 03:00:00         4        4 20170101034
## 5 2017-01-01 04:00:00         4        2 20170101044
## 6 2017-01-01 05:00:00         4        1 20170101054
## 7 2017-01-01 06:00:00         4        1 20170101064
## 8 2017-01-01 07:00:00         4        4 20170101074
## 9 2017-01-01 08:00:00         4        4 20170101084
## 10 2017-01-01 09:00:00         4        2 20170101094
## # i 4,334 more rows
```


c. Plot each junction in a using `geom_line()`. Show your solution and output.

```
# Junction 1
ggplot(junctions1, aes(x = DateTime, y = Vehicles, color = "Junction 1")) +
  geom_line() +
  labs(
    title = "Traffic Volume at Junction 1",
    x = "Date",
    y = "Volume"
  ) +
  scale_color_discrete(name = "Junction") +
  theme(plot.title = element_text(hjust = 0.5))
```






```
#Junction 2
ggplot(junctions2, aes(x = DateTime, y = Vehicles, color = "Junction 2")) +
  geom_line() +
  labs(
    title = "Traffic Volume at Junction 2",
    x = "Date",
    y = "Volume"
  ) +
  scale_color_discrete(name = "Junction") +
  theme(plot.title = element_text(hjust = 0.5))
```




```
#Junction 3
ggplot(junctions3, aes(x = DateTime, y = Vehicles, color = "Junction 3")) +
  geom_line() +
  labs(
    title = "Traffic Volume at Junction 3",
    x = "Date",
    y = "Volume"
  ) +
  scale_color_discrete(name = "Junction") +
  theme(plot.title = element_text(hjust = 0.5))
```

Traffic Volume at Junction 3



```
#Junction 4
ggplot(junctions4, aes(x = DateTime, y = Vehicles, color = "Junction 4")) +
  geom_line() +
  labs(
    title = "Traffic Volume at Junction 4",
    x = "Date",
    y = "Volume"
  ) +
  scale_color_discrete(name = "Junction") +
  theme(plot.title = element_text(hjust = 0.5))
```



7. From alexa\_file.xlsx, import it to your environment

```
library(readxl)
alexa_file <- read_excel("alexa_file.xlsx")
head(alexa_file)
```

```
## # A tibble: 6 x 5
##   rating date          variation      verified_reviews      feedback
##   <dbl> <dtm>          <chr>          <chr>          <dbl>
## 1     5 2018-07-31 00:00:00 Charcoal Fabric Love my Echo!         1
## 2     5 2018-07-31 00:00:00 Charcoal Fabric Loved it!             1
## 3     4 2018-07-31 00:00:00 Walnut Finish  Sometimes while playi~ 1
## 4     5 2018-07-31 00:00:00 Charcoal Fabric I have had a lot of f~ 1
## 5     5 2018-07-31 00:00:00 Charcoal Fabric Music              1
## 6     5 2018-07-31 00:00:00 Heather Gray Fabric I received the echo a~ 1
```

a. How many observations does alexa\_file has? What about the number of columns? Show your solution and answer.

```
observations <- nrow(alexa_file)
columns <- ncol(alexa_file)

cat("Number of observations:", observations, "\n")
```

```
## Number of observations: 3150
cat("Number of columns:", columns, "\n")
```

```
## Number of columns: 5
```

*#The number of observations is 3,150 and The number of columns is 5.*

b. group the variations and get the total of each variations. Use dplyr package. Show solution and answer.

```
library(dplyr)

result <- alexa_file %>%
  group_by(variation) %>%
  summarise(total_variations = n())

print(result)

## # A tibble: 16 x 2
##   variation                total_variations
##   <chr>                  <int>
## 1 Black                    261
## 2 Black Dot                516
## 3 Black Plus               270
## 4 Black Show               265
## 5 Black Spot               241
## 6 Charcoal Fabric          430
## 7 Configuration: Fire TV Stick 350
## 8 Heather Gray Fabric      157
## 9 Oak Finish                14
## 10 Sandstone Fabric         90
## 11 Walnut Finish            9
## 12 White                    91
## 13 White Dot                184
## 14 White Plus               78
## 15 White Show               85
## 16 White Spot              109
```


c. Plot the variations using the ggplot() function. What did you observe? Complete the details of the graph. Show solution and answer.

Answer: This plot is the variations of the Alexa File showing each variation name with color to guide for the viewer to analyze this plot also this include the total of each variation. The variation called Black Dot is more known or shows up a lot more often than the others. The legend, this split into two columns, helps easily see which color represents each type of variation.

```
library(ggplot2)

var <- ggplot(result, aes(x = variation, y = total_variations, fill = variation)) +
  geom_bar(stat = "identity") +
  labs(title = "Variations Count",
       x = "Variation",
       y = "Total Count") +
  theme_minimal() +
  theme(axis.text.x = element_text(angle = 45, hjust = 1)) +
  scale_fill_discrete(name = "Variation") +
  guides(fill = guide_legend(ncol = 2)) +
  theme(plot.title = element_text(hjust = 0.5))

print(var)
```



d. Plot a `geom_line()` with the date and the number of verified reviews. Complete the details of the graphs. Show your answer and solution.

```
library(dplyr)
library(ggplot2)

alexa_file$date <- as.Date(alexa_file$date)
alexa_file$month <- format(alexa_file$date, "%m")


monthcount <- alexa_file %>%
  count(month)

p <- ggplot(monthcount, aes(x = as.integer(month), y = n, color = "Reviews")) +
  geom_line(size = 1) +
  labs(title = "Number of Verified Reviews Over Time",
       x = "Month",
       y = "Number of Verified Reviews",
       color = "Legend Title") + # Change legend title
  scale_x_continuous(breaks = 1:12, labels = month.abb) +
  scale_color_manual(values = c("blue"), labels = c("Reviews")) +
  theme_minimal() +
  theme(plot.title = element_text(hjust = 0.5),
        axis.text.x = element_text(angle = 45, hjust = 1))

## Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use `linewidth` instead.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
```

```
## generated.
```

```
print(p)
```



- e. Get the relationship of variations and ratings. Which variations got the most highest in rating? Plot a graph to show its relationship. Show your solution and answer.

```
library(dplyr)
library(ggplot2)

variation_ratings <- alexa_file %>%
  group_by(variation) %>%
  summarize(avg_rating = mean(rating))
print(variation_ratings)
```

```
## # A tibble: 16 x 2
##   variation          avg_rating
##   <chr>          <dbl>
## 1 Black          4.23
## 2 Black Dot      4.45
## 3 Black Plus     4.37
## 4 Black Show     4.49
## 5 Black Spot     4.31
## 6 Charcoal Fabric 4.73
## 7 Configuration: Fire TV Stick 4.59
## 8 Heather Gray Fabric 4.69
## 9 Oak Finish     4.86
## 10 Sandstone Fabric 4.36
## 11 Walnut Finish  4.89
```


```
## 12 White 4.14
## 13 White Dot 4.42
## 14 White Plus 4.36
## 15 White Show 4.28
## 16 White Spot 4.31
```

```
highest <- variation_ratings %>%
  filter(avg_rating == max(avg_rating))
print(highest)
```

```
## # A tibble: 1 x 2
##   variation avg_rating
##   <chr>      <dbl>
## 1 Walnut Finish 4.89
```

```
variation_names <- variation_ratings$variation
average_ratings <- variation_ratings$avg_rating
```

```
barplot(average_ratings, names.arg = variation_names, col = "skyblue",
  main = "Average Rating by Variation",
  xlab = "Variation", ylab = "Average Rating",
  cex.axis = 0.8, cex.names = 0.5, las = 2)
```



```
top_variation <- variation_names[which.max(average_ratings)]
top_rating <- max(average_ratings)
```

```
cat("The variation with the highest average rating is:", top_variation, "with an average rating of", top_rating)
```

```
## The variation with the highest average rating is: Walnut Finish with an average rating of 4.888889
```