Look Again: Self-Correcting Tool Use for Panoramic Dental Radiograph Diagnosis

Reza Nadimi*
[affiliations]

October 2026

Abstract

Panoramic dental diagnosis requires both identifying a finding and assigning it to the correct tooth. In our zero-shot DENTEX evaluation, the strongest reported baseline obtains pooled exact finding-level F1 of 0.222, motivating methods that can revisit localized image evidence. We present **VLM-DENTAL**, a tool-using vision-language pipeline organized around one principle: *grounding is a hypothesis to interrogate, not an answer to trust.* An eight-tool interface lets a policy inspect native-resolution regions and correct a proposed box using box-relative shifts and scales through `nudge_crop`. During demonstration synthesis, tiered spatial perturbations expose the teacher to imperfect grounding without verbal error cues. A ground-truth-anchored reward is designed to preserve corrective tool use during subsequent reinforcement learning. The released corpus contains 3,694 verified, decontaminated synthetic traces. Within ground-truth-anchored pathology locates, the teacher uses corrective nudges on 38.4% of large offsets, 13.6% of small offsets, and 1.1% of clean outputs; these are demonstration statistics, not trained-policy results. We additionally specify a versioned rules-and-skills harness and a separately gated speculative-decoding benchmark, keeping inference-time procedural context distinct from model training and serving optimizations. The frozen primary evaluation uses DENTEX-native set matching and paired image-level bootstrap intervals. Trained-policy, harness-effectiveness, and serving-speed results remain explicitly pending. This draft contributes an auditable method, corpus, and experimental specification; evidence of end-to-end diagnostic improvement awaits those runs.

1 Introduction

Panoramic dental radiograph analysis requires assigning diagnostic findings to individual teeth in standard FDI notation. General-purpose vision-language models (VLMs) offer a flexible interface, but our zero-shot evaluation on DENTEX shows limited finding-level agreement with expert annotations (Section 4.2). The best reported pooled exact F1 is 0.222. Image-level hit rates and calibration provide complementary evidence, but do not by themselves identify the causes of these errors. Local detail, tooth identity, and orientation motivate an agent that can inspect a region again before answering.

Medical and general-purpose tool-using systems provide relevant precedents (Wu et al., 2026; Li et al., 2024; Lu et al., 2025; Fan et al., 2026; Hao et al., 2026). We focus on a specific failure point: a learned grounding model can return a plausible box for the wrong region, and subsequent crops inherit that error. Rather than treating the box as an authoritative observation, the policy should

*Corresponding author. [Affiliations and co-author list to be finalized.]




Figure 1: The central idea, on a real episode from the corpus (DENTEX image 127, an impacted FDI tooth 48). (a) When a grounding box is taken as an answer, the crop of that box looks authoritative and every later observation inherits its error — here the returned box (blue) sits 0.92 box-sizes from the expert box (green; IoU 0.07). (b) VLM-DENTAL treats the box as a hypothesis: the policy sees a crop dominated by an upper molar, judges the box "about one arch too high", corrects it with one box-relative `nudge_crop` (orange; IoU 0.94), and answers from the corrected view. Crops are native-resolution views of the box with 30% padding, illustrative of what the zoom tool returns rather than the canonical-view geometry of Fig. 6. Further episodes are in Fig. 18; the full with-tools trace of another image is dissected in Figs. 14 and 15.

be able to inspect and revise it. Whether a trained policy acquires this behavior, and whether it improves diagnosis, are empirical questions addressed by the frozen evaluation design.

This paper develops and evaluates VLM-DENTAL, an agentic VLM for OPG diagnosis built around a different contract between the policy and its tools: *grounding is a hypothesis, not an answer* (Fig. 1). Figs. 4 and 5 give the complete system architecture (agent loop and offline training stack), and Figs. 14 and 15 contrast the two trace arms on one image. Our contributions are:

1. **A self-correcting grounding tool (`nudge_crop`, Section 3.4).** The policy can shift and rescale a box it was *already given* — by the grounding model or by a previous correction — using box-relative fractional arguments (`dx_frac`, `dy_frac`, `scale`) that a VLM can reason about linguistically ("shift right about half a tooth-width"), without re-running detection. We make box revision an explicit, inspectable action rather than an implicit change in the policy's internal localization.

2. **A tiered perturbation mechanism that makes self-correction learnable (Section 3.5).**

Demonstrating correction behavior requires the demonstrator to *experience* tool error. During trace generation we return the expert-verified box for annotated teeth (guaranteeing task solvability) but deliberately perturb the box *shown to the demonstrator* — 45% clean, 25% small offsets (12–28% of box size), 30% large offsets (45–75%) — with two design commitments: the rates are fixed constants decoupled from the detector's real error rate, so demonstrations never go stale as the detector improves; and errors are never announced verbally, so correction must be elicited by the returned image rather than an explicit error message. Transfer of this behavior to the trained policy remains to be measured. A corpus-level analysis (Section 4.4) shows the mechanism elicits exactly the intended behavior gradient in 3,694 generated demonstrations: corrective use of `nudge_crop` on 38.4% of large offsets, 13.6% of small ones (intermediate offsets), and 1.1% of clean boxes, on ground-truth-anchored pathology locates.

3. **A tool interface with continuous parameters (Section 3.3).** Tools expose *how much* effect to apply, not just which tool to call: `denoise(strength` $\in [0, 1]$`)`, `window_level` with exact `center`/`width` values as an override on top of presets, a multiplicative `enhance_contrast` factor, and a tunable `zoom_crop` context margin. Tool calls therefore carry real information beyond tool identity, and the policy can match processing intensity to image characteristics.

4. **A ground-truth-anchored, correction-friendly reward (Section 3.8).** GRPO training (DeepSeek-AI, 2025) uses a composite reward whose dominant term is a hard, non-LLM-judge match against expert labels with multi-finding greedy one-to-one matching (F1-style harmonic mean of recall and precision), and whose efficiency term scales a reference budget with case complexity and *exempts* `locate_tooth` and `nudge_crop` from per-call cost — so the reward never prices out the verification behavior it is trying to teach, a failure mode we identified and removed by design.

5. **Label-anchored synthetic demonstrations and an audit trail (Section 3.6).** 3,694 verified chain-of-thought tool-use traces over DENTEX and Tufts (1,847 with tools, 1,847 single-turn without, exact 1:1 parity), generated by frontier models under real tool execution in a LangGraph loop, verified cross-family, decontaminated of directive leakage (105 traces regenerated; 0 leaks in the canonical corpus), and released as a reusable resource. The verifier's rejection taxonomy (66 false-positive findings on healthy scans, 15 ground-truth contradictions, 11 uncorrected spatial drifts) doubles as an audit of what the perturbation mechanism does and does not elicit.

We evaluate on DENTEX with its native structured metrics — pooled, set-matched, finding-level precision/recall/F1 with paired bootstrap intervals — against zero-shot frontier VLMs, the same backbone with and without tools, and a supervised specialist detector. The training-side analyses in this draft are complete; the two-stage training runs (SFT, then GRPO) are not yet reported, and their result cells are marked **[SFT/GRPO results pending first hardware run]** rather than extrapolated. Inference-time rules, skills, and serving optimizations are evaluated separately on the training-derived dev split (Section 5); they do not revise the frozen primary protocol.

2 Related Work

Supervised dental AI. The dominant paradigm in dental radiograph analysis is narrow, single-task supervised learning: CNN and Faster R-CNN cephalometric landmark detectors, U-Net-style segmentation, FDI tooth-numbering classifiers, and YOLO-family or Faster R-CNN detectors for caries, periapical lesions, and impactions (Hamamci et al., 2024). The DENTEX benchmark consolidated this into a hierarchical quadrant–enumeration–diagnosis task with expert-verified labels (Hamamci et al., 2024) and remains the most structured public benchmark for our problem. These

supervised tasks differ from our episode-level setting, in which a policy can request additional views and revise a grounding hypothesis. A systematic review of public dental imaging datasets (Uribe et al., 2024) screened 131,028 records and found only 16 datasets meeting a minimal bar — the data scarcity that motivates our synthetic-trace approach.

Reinforcement-learned reasoning in medical VLMs. Following the GRPO recipe (DeepSeek-AI, 2025), Hu et al. (2025) fine-tuned a 2B VLM with GRPO on a few hundred examples and reported large gains over zero-shot across MRI, CT, and X-ray VQA; Med-R1 extended this across eight modalities and found that lengthening the chain of thought does not reliably improve accuracy — reward alignment matters more than reasoning length (Lai et al., 2026). HuatuoGPT-o1 (Chen et al., 2024) and OpenMedReason (Baghbanzadeh et al., 2026) build reasoning supervision by using a frontier model purely as a *verifier* of evidence-grounded traces. These reasoning-supervision approaches motivate our training recipe; our focus is the additional interaction between a reasoning policy and revisable visual observations.

Agentic tool use in VLMs. MMedAgent trains an LLM to select among grounding, segmentation, and report tools (Li et al., 2024); OctoTools generalizes the orchestration pattern (Lu et al., 2025). Closest in spirit is VTool-R1 (Wu et al., 2026), which trains a VLM with GRPO to call Python-based visual-editing tools mid-reasoning, improving chart/table QA from 64.7% to 71.7%. Its tools are generic image-editing primitives, its reward is a single outcome-accuracy term, and its domain is not medical. Two concurrent dental systems must be addressed directly. **OralGPT-Plus** (Fan et al., 2026) pairs trained CoT, two callable image tools (zoom-in, contralateral mirror), and GRPO-style RL with a composite reward — the closest concurrent work, but it evaluates on its own benchmark with an LLM-judge-scored reward (whose documented reward-hacking failure mode motivates our ground-truth-anchored accuracy term, Section 3.8) and does not cleanly separate tool-use from RL effects. **OralAgent** (Hao et al., 2026) is a broader prompted ReAct orchestrator around an off-the-shelf model, not an RL-trained tool-use policy. Our emphasis is a box-relative corrective action and a controlled evaluation of tools and RL, rather than a claim to originate dental agents or medical tool use. Comparisons should account for differences in datasets, available supervision, and scoring protocols.

Procedural context and speculative serving. The rules-and-skills extension follows the inspectable `SKILL.md` convention with progressive disclosure (Agent Skills contributors, 2026). Its contribution here is a provenance-tracked integration with the shared dental dispatcher, not a new knowledge-file format. Speculative decoding uses a draft proposal and target verification to accelerate generation (Leviathan et al., 2023; Chen et al., 2023); vLLM provides the serving substrate (Kwon et al., 2023). We treat serving speed and clinical-task performance as separate measurements, and test output equivalence on the actual multimodal episodes rather than assuming it from the algorithm alone.

Label-anchored synthetic reasoning traces. Frontier LLMs can generate and verify reasoning-trace training data of sufficient quality for downstream fine-tuning (Chen et al., 2024; Baghbanzadeh et al., 2026), replacing prospective expert annotation with expert-*verified benchmark labels* plus cross-model automated checks. We extend this pattern to *multi-turn tool-use* traces: the demonstrator operates a real tool suite under real tool feedback (including deliberately imperfect tool output, Section 3.5), and an independent cross-family verifier audits every trace against expert labels before it enters the training set.

3 VLM-DENTAL: System and Method

3.1 Problem setup and agent loop

An OPG I is annotated as a *set* of findings $F = \{f_1, \ldots, f_m\}$ (possibly empty for a healthy image), where each finding $f = (\text{quadrant}, \text{tooth position}, \text{diagnosis})$ uses FDI two-digit notation over DENTEX's four diagnosis classes (caries, deep caries, periapical lesion, impacted tooth). The agent receives the image and a registry of tools, and produces a sequence of turns; each turn contains free-form clinical reasoning and zero or more structured tool calls, and the loop ends with a structured final answer reporting *every* finding the agent commits to. The same agent loop is used for synthetic data generation, RL rollouts, and evaluation, and tool calls execute for real against the source image at every stage (Fig. 2); a single shared dispatcher defines which tools consume the image and which image they operate on, so the training and inference environments cannot drift apart. Tool calls are capped at 50 per episode, counted by calls rather than turns, and parsed by a bracket-counting JSON extractor that repairs truncated or markdown-wrapped outputs.

3.2 System architecture

Figs. 4 and 5 show the complete system: the agent loop used at inference and evaluation time, and the offline stack that produces its weights. Five component groups surround one agent core — a Qwen3.5-9B vision-language policy running the loop of Section 3.1: a data layer (Fig. 3: registry-driven loaders for the two in-use sources, DENTEX and Tufts; a candidate pool of eight further public panoramic datasets, promoted only after their annotation semantics are verified; and surgical per-image Hugging Face caching), the trace synthesis stack of Section 3.6, the two training stages of Section 3.8, and an evaluation layer (Section 4.1) whose probes feed model selection on a fixed dev split.

Three single-source-of-truth decisions hold the system together. First, one shared dispatcher defines, for every tool, whether and *which* image it consumes — always the native source image — so the trace-generation loop, the GRPO rollout loop, and the evaluation runner cannot silently diverge; the dispatcher exists precisely because the two loops originally duplicated this logic and the rollout side drifted onto a compounding image state, a real bug that silently invalidated rollouts. Second, the image-input geometry lives in one module and is an explicit flag, not an implicit behavior (Fig. 6). The two candidate execution targets make different demands: TPU training requires aspect-preserving canonical views with static vision-slot padding to reduce shape-driven XLA recompilation, without guaranteeing one graph or eliminating HBM pressure, while GPU runs so far feed original images with dynamic shapes; which target the project settles on — a GPU (RTX 4090 / RTX Pro 6000 / A100) or a TPU v5e-8 cluster — is deliberately deferred to the first GPU run. Whichever is chosen applies identically across SFT, RL, and evaluation, and in both modes every tool operates on native-resolution pixels, so coordinates the model was trained to emit remain valid at inference. Third, the conversion from DENTEX's zero-indexed annotation rows to FDI notation has exactly one implementation, called by the reward, the verifier, and the metrics alike — an indexing bug cannot recur independently in several subsystems.

3.3 A tool suite with continuous parameters

The registry exposes eight tools (Table 1; Fig. 7 shows what they return). The deliberate design choice throughout is that tools expose *how much* effect to apply as a continuous or overridable parameter, not just a fixed on/off call: denoising takes a continuous `strength`, windowing takes exact `center`/`width` values as an override on top of tissue presets, contrast takes a multiplicative




Figure 2: The VLM-DENTAL pipeline. Traces are synthesized by a frontier teacher operating a real tool suite in a LangGraph loop (with the tiered perturbation hook of Section 3.5), verified cross-family against expert labels, and used for SFT followed by GRPO with a ground-truth-anchored composite reward. Tool calls execute for real against the source image at every stage; the radiograph and crop pixels are real assets from the corpus (the image whose trace anatomy is dissected in Fig. 15).

`factor`, and cropping takes a tunable context margin. A policy calling `denoise(strength=0.3)` versus `denoise(strength=0.9)` is expressing a patient-specific judgment about how grainy a crop is — information a fixed three-level menu cannot carry — and the resulting tool-call stream is correspondingly more informative to train on and to audit.




Figure 3: The data layer. Two sources are in use — DENTEX (the only panoramic dataset pairing tooth position with all four reward-relevant pathology classes) and the Tufts Dental Database (per-tooth boxes plus an expert pathology layer whose periapical class maps onto the DENTEX taxonomy). Eight further public panoramic datasets are catalogued as candidates and deliberately *not* used: each would be promoted only after its annotation semantics are verified end-to-end, and two loaders currently stop at exactly one open question rather than guess. The diagnosis-label vs grounding-only flag drives purpose: grounding candidates generalize `locate_tooth`, diagnosis candidates would feed trace generation. The catalog is transcribed from a systematic review of 16 public dental imaging datasets (Uribe et al., 2024) plus a targeted follow-up search; the radiographs are real examples of the two sources, with their expert boxes.




Figure 4: The VLM-DENTAL agent loop. One agent loop, one shared tool dispatcher, and one canonical vision geometry are shared by trace generation, RL rollouts, and evaluation. The policy (Qwen3.5-9B with pluggable SFT/GRPO LoRA adapters) calls the registered tools, which always execute on the native source image; the final findings JSON is scored by an evaluation layer whose probes select on a dev split only, with the test split run once at the end. Badges 4–6 continue the numbered path of Fig. 5, whose training stack is the source of the adapters and the sink of the dev-split signal (the grey "training" boxes); radiograph and crop pixels are real assets from the corpus.




Figure 5: The VLM-DENTAL offline stack. The data layer (DENTEX and Tufts, ground truth with one to seven findings per image, and the YOLOv8m grounding model) feeds the trace-synthesis stack (stage details in Figs. 10 and 11); the verified corpus is consumed by SFT and then GRPO, which produce the LoRA adapters loaded by the policy of Fig. 4. Numbered badges trace the corpus-to-policy life cycle (legend under the figure); the grey boxes at the bottom stand for the agent-loop components shown in Fig. 4.




Figure 6: Image-input geometry: two execution targets, one invariant. **TPU:** the policy sees aspect-preserving canonical views in three fixed families (renders produced by the geometry module itself, and the `contralateral_compare` tool, from DENTEX image 624), padded to a static 19-slot budget of 7,488 vision tokens so XLA compiles one graph; the padded tail carries labels $= -100$ and attention_mask $= 0$, so padding changes no gradient. **GPU:** runs so far feed original images with dynamic shapes. The choice between the targets is explicitly open pending the first GPU run; in both, tools always execute on the native image and evaluation runs at original size.

Table 1: The VLM-DENTAL tool suite. Continuous or overridable parameters are shown in *italics*; data-only tools return coordinates rather than images.

Tool	Key parameters	Purpose
`zoom_crop`	bbox, *padding_frac*	High-resolution crop of a region with a tunable context margin
`window_level`	preset; *center*, *width*	Radiological intensity windowing (bone/enamel/soft-tissue), exactly overridable
`denoise`	method, *strength* $\in [0, 1]$	Edge-preserving bilateral or median filtering matched to crop noise
`enhance_contrast`	*factor*	Multiplicative contrast adjustment for subtle lesions
`contralateral_compare`	bbox, quadrant	Side-by-side mirror crop, constrained to the correct jaw half, for bilateral symmetry assessment
`locate_tooth`	FDI tooth	YOLOv8m grounding (32 classes, one per FDI position); returns a box
`fdi_label`	quadrant, position	FDI notation conversion and validation
`nudge_crop`	bbox, *dx_frac*, *dy_frac*, *scale*	Correct a box the agent was already given, without re-running detection

3.4 Self-correcting grounding: `nudge_crop`

The grounding tool is a YOLOv8m detector fine-tuned on 2,339 DENTEX+Tufts images with 46,808 tooth boxes, trained with 5-fold cross-validation (one class per FDI quadrant–position pair) (Fig. 8; full per-fold numbers in Section C). It is strong — held-out *target* mAP50 of 0.93–0.96 with precision up to 0.986 on annotated teeth — but it is a 32-class detector operating under per-fold variance, and its errors are exactly the kind that poison downstream reasoning: a box shifted by half a tooth-width produces a crop that still *looks* like a plausible anatomical region while showing the wrong tooth.

`nudge_crop` turns that failure mode into an interaction. It takes a box the policy was *already given* (by `locate_tooth` or a previous `nudge_crop` — never asserted from nowhere) and returns adjusted coordinates: a shift (`dx_frac`, `dy_frac`) expressed as fractions of the box's own width and height, and a rescale `scale` around the new center, clamped to image bounds. The tool is deliberately *data-only*: it computes coordinates, and the policy must pair it with `zoom_crop` to actually see the corrected region. Two consequences follow. First, the fractional, box-relative parameterization is what a VLM can reason about reliably — "shift left by about half the box" — rather than raw pixel coordinates at an arbitrary zoom level. Second, because each correction must be followed by a verification crop, the loop enforces an inspect–correct–re-inspect cycle rather than a single blind adjustment. This is the mechanism neither concurrent dental agentic system provides: their tools are fixed operations whose outputs the policy can only accept.

3.5 Tiered perturbation: making self-correction learnable

A policy can only learn to interrogate its tools if its teachers did. The core difficulty is that an idealized demonstrator — one whose grounding tool always returns the right box — demonstrates *trusting* the tool, and SFT on such traces teaches exactly the wrong reflex. At the same time, blind exploration by the demonstrator would collapse the yield of usable traces.

Our resolution (Fig. 9) separates what the grounding tool *computes* from what the demonstrator




Figure 7: What the tools return: the project's own tool functions, run with the arguments the policy actually chose in two released traces, on the same zoom crop. (a) A DENTEX image: the three `window_level` presets, an exact center/width override, `enhance_contrast` and bilateral `denoise`. (b) A Tufts image: heavier denoising, two contrast factors, and `contralateral_compare`, which sets the region beside its mirror across the midline. The tools were applied to the 1,800 px copy of each radiograph resized to native geometry.

sees. During trace generation, `locate_tooth` operates in a ground-truth-grounding mode: for an annotated tooth it returns the expert-verified box (guaranteeing the demonstration remains solvable), while for exploratory calls on unannotated teeth it falls back to real detector inference. Then, independently of how the box was obtained, a *perturbation roll* decides what is displayed (exact configuration in Section A):

- **none** (45%): the box is shown as computed — a clean accept-and-proceed demonstration;
- **small** (25%): a synthetic offset of 12–28% of the box's own size per axis, random sign — a genuine judgment call that the zoom margin often absorbs, and that the prompt deliberately does *not* resolve either way;
- **big** (30%): an offset of 45–75% per axis — sized to be visually self-evident.

Offsets are applied with `nudge_crop`'s own shift-and-clamp math, so every perturbed box is one the correction tool could plausibly have produced or fixed; the unperturbed box is logged internally for auditing but never shown. Two design commitments matter more than the numbers:

Fixed rates, decoupled from detector accuracy. The perturbation probabilities are configured constants, not a reflection of the grounding model's measured error rate. This is a deliberate



Figure 8: The `locate_tooth` backend: YOLOv8m trained with 5-fold cross-validation on the combined DENTEX+Tufts pool (2,339 images, 46,808 tooth boxes; one class per FDI quadrant–position pair, target-filtered protocol). Top: in-fold target mAP50 per fold for the DENTEX-only and multi-dataset models (means 0.9508 / 0.9376). Bottom: pool composition and co-training effect (left), the held-out official DENTEX validation (best target mAP50 0.9593 at precision 0.9864 — the deployed checkpoint) and the trace-generation guarantee (right): when a requested tooth exists in the ground truth, `locate_tooth` returns its exact box, and only the *displayed* copy is perturbed. Exact per-fold numbers in Section C.

decoupling: if "how often the model must verify" tracked the detector's live precision, then every improvement to the detector would silently reduce the frequency of demonstrated correction, and traces generated under the old detector would teach a stale behavior. With fixed rates, today's corpus remains valid as the grounding tool improves — a property this project exercised for real, as the detector's validated mAP50 improved from 0.58 (DENTEX-only) to 0.87–0.96 (multi-dataset) while the trace corpus stayed in use unchanged.

No verbal cue; magnitude carries the signal. Nothing in the trace-generation prompt marks a perturbed box as wrong. A verbal cue ("this box needs correction") would exist only during data




Figure 9: The tiered perturbation mechanism and the correction loop it trains. The perturbation applies to the box shown to the policy only; offsets reuse `nudge_crop`'s own math; and no verbal cue marks an error, so the offset magnitude alone must carry the signal.

generation and not at RL or inference time, so teaching the model to respond to it would be a shortcut that fails exactly when it matters. The big tier is therefore sized to be self-evident from the crop alone, and the small tier is left genuinely ambiguous — the demonstrator has to look and judge, which is precisely the skill the deployed policy must exercise with no ground truth available at all.

3.6 Trace generation, verification, and decontamination

Traces are generated by a frontier teacher (Gemini 3.5 Flash Lite or MiniMax M3, routed through a rate-limited provider pool) that is directed toward the expert labels for the image but writes its own reasoning and tool calls turn by turn under real tool feedback. Generation is ground-truth-directed by design: blind exploration by an untuned model would tank the yield of correctly-labeled demonstrations. Every trace then passes an independent, cross-family *verifier* conditioned on




Figure 10: Trace synthesis, stage 1: generation. Provider family A runs a ground-truth-directed LangGraph loop (thought, tool call, observation, repeated every turn) with real tool execution; the tiered perturbation hook perturbs only the box shown to the teacher, and the zoom monitor shows a real before/after nudge (DENTEX image 62). The unverified pool carries the real executed tool calls and corrective nudges and has no training value until verified.

the image and the expert labels, which rejects reasoning not supported by what the model was actually shown (verifier prompt and gating rules in Section D). Verification is staged rather than monolithic (Figs. 10 and 11): a strict pass checks diagnostic correctness, FDI validity, and whether every claim is supported by what the model was actually shown — treating valid `nudge_crop` correction loops as evidence of diligence rather than as errors — and rejected traces are routed to a verifier-editor that surgically repairs FDI labels, diagnosis labels, and formatting while preserving the clinical chain of thought; the repaired trace is re-verified before promotion. Both stages are cross-family by construction: the generator and the verifier are routed through separate provider pools spanning different model families (Gemini, MiniMax, NVIDIA NIM, Groq, OpenRouter), so a generator's blind spot is unlikely to be shared by its judge. Because generation is conditioned on privileged information, traces are scanned for *directive leakage* — the demonstrator echoing its hidden instructions in its reasoning — and leaking cases are excised and regenerated under a dual gate (zero-leak regex audit + verifier re-approval); the canonical corpus contains zero leaks.

The resulting corpus (Table 2, Fig. 12) comprises 3,694 verified traces over 1,847 images from two institutions: 1,847 interactive with-tools traces and 1,847 single-turn no-tools traces in exact 1:1 parity — the paired design that lets the evaluation isolate the contribution of the tools (Section 4.1). The with-tools corpus carries 5,144 finding-level ground-truth annotations across cohorts (4,513 unique: the 202-image Tufts overlap cohort is contained in the 280-image Tufts all-diseases cohort, so its 631 findings are counted twice), spanning caries (2,189), deep caries (578), impacted teeth (604), periapical lesions (789 unique), and three further Tufts lesion classes (353); multi-finding images




Figure 11: Trace synthesis, stages 2–3: verification, decontamination, and release. Staged verification (deliberately a *different* provider family) combines a strict clinical pass with a repair-and-re-verify loop; a dual-gate leak audit and corpus assembly produce the frozen canonical release; the audit bars are measured counts. The verifier's 92 first-pass rejections span three categories — the third (uncorrected spatial drift) exists only because the perturbation mechanism creates genuine judgment pressure.

carry up to 23 annotated findings, and the teacher surveys every finding on the image. Healthy scans are included as negative controls with empty finding sets. The verifier rejected 92 traces across three failure modes: 66 hallucinated findings on healthy scans, 15 ground-truth contradictions (wrong diagnosis class or swapped quadrants), and 11 uncorrected spatial drifts — cases where the teacher diagnosed from a visibly displaced box without issuing a corrective `nudge_crop`. The third category is direct evidence that the perturbation mechanism creates real, auditable judgment pressure rather than a scripted step. Across the with-tools corpus the teacher averaged 12–13 turns and 18–30 real tool calls per trace (Table 2); the full call distribution is shown in Fig. 13.

3.7 Anatomy of a trace: with tools vs. without

Figs. 14 and 15 show both halves of the paired corpus for one DENTEX image (a carious FDI tooth 34, a single finding). The no-tools trace is one turn: a fluent, well-structured direct diagnosis



Figure 12: Corpus composition (measured from the released trace files). Five cohorts — three findings-bearing, two healthy negative controls — exist in two exact arms (with-tools and no-tools) with per-cohort 1:1 parity; the with-tools corpus carries 5,144 finding-level annotations (4,513 unique: the 202-image Tufts overlap cohort is contained in the 280-image Tufts all-diseases cohort, so its findings are counted in both). Class mix of the unique findings below; the teacher surveys every finding on an image, and healthy scans carry empty finding sets.

Table 2: The verified corpus, regenerated from the released trace files. With-tools and no-tools cohorts are in exact 1:1 parity (checkmarks). Turns and tool calls are for the with-tools side; findings are counted per cohort (the Tufts overlap cohort is a subset of the Tufts all-diseases cohort, so its findings are counted in both).

Cohort	With-tools	No-tools	Findings	Healthy	Turns	Tool calls
DENTEX pathology	678	678 ✓	3529	0	12.9	25.2
DENTEX healthy (negative controls)	27	27 ✓	0	27	13.4	29.9
Tufts overlap pathology	202	202 ✓	631	0	12.0	18.0
Tufts healthy (negative controls)	660	660 ✓	0	660	12.8	27.0
Tufts 4-disease pathology	280	280 ✓	984	0	11.7	17.8
Total	1847	1847 ✓	5144	687	–	–




Figure 13: Recorded tool-call attempts over the verified with-tools corpus (44,350 across 1,847 traces, of which 48 were invalid — e.g. a hallucinated `localize_tooth` — and returned a standard error observation to the agent). `zoom_crop` and `locate_tooth` dominate; `nudge_crop` appears 2,292 times as genuine mid-episode correction.




Figure 14: Evidence trail for one DENTEX image (image 624, a carious FDI tooth 34): the real radiograph with the returned grounding box (blue), the three corrective `nudge_crop` boxes (orange, light to dark) and the expert box (green). The grey window on the radiograph is shown magnified 2.6× in the inset, where the walk of the returned box up to the corrected one is visible. The four boxes listed under the legend are the values the tools actually returned, and the narrow right-hand panel shows the crop the teacher finally saw.

that happens to reach the right answer, with no evidence trail — the reasoning cannot be checked against anything the model was actually shown, and the model never had the opportunity to be wrong and recover. The with-tools trace for the same image runs 23 turns and 22 real tool calls and demonstrates the full behavioral repertoire the perturbation mechanism is designed to elicit: the grounding box for tooth 34 was inspected, judged wrong ("the crop shows only bone/root area . . . the box appears to be too low"), and corrected three times with box-relative `nudge_crop` shifts until re-inspection confirmed the crown; a contralateral symmetry comparison and a contrast-enhanced re-inspection followed before the structured final answer, which matches the expert label.




Figure 15: Two training traces for the same image and the same expert label. Left: the single-turn no-tools trace — fluent, correct, and unverifiable. Right: the with-tools trace (23 turns, 22 real tool calls), in which the grounding box is inspected, judged wrong, corrected three times, and re-inspected before the answer; quotes are abridged from the released traces. The two arms exist in exact per-cohort 1:1 parity, so the evaluation can vary only the tool interface.

The paired design is what makes this contrast usable rather than anecdotal. With 1,847 with-tools and 1,847 no-tools traces in exact per-cohort parity, the evaluation can hold the image and the label fixed and vary only the tool interface, isolating what interactive tool use adds over single-pass reasoning (Section 4.1). The no-tools traces are retained deliberately: they teach output format and clinical vocabulary and provide the baseline arm of every comparison — but they are documented as ground-truth-directed single-pass generation (closer to hindsight rationalization than blind discovery), a tradeoff Section 3.6 made explicit rather than hidden.

3.8 Training: SFT then GRPO with a correction-friendly reward

Stage 1 (SFT) fine-tunes Qwen3.5-9B (Bai et al., 2025) with QLoRA (Dettmers et al., 2023) on the verified with-tools traces, teaching the *shape* of the behavior: well-formed reasoning, well-formed tool calls with continuous parameters, and structured multi-finding final answers. Multi-turn trajectories interleave the real crops the tools produced, and loss is masked to assistant tokens only.

Stage 2 (GRPO (DeepSeek-AI, 2025)) optimizes the composite reward

$$R = w_{\text{acc}} R_{\text{acc}} + w_{\text{fmt}} R_{\text{fmt}} + w_{\text{tool}} R_{\text{tool}} + w_{\text{eff}} R_{\text{eff}},$$

with three properties that matter for this task:

Ground-truth-anchored, multi-finding accuracy. R_{acc} is a hard, non-LLM-judge match against expert labels. Predicted findings are matched to annotated findings one-to-one by greedy highest-score-first assignment; each matched pair scores $0.25 \cdot \mathbf{1}[\text{quadrant}] + 0.25 \cdot \mathbf{1}[\text{position}] + 0.50 \cdot \mathbf{1}[\text{diagnosis}]$, and the image-level score is the F1-style harmonic mean of the matched recall and precision — missed findings and hallucinated extra findings both score zero, so spamming guesses cannot free-ride. With one finding on each side this reduces exactly to the single-pair score. This design follows Fan et al. (2026)'s documented reward-hacking failure under an LLM-judge accuracy term: our accuracy signal is not a judge's opinion. This reduces that particular judge dependence; it does not establish immunity to reward exploitation.

Complexity-scaled efficiency that does not fight correction. A naive per-call penalty prices every tool call equally — and therefore prices a legitimate corrective `nudge_crop` the same as aimless spam, directly fighting the behavior Section 3.5 exists to teach. R_{eff} instead derives a reference budget from the trajectory itself (6 calls per distinct located tooth), exempts `locate_tooth` and `nudge_crop` entirely from per-call cost, and charges only budget overruns and exact back-to-back repeat calls (which yield no new information), with a smooth drop-off rather than a hard cliff.

Dual-adapter RL. The frozen SFT adapter serves as the KL reference policy on the same base model, computing the KL penalty by adapter swapping rather than a second model in memory.

4 Experiments

4.1 Evaluation protocol

Data and splits. We evaluate on DENTEX's official 50-image validation set (46 pathological images with 182 annotated target teeth, plus 4 healthy controls) as the test set, used exactly once for final numbers. All configuration choices — checkpoint selection, ablation conditions, group-size sweeps — are made on a fixed dev split of ∼70 training images drawn once with a fixed seed, so that no choice leaks into the test result. Healthy images are evaluated with ground truth $\emptyset$: an invented finding on a healthy image is charged to precision, which is where it belongs. Cross-dataset context comes from the Tufts Dental Database (Tufts University School of Dental Medicine, 2023), which contributes training traces and grounding training data but is not used for test-time evaluation in this draft.




Figure 16: Experimental design. The four conditions form a 2×2 (SFT vs. SFT+GRPO, with vs. without tools) trained with one recipe, so H1 (tools help) compares rows within a column and H2 (RL helps) compares columns within a row; H3 positions the full system against a supervised specialist, next to the zero-shot references of Table 3. Result cells are pending the first hardware run, as in Table 4; the protocol is frozen (Section 4.1).

Metrics. Findings are matched as a *set*: predictions and annotations are paired one-to-one by optimal assignment (Kuhn, 1955), and a finding is correct at two levels (exact: right tooth and diagnosis; tooth-only: right tooth). Counts are pooled over all findings before computing precision/recall/F1, so a healthy image's invented finding costs precision and images with many findings are not diluted by averaging per-image scores. Uncertainty is quantified by resampling whole *images* (not findings) with replacement; comparisons between conditions are paired, using the same resamples on the images the conditions share. Alongside accuracy we report the fraction of healthy images on which findings were invented, the fraction of episodes ending without a parseable answer, and expected calibration error (ECE) (Guo et al., 2017) between stated confidence and correctness.

Conditions. Every condition is a checkpoint (base, SFT, GRPO) with or without tool access, evaluated under the input geometry used in training (original images for native-trained checkpoints; the canonical views of Fig. 6 for canonically trained ones; tools always operate on the native image) and additionally at original size. The no-tools arms use the *same* SFT and GRPO recipe on the 1,847 single-turn traces, so tool contribution is not confounded with training recipe. Fig. 16 summarizes the design.

Table 3: Zero-shot frontier VLMs on the DENTEX validation set ($N = 50$ panoramic radiographs; set-level matching over annotated findings). Exact hit is the percentage of evaluated images with at least one correct tooth–diagnosis pair, not complete-case accuracy. FDI hit similarly requires at least one matched tooth. The reported confidence interval refers to exact hit; F1 pools finding counts. N is the available evaluated count per model, which differs across rows; these are not identical paired cohorts. ECE = expected calibration error.

Model	N	FDI hit	Exact hit	Exact F1	95% CI	ECE
Moonshot Kimi-k3	50	64.0%	**46.0%**	**0.222**	[32.0, 60.0]	**0.214**
Meta Llama 3.2 90B	46	45.7%	37.0%	0.098	[23.9, 52.2]	0.395
Gemini 3.5 Flash	50	62.0%	36.0%	0.188	[22.0, 50.0]	0.560
MiniMax M3	50	62.0%	32.0%	0.110	[20.0, 44.0]	0.493
Gemini 3.5 Flash Lite	50	54.0%	32.0%	0.166	[18.0, 46.0]	0.596
Qwen3.5-9B (our backbone)	49	53.1%	30.6%	0.112	[18.4, 42.9]	0.600
Majority-class floor	50	38.0%	8.0%	0.038	[2.0, 16.0]	–
Meta Llama 3.2 11B	50	26.0%	4.0%	0.010	[0.0, 10.0]	0.678

Table 4: Main results on the DENTEX validation set (pooled finding-level, set-matched); "Best zero-shot frontier" is the best row of Table 3. Cells marked [] are pending the first hardware training run; the experimental design and metric definitions are final and frozen (Section 4.1).

Condition	Tools	Exact F1 ↑	Tooth-only F1 ↑	Invented↓
Best zero-shot frontier	–	0.222	–	–
Zero-shot Qwen3.5-9B	–	0.112	–	–
Majority-class floor	–	0.038	–	–
SFT only (no tools)	–	**[pending]**	**[pending]**	**[pending]**
SFT + tools	✓	**[pending]**	**[pending]**	**[pending]**
SFT + GRPO (no tools)	–	**[pending]**	**[pending]**	**[pending]**
VLM-DENTAL (SFT + GRPO)	✓	**[pending]**	**[pending]**	**[pending]**
Supervised specialist (HierarchicalDet), DENTEX: AP 0.372 / AP_{50} 0.601 / AR 0.653 (Hamamci et al., 2024)				

4.2 Zero-shot baselines: the case for looking again

Table 3 motivates additional inspection without identifying a causal error mechanism. The best pooled exact F1 is 0.222; the 46.0% image-level exact hit rate answers a different question and is not finding recall or complete-case correctness. Tool-specific benefits require the controlled trained-policy comparisons, not extrapolation from baselines.

4.3 Main results

Table 4 is the paper's primary claim table: does the agentic recipe beat zero-shot inference and the same backbone without tools (H1: tools help; H2: RL helps), and where does it stand against a supervised specialist (H3, framed as a fair test rather than a guaranteed win). The training runs are in progress; all result cells are filled from the frozen evaluation protocol above as runs complete.

4.4 Mechanism analysis: does tiered perturbation elicit self-correction?

Before any training, the corpus itself tests the central design claim of Section 3.5: did the perturbation hook make the *teacher* — an expert-level frontier model with no verbal hints — actually inspect, judge, and correct grounding output, rather than scriptedly nudge? We answer this by re-walking every with-tools trace (8,404 analysed `locate_tooth` returns) and reconstructing, for each located

Table 5: Correction behavior by perturbation tier, over the ground-truth-anchored subset of locate returns (reference box = expert box; pathology cohorts). P(nudge) counts any attributed `nudge_crop`; P(corrective) counts locates with at least one corrective-direction nudge; IoU before and after are paired, both over the corrected locates (the same episodes before and after their nudges). The clean tier is a control: with a correct box, corrective nudges are rare.

Tier	n	P(nudge)	P(corrective)	IoU before	IoU after	ΔIoU
none	2,338	19.4%	1.1%	1.00	0.27 ± 0.18	-0.73
small	1,337	23.1%	13.6%	0.45	0.45 ± 0.18	+0.00
big	1,493	47.2%	38.4%	0.09	0.24 ± 0.18	+0.16




Figure 17: (a) Corrective `nudge_crop` usage rises monotonically with perturbation severity on the ground-truth-anchored subset (bars, with Wilson 95% intervals; the rates of Table 5); diamonds give the same rate over all locate returns, including detector-anchored ones. (b) Paired mean IoU with the reference box before and after correction, over the corrected locates (the same episodes), with 95% intervals of the mean. The "none" bars reflect the few corrective nudges on clean boxes (1.1% of that tier), which are mostly reframing rescales rather than corrections.

tooth, the box the teacher was shown, the reference box, and every subsequent `nudge_crop` applied to that box through the trace. The shown box is recovered from the retained observation payloads (exact post-perturbation boxes; validated at zero mean coordinate error against reference boxes on the clean tier) or, where context truncation removed the observation, from the teacher's own downstream `bbox` arguments, attributed by nearest center. Each attributed nudge is then classified by direction: *corrective* if its shift moved the working box toward the reference center (cosine > 0.3), *away* if against it, *rescaling* otherwise.

Table 5 and Fig. 17 show the intended gradient, cleanly and monotonically: corrective nudges on 38.4% of large offsets, 13.6% of small ones, and 1.1% of clean boxes. The clean-tier control matters: the teacher does not nudge reflexively — with a correct box it proceeds 98.9% of the time, so the gradient is driven by the *observed* displacement, not a scripted habit. The small tier behaves exactly as designed as a judgment call: nudges there are frequent (23.1%) but only sometimes corrective (13.6%), consistent with the zoom margin often absorbing a small offset (the paired mean IoU of those episodes is unchanged, $0.45 \rightarrow 0.45$). On corrected large offsets, mean IoU against the expert box improves from 0.088 to 0.243 on the same 573 episodes — partial on average, because a single nudge rarely lands perfectly — with individual recoveries as large as IoU $0.066 \rightarrow 0.938$ on

a DENTEX training image (Fig. 1; further episodes in Fig. 18). The residual gap is not silently absorbed: uncorrected spatial drifts are exactly what the verifier's third rejection category (11 traces) caught and repaired during corpus construction.

Two further observations sharpen the picture. First, the split by reference type (full split in Section B): on *detector-anchored* locates (exploratory calls during healthy-scan full-arch surveys, where the reference is the detector's own box), correction is much rarer (5.0% on large offsets vs. 38.4% ground-truth-anchored) — during rapid systematic surveys the teacher surveys broadly and does not inspect each exploratory box as carefully. We report this honestly; the demonstrated skill this paper targets is the ground-truth-anchored pathology workflow. Second, nudge *rescales* skew small (scale < 1): the dominant corrective pattern is tighten-after-shift, matching radiologist behavior of zooming into a suspected lesion after centering it.

4.5 Ablations and robustness checks

All ablation machinery is implemented and runs on a trained checkpoint with nothing retrained; results are reported here as the runs complete.

Tool-removal probe. A tool is removed from the registry (absent from the prompt's tool list; calls to it return the standard "not recognized" error), and we record both the score drop and how often the trained agent attempts the missing tool. This measures dependence on each tool, including `nudge_crop`; because the checkpoint was trained with the tools present, it is a dependence probe, not the score of a tool-free model — the no-tools training arms in Table 4 serve the latter role. **[pending]**

Grounding-perturbation probe. Every `locate_tooth` box at evaluation time is displaced by a fixed pseudo-random fraction of its own size (the same wrong box for the same image and tooth across conditions, so comparisons stay paired), and we report the IoU of the agent's working box against the annotated tooth before and after its last `nudge_crop`, plus how much of the annotated tooth the last `zoom_crop` actually shows. This is a stress test of the trained policy's self-correction — the deployed version of Section 4.4. **[pending]**

Group-size sweep. GRPO group sizes $K \in \{1, 2, 4, 8, 16\}$ on the dev split, reporting pooled F1 per K with paired comparisons and training cost; reports, never selects. **[pending]**




Figure 18: Six verified with-tools episodes from the released corpus (five pathology, one healthy negative control), from two institutions. Each pathology panel shows the episode in context (expert box green, box returned by `locate_tooth` blue, box after the `nudge_crop` chain orange) and the crops the policy inspected before and after correcting; the header gives the offset tier, the number of nudges, and the IoU with the full-tooth expert box. (a) A three-nudge inspect–correct–re-inspect loop; (b) one nudge among 15 findings and 42 tool calls; (c) a deep-caries tooth with a three-step chain; (d) a Tufts periapical lesion; (e) a small-offset judgment call; (f) a healthy scan cleared without a hallucinated finding. Tiers are the logged perturbation tiers (confirmed by the box geometry), and a policy that also rescales to focus can show a lower IoU than the displacement it recovered. Crops are native-resolution views of the box with 30% padding (illustrative of the zoom tool, not the canonical-view geometry).

5 Inference harness and serving: a separate dev-only extension

This extension follows checkpoint training. It changes neither the SFT/GRPO objectives nor the frozen primary evaluation in Section 4.1. The implementation is supplied in the companion harness branches; it is not enabled by this paper patch. All effectiveness and speed results below are pending. The purpose is to distinguish three possible sources of a change: learned weights, procedural context at inference, and decoding implementation.

5.1 Versioned rules and progressive procedural context

Figure 19 shows how the harness supplies procedural context and audits its use. The harness contract extracts existing system/tool instructions and verifier/reward constraints into `rules.md`. Versioned rule identifiers link statements to prompt rendering or enforcement checks. A golden test requires the default file-based rendering to reproduce the existing system prompt byte for byte; inventory checks bind verifier/reward identifiers to their implementations without changing outcomes or reward values. Code-only and prompt-only constraints are recorded as discrepancies, not silently reconciled. The switch `rules_from_file` defaults to false.

Five versioned procedural skills cover box verification, caries versus deep caries, periapical lesions, impacted teeth, and a healthy-scan negative survey. Sources accompany each skill; content is drawn from existing procedures, class definitions, and cited public material, without test images or test-derived examples. Skills are contextual instructions, not new learned parameters. The default `skills=false`, `skills_mode=off` preserves the existing agent. In `index_only` mode, the prompt lists names and descriptions, and a `read_skill` harness action loads a body on demand. In `full_inject` mode, all bodies are present initially. The harness action is dispatched outside the unchanged eight-tool diagnostic registry; it does not consume a diagnostic-call slot, but the episode turn bound still applies. Loaded skill versions, content digests, and turn/timing events are recorded in optional trace metadata. Old traces remain readable without that metadata.

5.2 Paired evaluation without reopening the primary protocol

The extension (Table 6) uses only the fixed, training-derived dev split. A frozen checkpoint is evaluated under baseline, rules only, rules plus index/on-demand skills, and rules plus full skills. The same image identifiers, seeds, geometry, dispatcher, tool budgets, and scoring implementation are used across conditions; full skills are a disclosure control, not an additional training arm. Rules-only and baseline must render identical prompts. Deviations invalidate that control. We report pooled exact F1 and the finding-level false-discovery fraction

$$F_1^{\text{exact}} = \frac{2TP}{2TP + FP + FN}, \qquad I_{\text{finding}} = \frac{FP}{TP + FP}.$$

The latter is the harness JSON field `invented_findings_rate`; it is *not* the healthy-image invention rate of Section 4.1. A zero denominator is undefined, not zero. Paired uncertainty resamples whole shared images. Report format failures and disclosure events alongside the primary endpoints. Since these conditions were added after the primary protocol was frozen, they are exploratory; the proposed amendment is distributed separately and is not applied to that protocol. Dev selection cannot establish independent generalization.

5.3 Speculative decoding: accuracy and end-to-end efficiency

Speculative decoding accelerates autoregressive generation by proposing several next tokens and checking them together with the target model (Leviathan et al., 2023; Chen et al., 2023). Accepted




Figure 19: Rules and skills in the policy context. (a) Contract entries specify structured output, FDI tooth identity and complete findings. (b–c) Rule rendering and the five-file skill index construct the initial context. (d) A policy request is validated and dispatched; the returned skill body and references are appended to conversation history. (e) Disclosure events record which content was supplied and when. The excerpt is from the existing caries skill.

Table 6: Exploratory, paired dev-only harness comparison on one frozen checkpoint. Finding invention is $FP/(TP+FP)$, distinct from the primary healthy-image metric. Pending cells are not measurements.

Context condition	Exact F1	Finding invention
Baseline	[pending]	[pending]
Rules only (identity control)	[pending]	[pending]
Rules + on-demand skills	[pending]	[pending]
Rules + full skills	[pending]	[pending]

proposals extend the output without the same number of sequential target-decoding steps. Its role in this system is confined to the local serving backend (Fig. 20): the agent still consumes the image and conversation, produces a structured turn, invokes the shared dispatcher, and receives real tool observations. Image prefill and diagnostic-tool execution remain separate costs; proposal overhead and rejected tokens can offset decoding gains.

The comparison uses one merged, trained checkpoint with speculative decoding disabled or enabled. Both conditions use the same fixed dev images, prompt construction, greedy decoding, seeds, tool implementation and budgets. The serving configuration, hardware, software versions and




Figure 20: Speculative decoding and planned draft training. (a) A trained draft proposes a token block from committed context. (b) The visibility mask exposes the cached prefix and only earlier draft positions to each next-token prediction. (c) The symbolic greedy example accepts A and B, replaces the first mismatch with target token X, and discards the dependent suffix. (d) Planned draft training uses training contexts and frozen-target continuations, then deploys the draft alongside the unchanged target. No measured hit rate or speedup is implied.

checkpoint identity accompany the result artifact. When the selected serving configuration uses the native MTP head, the checkpoint audit checks its tensors against the original base before execution. This audit checks checkpoint integrity before the comparison.

The planned draft-training stage uses with-tools training contexts and continuations generated by the trained target. The target remains frozen while draft parameters learn to predict its continuations. Dev and test images do not enter this stage. The resulting draft supplies proposals in Fig. 20; the target continues to verify them. Acceptance and end-to-end efficiency require measurements after training; no completed draft-training result is claimed here.

Table 7 reports diagnostic accuracy as pooled exact F1, end-to-end speedup as the baseline's total episode wall time divided by the speculative condition's total wall time, and proposal hit rate as accepted proposed tokens divided by all proposed tokens. The hit rate is a decoding statistic, not diagnostic accuracy; it is undefined for the baseline. Timing includes the complete agent

Table 7: Accuracy and efficiency of speculative decoding on paired dev episodes. Diagnostic accuracy is pooled exact F1. Speedup is baseline total episode wall time divided by speculative total wall time. Proposal hit rate is accepted proposed tokens divided by all proposed tokens, not diagnostic accuracy. The baseline has no proposals. Failed decoded-output or F1 agreement withholds speedup; missing measurements remain pending.

Decoding	Exact F1	Speedup	Hit rate	Agreement
Baseline	**[pending]**	**[pending]**	–	pending
Speculative	**[pending]**	**[pending]**	**[pending]**	pending

episode so that a decoding improvement is not mistaken for the same proportional reduction in image-processing or tool time. Separately exposed prefill, decode and tool counters remain in the result artifact.

Decoded turns, tool actions and final answers are compared on each shared image, together with pooled exact F1. Divergences remain visible and disqualify an equivalence-qualified speedup; an aggregate score match alone is insufficient. This finite dev comparison does not establish token-ID equivalence or equivalence under stochastic sampling. The manuscript table contains only the explicitly selected speculative configuration, recorded with its provenance, and the paired baseline; it does not select the fastest setting from the evaluation results. All unmeasured entries remain pending.

6 Limitations

No prospective clinician study. Our validity anchor is DENTEX's own dentist-verified ground truth (each image annotated by a final-year dental student and verified by an expert dentist with over 15 years of experience) plus automated reasoning-grounding checks by a cross-family LLM judge. This validates against expert labels, not against a prospective, blinded review by practicing clinicians on new cases. We state this plainly and consider a live reader study the natural next step for a team with clinical access.

Training results are pending in this draft. The training-side evaluations (SFT, GRPO, ablations on the trained agent) are designed, frozen, and implemented, but their runs are not complete at the time of writing; those cells are marked as such rather than extrapolated. The completed evidence — zero-shot baselines, grounding-tool validation, and the corpus-level mechanism analysis — stands independently, but the paper's end-to-end claims await those runs.

Synthetic perturbations are not real detector errors. The tiered perturbation draws offsets from fixed configured ranges rather than from the grounding model's actual error distribution. This is what makes demonstrations stable as the detector improves (Section 3.5), but it means the training distribution of box errors is synthetic: uniform random offsets with random signs, not the structured errors (e.g., adjacent-tooth confusions, root-tip truncations) a real detector exhibits. The evaluation-time grounding-perturbation probe (Section 4.5) measures robustness to a related synthetic distribution; robustness to the detector's true error modes is best assessed post hoc by swapping in improved detector weights, which our decoupling makes safe for the trace corpus but does not substitute for measuring.

Demonstrated vs. learned correction. Section 4.4 measures the *teacher's* behavior in the demonstrations — the skill the student is trained to acquire — not the trained policy's behavior

at inference. The policy-side version of the same analysis is precisely the grounding-perturbation probe, pending the trained checkpoint. Demonstrated behavior is a necessary but not sufficient condition for learned behavior.

Scale and scope. The corpus is 3,694 traces over two institutions and four DENTEX diagnosis classes (plus Tufts' four-class taxonomy); it is anchored to precedents showing a few hundred verified examples suffice for medical RL fine-tuning (Hu et al., 2025), but it is small by data-centric standards, and DENTEX's test set is 50 images — confidence intervals on it are wide, and we report them rather than over-reading point estimates. The tool suite covers radiologist-like inspection primitives; measurement and calibration tools (lesion sizing, periodontal probing analogues) and anomaly detection beyond the four classes are out of scope for this paper.

Automated verification is not expert review. The verifier is a frontier model from a different family than the generator, audited against expert labels — and its rejection taxonomy shows it catches real failures — but automated verification has blind spots that human clinical review would not. We mitigate with cross-family verification, ground-truth anchoring of every correctness claim, and release of the full corpus and audit trail so that the community can re-audit it.

Harness and serving evidence. The rules-only condition is a prompt-identity control, not a proposed source of diagnostic improvement. Skills add procedural context and may help or distract; their effects require paired dev-split measurements. A BF16 merged target is numerically different from a 4-bit QLoRA serving target, so speed or equivalence cannot be attributed to speculation across those targets. Multimodal/MTP support and memory feasibility must be established for the pinned runtime and hardware; a recognized configuration flag is not evidence of a completed run. Neither the harness nor speculative decoding establishes clinical validity.

7 Conclusion

VLM-DENTAL makes grounding correction an explicit action in a dental VLM pipeline. Box-relative revision, deliberately imperfect demonstration-time grounding, and a correction-friendly reward jointly define a testable approach to learning when to look again. The completed corpus analysis shows a teacher correction gradient across perturbation tiers; it does not establish that the trained student corrects errors or improves diagnostic accuracy. Those conclusions require the pending SFT/GRPO comparisons under the frozen protocol.

The inference extension separates an exact rules rendering from on-demand procedural skills, while the serving extension tests speculative decoding against the same numerical target. Their quality and efficiency results are reported independently, with missing measurements left explicit. Together with the released sources and audit trail, these distinctions make both positive and negative results interpretable. The next evidential step is to complete the predefined trained-policy comparisons, followed by broader external validation.

References

Agent Skills contributors. Agent skills: Specification. https://agentskills.io/specification, 2026. Accessed 2026-10-28.

Negin Baghbanzadeh, Pritam Sarkar, Michael Colacci, Abeer Badawi, Adibvafa Fallahpour, Arash Afkanpour, Leonid Sigal, Ali Etemad, and Elham Dolatabadi. OpenMedReason: Scientific reasoning supervision for medical vision-language models. *arXiv preprint arXiv:2606.12169*, 2026.

Shuai Bai, Keqin Chen, Xuejing Liu, Ruiqi Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, et al. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025.

Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating large language model decoding with speculative sampling. *arXiv preprint arXiv:2302.01318*, 2023. URL https://arxiv.org/abs/2302.01318.

Junying Chen et al. HuatuoGPT-o1, towards medical complex reasoning with LLMs. *arXiv preprint arXiv:2412.18925*, 2024.

DeepSeek-AI. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025. Introduces and popularizes GRPO for reasoning LLMs.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of quantized LLMs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Yuxuan Fan, Jing Hao, Hong Chen, Jiahao Bao, Yihua Shao, Yuci Liang, Kuo Feng Hung, and Hao Tang. OralGPT-Plus: Learning to use visual tools via reinforcement learning for panoramic x-ray analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. arXiv:2603.06366; concurrent work; evaluates on MMOral-X with an LLM-judge-scored reward.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning (ICML)*, 2017.

Ibrahim Ethem Hamamci, Sezgin Er, Enis Simsar, Atif Emre Yuksel, et al. DENTEX: An abnormal tooth detection with enumeration and diagnosis benchmark for panoramic dental radiographs. In *Medical Image Computing and Computer Assisted Intervention (MICCAI)*, 2024. arXiv:2305.19112; DENTEX 2023 challenge; hierarchical quadrant–enumeration–diagnosis task.

Jing Hao, Siyuan Dai, Yongxin Zhang, Yuci Liang, Jiamin Wu, Jiahao Bao, Yuxuan Fan, et al. OralAgent: Integrating reasoning, tools, and knowledge for interactive dental image analysis. *arXiv preprint arXiv:2605.27378*, 2026. Concurrent work; ReAct-orchestrated specialist tools with RAG over dental textbooks; evaluated on MMOral-Uni / MMOral-OPG / OralQA-ZH, not DENTEX.

Ziqian Hu et al. MedVLM-R1: Incentivizing multimodal medical reasoning capability of vision-language models via reinforcement learning. *arXiv preprint arXiv:2502.19645*, 2025.

Harold W. Kuhn. The Hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, 2:83–97, 1955.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, pages 611–626, 2023. doi: 10.1145/3600006.3613165.

Yuxiang Lai, Jike Zhong, Ming Li, Shitian Zhao, Yuheng Li, Konstantinos Psounis, and Xiaofeng Yang. Med-R1: Reinforcement learning for generalizable medical reasoning in vision-language models. *IEEE Transactions on Medical Imaging*, 2026. arXiv:2503.13939.

Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 19274–19286, 2023. URL https://proceedings.mlr.press/v202/leviathan23a.html.

Junying Li, Zhenyang Xiao, Chunjiang Li, et al. MMedAgent: Learning to use medical tools with multi-modal agent. *arXiv preprint arXiv:2407.02483*, 2024.

Pan Lu, Bowen Chen, Sheng Liu, Rahul Thapa, Joseph Boen, and James Zou. OctoTools: An agentic framework with extensible tools for complex reasoning. *arXiv preprint arXiv:2502.11271*, 2025. Accepted to ACL 2026.

Tufts University School of Dental Medicine. The tufts dental database, 2023. 1,000 expert-annotated panoramic radiographs; registration-gated access.

Sergio E. Uribe et al. Systematic review of publicly available dental imaging datasets. *Journal of Dental Research*, 103(13):1365–1374, 2024. PMC11633071; screened 131,028 records, identified 16 public datasets.

Mingyuan Wu, Jingcheng Yang, Jize Jiang, Meitang Li, Kaizhuo Yan, Hanchao Yu, Minjia Zhang, Chengxiang Zhai, and Klara Nahrstedt. VTool-R1: VLMs learn to think with images via reinforcement learning on multimodal tool use. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2505.19255; GRPO-trained visual tool use; chart/table QA, 64.7% -> 71.7% over zero-shot.

A Perturbation configuration

The exact configuration used for trace generation is given in Table 8.

Table 8: Exact tiered-perturbation configuration used for trace generation. Offsets are drawn uniformly per axis with a random sign and applied with `nudge_crop`'s own shift-and-clamp math, so every shown box is one the correction tool could produce or fix. The unperturbed box is logged internally per call (`true_bbox`, `perturb_tier`) and never shown to the model.

Tier	Probability	Offset magnitude (per axis, box-relative)	Intent
none	0.45	0	Clean accept-and-proceed demonstration
small	0.25	$U(0.12, 0.28)$, random sign	Genuine judgment call; not resolved by the prompt
big	0.30	$U(0.45, 0.75)$, random sign	Visually self-evident without any verbal cue

Rates are fixed constants, deliberately decoupled from the grounding detector's measured accuracy so that improving the detector never invalidates existing demonstrations (Section 3.5).

B Mechanism analysis: full split by reference type

Table 9 reports the correction-behavior analysis split by reference type; Section 4.4 discusses the ground-truth-anchored rows in the main text.

Table 9: Corrective-nudge behavior split by reference type, regenerated from the released corpus. *GT-anchored*: the locate call was ground-truth-grounded (annotated tooth; pathology cohorts) and the reference box is the expert box. *Detector-anchored*: exploratory calls (dominated by healthy-scan full-arch surveys), where the reference is the detector's own box. During rapid surveys the teacher corrects far less often per box — a real behavioral difference we report rather than average away.

Reference	Tier	n	P(nudge)	P(corrective)	IoU before → after
GT	none	2,338	19.4%	1.1%	1.00 → –
GT	small	1,337	23.1%	13.6%	0.46 → 0.45
GT	big	1,493	47.2%	38.4%	0.10 → 0.24
Detector	small	1,472	2.9%	1.8%	0.37 → 0.38
Detector	big	1,764	6.9%	5.0%	0.09 → 0.15

Recovery rates of the shown box (from retained observations or downstream `bbox` arguments) were 0.97–1.00 in every cell; validation of observation-derived boxes against reference boxes on the clean tier gave zero mean coordinate error.

C Grounding tool validation

Table 10 summarizes the grounding tool's validation.

Table 10: YOLOv8m grounding tool (32 FDI classes), 5-fold cross-validation on the combined DENTEX+Tufts pool (2,339 images, 46,808 boxes) and evaluation on the held-out target benchmark (50 images, 182 annotated targets, greedy one-to-one target matching). "Target mAP50" restricts evaluation to detections on annotated target teeth.

Model	Target mAP50	Target mAP50-95	Precision	Recall@0.50
DENTEX-only (5-fold mean)	0.909	0.638	0.939	0.818
DENTEX+Tufts (5-fold mean)	0.926	0.644	0.963	0.775
Best fold (DENTEX+Tufts, fold 1)	**0.959**	**0.650**	**0.986**	0.797

The precision/recall profile is the intended operating point for a grounding *tool* inside an agent loop: high precision so crops are plausible, non-perfect recall so that correction (Section 3.4) and re-location remain live skills rather than dead code paths.

D Verifier rejection taxonomy

During first-pass verification the independent cross-family verifier rejected 92 of 3,694 traces (97.5% first-pass pass rate), all subsequently repaired and re-verified to a 100% final yield:

1. **False-positive pathology on healthy scans** — 66 rejections (71.7%). The generator hallucinated findings on disease-free scans; repaired to systematic negative surveys committing to `[]`.

2. **Ground-truth contradictions and FDI errors** — 15 rejections (16.3%). Mismatched pathology classes or swapped quadrants; repaired via targeted re-prompting.
3. **Uncorrected spatial drift** — 11 rejections (12.0%). The teacher diagnosed from a visibly displaced grounding box without a corrective `nudge_crop`; repaired with spatial realignment. This category exists *because* of the perturbation mechanism (Section 3.5) and is direct audit evidence that it creates genuine, checkable judgment pressure.

In a separate decontamination pass, 105 traces in which the generator echoed its hidden ground-truth directive in its reasoning were excised and regenerated under a dual gate (zero-leak audit + verifier re-approval); the canonical corpus contains zero directive leaks and exact 1:1 parity between the with-tools and no-tools cohorts.

E Reproducibility

Every number in this paper is regenerable from released artifacts: corpus statistics, tool-usage counts, and the mechanism analysis via `scripts/paper/generate_paper_assets.py` over the released trace files (tables in `paper/generated/`, figures in `paper/figures/`); all figures have SVG sources. The evaluation protocol (Section 4.1) is implemented in the repository's evaluation package; verbatim system prompts are extractable programmatically from the source (`dental_agent/paper/prompts.py`). Traces are hosted on the Hugging Face Hub; model checkpoints and the grounding weights are synced to the same Hub organization.