The data layer: two sources in use, eight candidates on file

a candidate is promoted only after its annotation semantics are verified -
two loaders deliberately stop at one open question each

IN USE — feeds the released corpus

DENTEX — 2,332 images

quadrant · enumeration · diagnosis labels
4 pathology classes + box coordinates

the only panoramic source pairing tooth position
with all four reward-relevant classes

loader: complete

contributes 705 corpus traces
(678 pathology + 27 healthy)

grounding pool: 1,339 images · 21,624 tooth boxes

Tufts Dental Database — 1,000 images

per-tooth boxes (Universal Numbering)
expert pathology layer · 25,184 boxes

periapical maps onto the DENTEX taxonomy;
no caries findings in this layer

loader: partial - 1 open question

contributes 1,142 corpus traces
(202 overlap + 660 healthy + 280 all-diseases)

grounding pool: 1,000 images · 25,184 boxes

CANDIDATE POOL — pending - not used in this work

Dental Radiography	1,272	**DNS (UFBA-UESC)**	543
no confirmed diagnosis taxonomy		FDI boxes in COCO - access on request	
(systematic review)		(targeted follow-up)	
Segmented Mandibles	232	**TL-pano**	197
mandible-only masks, not per-tooth		FDI + quadrant labels - NC license	
(systematic review)		(targeted follow-up)	
TK Tooth Number Code	188	**Tunisia Panoramic**	180
numbering only, no diagnosis		in progress - 1 open FDI question	
(systematic review)		(systematic review)	
Panoramic-Paraguay	135	**Panoramic-Caries-Seg**	75
thin documentation in the review		binary caries masks (pixel level)	
(systematic review)		(systematic review)	

diagnosis-labeled: 1 of 8 (binary caries masks) · grounding-only: 7 of 8
promotion rule: verified end-to-end annotation semantics, per dataset

catalog transcribed from a systematic review of 16 public dental imaging datasets
(Uribe et al. 2024) plus targeted follow-up search

the diagnosis-label vs grounding-only flag drives purpose: grounding candidates generalize
locate_tooth, diagnosis candidates feed trace generation