The data layer: two sources in use, eight candidates on file

a candidate is promoted only after its annotation semantics are verified - two loaders deliberately stop at one open question each

IN USE

feeds the released corpus

DENTEX — 2,332 images

quadrant · enumeration · diagnosis labels
4 pathology classes + box coordinates

the only panoramic source pairing tooth position
with all four reward-relevant classes

loader: complete

contributes 705 corpus traces

(678 pathology + 27 healthy)

grounding pool: 1,339 images · 21,624 tooth boxes

Tufts Dental Database — 1,000 images

per-tooth boxes (Universal Numbering)
expert pathology layer · 25,184 boxes

periapical maps onto the DENTEX taxonomy;
no caries findings in this layer

loader: partial - 1 open question

contributes 1,142 corpus traces

(202 overlap + 660 healthy + 280 all-diseases)

grounding pool: 1,000 images · 25,184 boxes

CANDIDATE POOL

pending - not used in this work

Dental Radiography 1,272	no confirmed diagnosis taxonomy	(systematic review)
DNS (UFBA-UESC) 543	FDI boxes in COCO - access on request	(targeted follow-up)
Segmented Mandibles 232	mandible-only masks, not per-tooth	(systematic review)
TL-pano 197	FDI + quadrant labels - NC license	(targeted follow-up)
TK Tooth Number Code 188	numbering only, no diagnosis	(systematic review)
Tunisia Panoramic 180	in progress - 1 open FDI question	(systematic review)
Panoramic-Paraguay 135	thin documentation in the review	(systematic review)
Panoramic-Caries-Seg 75	binary caries masks (pixel level)	(systematic review)

diagnosis-labeled: 1 of 8 (binary caries masks) · grounding-only: 7 of 8

promotion rule: verified end-to-end annotation semantics, per dataset

catalog transcribed from a systematic review of 16 public dental imaging datasets (Uribe et al. 2024) plus targeted follow-up search

the diagnosis-label vs grounding-only flag drives purpose: grounding candidates generalize locate_tooth, diagnosis candidates feed trace generation