### **Tutorial 8**

COMP 5361: Discrete Structures and Formal Languages

#### Mohammad Reza Davari

Concordia University



### Outline

Introduction to Automata Theory

2 Deterministic Finite Automata (DFA)

3 Examples



### Contents of the section

Introduction to Automata Theory

- ② Deterministic Finite Automata (DFA)
- 3 Examples



# **Alphabets**

### Definition

An alphabet is a finite, nonempty set of symbols. Conventionally, we use the symbol  $\boldsymbol{\Sigma}$  for an alphabet.



# **Alphabets**

#### **Definition**

An alphabet is a finite, nonempty set of symbols. Conventionally, we use the symbol  $\boldsymbol{\Sigma}$  for an alphabet.

### Example

Example 1:  $\Sigma = \{0, 1\}$ 

Example 2:  $\Sigma = \{a, b, c\}$ 

Example 3:  $\Sigma = \{1, a, 2, b, \#\}$ 



#### Definition

- Word: A word (or sometimes string) is a finite sequence of symbols chosen from some alphabet.
- **Empty String**: The empty string is the string with zero occurrences of symbols. This string, denoted  $\epsilon$ , is a string that may be chosen from any alphabet whatsoever.
- Length of a Word: Length of a Word is equal to the number of symbols in the word.
- Powers of an Alphabet: The set of strings of length k, each of whose symbols is in  $\Sigma$ , is the  $k^{\text{th}}$  power of the alphabet, i.e.  $\Sigma^k$ .



Mohammad Reza Davari 5 / 20

## Example

```
Let \Sigma = \{0, 1\}
```

Example 1:  $\Sigma^1 = \{0, 1\}$ 

Example 2:  $\Sigma^2 = \{00, 01, 10, 11\}$ 

Example 3: |01| = 2

Example 4:  $|\epsilon| = 0$ 



#### **Definition**

Let  $\Sigma$  be set of the alphabet, then:

Set of all words over the alphabet:

$$\Sigma^* = \Sigma^0 \cup \Sigma^1 \cup \Sigma^2 \cup \dots$$

• Set of nonempty strings over the alphabet:

$$\Sigma^+ = \Sigma^1 \cup \Sigma^2 \cup \Sigma^3 \cup \dots$$



### Definition

Let  $\Sigma$  be set of the alphabet, then:

• **Concatenation**: Let *x* and *y* be words, then *xy* denotes the concatenation of *x* and *y*.



#### **Definition**

Let  $\Sigma$  be set of the alphabet, then:

• Concatenation: Let x and y be words, then xy denotes the concatenation of x and y.

### Example

Let x = 01101 and y = 110, then:

- y = 01101110
- yx = 11001101



## Language

### **Definition**

Let  $\Sigma$  be set of the alphabet, then:

• Language: A set of words all of which are chosen from some  $\Sigma *$  is called a language.



## Language

#### Definition

Let  $\Sigma$  be set of the alphabet, then:

• Language: A set of words all of which are chosen from some  $\Sigma *$  is called a language.

## Example

- Example 1: The language of all words consisting of n 0's followed by n 1's, for some  $n \ge 0$ :  $\{\epsilon, 01, 0011, 000111, \dots\}$
- Example 2: The empty language:  $\emptyset$
- Example 3: The language consisting of only the empty string:  $\{\epsilon\}$



Mohammad Reza Davari 9 / 20

## Contents of the section

Introduction to Automata Theory

2 Deterministic Finite Automata (DFA)

3 Examples



#### Definition

DFA: A deterministic finite automaton is a five-tuple consists of:

$$M = (Q, \Sigma, \delta, q_0, F)$$

- A finite set of states, often denoted Q.
- $\bigcirc$  A finite set of input symbols, often denoted  $\Sigma$ .
- A start state  $q_0$ , one of the states in Q.
- A set of final or accepting states F. The set F is a subset of Q.
- **o** A transition function  $\delta$  that takes as arguments a state and an input symbol and returns a state.



Mohammad Reza Davari 11 / 20

#### Definition

- Transition diagram for a DFA: A transition diagram for a DFA is a graph defined as follows:
  - **1** For each state in *Q* there is a node.
  - ② For each state q in Q and each input symbol a in  $\Sigma$ , let  $\delta(q,a)=p_q$ . Then the transition diagram has an arc from node q to node  $p_q$ , labeled a.
  - **3** There is an arrow into the start state  $q_0$ , labeled Start.
  - Nodes corresponding to accepting states (those in F) are marked by double circle



Mohammad Reza Davari

#### Definition

• Transition table for a DFA: A transition table is a conventional, tabular representation of a function like  $\delta$  that takes two arguments and returns a value. The rows of the table correspond to the states, and the columns correspond to the inputs. The entry for the row corresponding to state q and the column corresponding to input a is the state  $\delta(q,a)$ .



Mohammad Reza Davari 13 / 20

### Definition

• Extended Transition Function: The extended transition function is a function that takes a state q and a word w and returns a state p, the state that the automaton reaches when starting in state q and processing the sequence of inputs w. If the transition function is denoted by  $\hat{\delta}$ , the extended transition function is denoted by  $\hat{\delta}$ .



Mohammad Reza Davari 14 / 20

### Definition

 The Language of the DFA: The language of the DFA is the set of all strings that the DFA accepts. This language is denoted by L(A):

$$L(A) = \{w | \hat{\delta}(q_0, w) \text{ is in } F\}$$



Mohammad Reza Davari 15 / 20

### Contents of the section

1 Introduction to Automata Theory

- 2 Deterministic Finite Automata (DFA)
- 3 Examples



## Example 1

For the following DFA determine:

• The alphabet set.



## Example 1

For the following DFA determine:

- The alphabet set.
- Its transition table.



## Example 1

For the following DFA determine:

- The alphabet set.
- Its transition table.
- Its Language.



## Example 1

For the following DFA determine:

- The alphabet set.
- Its transition table.
- Its Language.




Figure: Example 1 DFA

### Example 2

Build a DFA that identifies the non-negative multiples of 3.

• What is the set of alphabet?



### Example 2

Build a DFA that identifies the non-negative multiples of 3.

- What is the set of alphabet?
- What is the transition diagram?



### Example 2

Build a DFA that identifies the non-negative multiples of 3.

- What is the set of alphabet?
- What is the transition diagram?
- What is the transition table?



Mohammad Reza Davari 18 / 20

### Example 3

Build a DFA that identifies the non-negative multiples of 5.

• What is the set of alphabet?



### Example 3

Build a DFA that identifies the non-negative multiples of 5.

- What is the set of alphabet?
- What is the transition diagram?



### Example 3

Build a DFA that identifies the non-negative multiples of 5.

- What is the set of alphabet?
- What is the transition diagram?
- What is the transition table?



Mohammad Reza Davari 19 / 20

### Example 4

Build a DFA that identifies the non-negative powers of 2.

• What is the set of alphabet?



### Example 4

Build a DFA that identifies the non-negative powers of 2.

- What is the set of alphabet?
- What is the transition diagram?



### Example 4

Build a DFA that identifies the non-negative powers of 2.

- What is the set of alphabet?
- What is the transition diagram?
- What is the transition table?



Mohammad Reza Davari 20 / 20