

# Tutorial 3

## COMP 5361: Discrete Structures and Formal Languages

Mohammad Reza Davari

Concordia University

1 Nested Quantifiers

2 Rules of Inference

# Contents of the section

## 1 Nested Quantifiers

## 2 Rules of Inference

# Nested Quantifiers

## Definition

The case where one quantifier is within the scope of another quantifier.

# Examples

Assuming the domain of discourse is  $\mathbb{R}$  translate the followings to plain English:

①  $\forall x \forall y (x + y = y + x)$

# Examples

Assuming the domain of discourse is  $\mathbb{R}$  translate the followings to plain English:

①  $\forall x \forall y (x + y = y + x)$

②  $\forall x \exists y (x + y = 0)$

# Examples

Assuming the domain of discourse is  $\mathbb{R}$  translate the followings to plain English:

- ①  $\forall x \forall y (x + y = y + x)$
- ②  $\forall x \exists y (x + y = 0)$
- ③  $\forall x \forall y \forall z (x + (y + z) = (x + y) + z)$

# Examples

Assuming the domain of discourse is  $\mathbb{R}$  translate the followings to plain English:

- ①  $\forall x \forall y (x + y = y + x)$
- ②  $\forall x \exists y (x + y = 0)$
- ③  $\forall x \forall y \forall z (x + (y + z) = (x + y) + z)$
- ④  $\forall x \forall y ((x > 0) \wedge (y < 0) \rightarrow (xy < 0))$



## Order matters...

- Be careful with the order of existential and universal quantifiers!

## Order matters...

- Be careful with the order of existential and universal quantifiers!
- Quantifiers of the same kind can interchange places.

# Example

- $\forall x \forall y \exists z (x + y = z)$

# Example

- $\forall x \forall y \exists z (x + y = z)$ 
  - True

# Example

- $\forall x \forall y \exists z (x + y = z)$ 
  - True
- $\exists z \forall x \forall y (x + y = z)$

# Example

- $\forall x \forall y \exists z (x + y = z)$ 
  - True
- $\exists z \forall x \forall y (x + y = z)$ 
  - False

- Translate the statement,  $\forall x(C(x) \vee \exists y(C(y) \wedge F(x, y)))$  where:
  - $C(x)$ :  $x$  has a computer
  - $F(x, y)$ :  $x$  and  $y$  are friends

- Translate the statement,  $\forall x(C(x) \vee \exists y(C(y) \wedge F(x, y)))$  where:
  - $C(x)$ :  $x$  has a computer
  - $F(x, y)$ :  $x$  and  $y$  are friends
- Translate the statement,  
 $\exists x \forall y \forall z ((F(x, y) \wedge F(x, z) \wedge (y = z)) \rightarrow \neg F(y, z))$  where:
  - $F(x, y)$ :  $x$  and  $y$  are friends
  - Domain: All student in the class



Translate the followings into logical expressions:

- If a person is female and is a parent, then this person is someone's mother.

Translate the followings into logical expressions:

- If a person is female and is a parent, then this person is someone's mother.
- Everyone has exactly one best friend.

# Negating Nested Quantifiers

## Recursive Negation

Statements involving nested quantifiers can be negated by successively applying the rules for negating statements involving a single quantifier.

# Example

Negate the following statement:

$$\exists w \forall a \exists f (P(w, f) \wedge Q(f, a))$$

for some  $f$ ,  $P$ , and  $Q$ .

# Contents of the section

1 Nested Quantifiers

2 Rules of Inference

- **Argument:** An argument is a sequence of statements that end with a conclusion.

---

<sup>1</sup>Also called premise

- **Argument:** An argument is a sequence of statements that end with a conclusion.
- **Valid Argument:** A valid argument is an argument that the conclusion, or final statement of the argument, follows from the **truth** of the preceding statements<sup>1</sup>.

---

<sup>1</sup>Also called premise

- **Argument:** An argument is a sequence of statements that end with a conclusion.
- **Valid Argument:** A valid argument is an argument that the conclusion, or final statement of the argument, follows from the **truth** of the preceding statements<sup>1</sup>.
- **Fallacy:** An incorrect way of reasoning which lead to invalid arguments.

---

<sup>1</sup>Also called premise



# Example

Check whether the following argument is valid or not.

$$p \rightarrow q$$

$$p$$

---

$$\therefore q$$

# Rules of Inference for Propositional Logic

## The most important rule of all time

The tautology  $(p \wedge (p \rightarrow q)) \rightarrow q$  is the basis of the rule of inference called modus ponens, or the law of detachment.

# Rules of Inference for Propositional Logic

- **Modus tollens:**  $(\neg q \wedge (p \rightarrow q)) \rightarrow \neg p$
- **Hypothetical syllogism:**  $((p \rightarrow q) \wedge (q \rightarrow r)) \rightarrow (p \rightarrow r)$
- **Disjunctive syllogism:**  $((p \vee q) \wedge \neg p) \rightarrow q$
- **Addition:**  $p \rightarrow (p \vee q)$
- **Simplification:**  $(p \wedge q) \rightarrow p$
- **Conjunction:**  $((p) \rightarrow (q)) \rightarrow (p \wedge q)$
- **Resolution:**  $((p \vee q) \wedge (\neg p \vee r)) \rightarrow (q \vee r)$