

```

1 local b4={}; for k,_ in pairs(_ENV) do b4[k]=k end
2 local as,asserts,atom,copy,cs,cs,firsts,fmt,go
3 local help,inc,isa, klass,last,map,o,obj,old,push,rand,randi
4 local rnd,roques,settings,slots,sort,the,xpects
5 local BAG, NB,NUM, RANGE, SYM
6 local the -- user settings. derived from 'help'. can be changed via command line
7 help = {}
8
9 ./duo [OPTIONS] : data miners using/used by optimizers.
10 (c) 2022, Tim Menzies, opensource.org/licenses/MIT
11 Understands "N" items by peeking at at few (maybe zero) items.
12
13 OPTIONS
14 -ample max items in a 'SAMPLE' : 512
15 -bins max number of bins : 16
16 -Debug one crash, show stackdump : true
17 -h show help : false
18 -p coefficient on distance calcs : 2
19 -round print to 'round' decimals : 2
20 -seed random number seed : 10019
21 -Some max number items to explore : 512
22 -Tiny bin size = #t*'Tiny' : .5
23 -todo start up action ('all'=every) : -]]
24
25 -- ## Library stuff
26 -- ### OO stuff
27 -- New instance
28 function as(mt,t) return setmetatable(t,mt) end
29 -- New class
30 function klass(s, t)
31   t = i._s, _tostoring=o, _index=t
32   return as({__call=function(_,...) return t.new(...) end},t) end
33
34 -- ### List stuff
35 function last(t) return t[#t] end
36 function firsts(a,b) return a[1] < b[1] end -- used for sorting
37 function sort(t,f) table.sort(t,f); return t end
38 function push(t,x) table.insert(t,x); return x end
39 function inc(d,k) d[k]=1+(d[k] or 0); return k end -- used for counting
40
41 function map(t,f, u)
42   u={};for k,v in pairs(t) do u[#u+1]=f(v) end; return u; end
43
44 -- Deep copy
45 function copy(t, u)
46   if type(t) ~= "table" then return t end
47   u={}; for k,v in pairs(t) do u[k]=copy(v) end
48   return setmetatable(u, getmetatable(t)) end
49
50 -- ### Display stuff
51 fmt = string.format
52
53 function slots(t, u)
54   u={}; for k,_ in pairs(t) do u[1+#u]=k end; return sort(u) end
55
56 function o(t, show)
57   function show(k) return fmt("%s %s", k, t[k]) end
58   t = #t>0 and map(t,tostoring) or map(slots(t),show)
59   return (t._is or "or")..{"..table.concat(t,".").."}" end
60
61 function rnd(x,d, n)
62   n=10^(d or the.round)
63   return type(x)~="number" and x or math.floor(x*n+0.5)/n end
64
65 -- ## OS Stuff
66 function atom(x)
67   if x=="true" then return true elseif x=="false" then return false end
68   return tonumber(x) or x end
69
70 function csv(file)
71   file = io.input(file)
72   return function()
73     x=io.read();
74     if x then
75       t={}; for y in x:gsub("%s+",""):gmatch("[^,]+) do t[1+#t]=atom(y) end
76       return #t>0 and t
77     else io.close(file) end end end
78
79 -- ## Settings stuff
80 function settings(help, t)
81   t = {}
82   help:gsub("\n [-](%s+)[^%n]*(%s+)", function(flag, x)
83     for n,t in ipairs(arg) do
84       if t:sub(1,1)=="-" and flag:match("^"..t:sub(2)..".*")
85       then x = x=="false" and true or x=="true" and false or arg[n+1] end end
86       t[flag] = atom(x) end
87   return t end
88
89 -- ## Random stuff
90 function randi(lo,hi) return math.floor(0.5 + rand(lo,hi)) end
91 function rand(lo,hi)
92   the.seed = (16807 * the.seed) % 2147483647
93   return (lo or 0) + ((hi or 1) - (lo or 0)) * the.seed / 2147483647 end
94
95 -- ## Math stuff
96 function xpects(t, sum,n)
97   sum,n = 0,0
98   for _,one in pairs(t) do n = n + one.n; sum = sum + one.n*one:div() end
99   return sum/n end
100
101 -- ## Error stuff
102 failures=0
103 function asserts(test,msg)
104   msg=msg or ""
105   if test then return print(" PASS: "..msg) end
106   failures = failures+1
107   print(" FAIL: "..msg)
108   if the.Debug then assert(test,msg) end end
109
110 function roques(b4)
111   for k,v in pairs(_ENV) do if not b4[k] then print("?",k,type(v)) end end end
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247

```

```

248     if after then
249         maybe = now:merge(after)
250         if maybe then now=maybe; j=j+1 end end
251     push(tmp,now) end
252     return #tmp==#b4 and b4 or i:superRanges(tmp) end
253
254 -- Divide 'i,j' numbers into 'the.bins' ranges.
255 function NUM.ranges(i,j, yklass)
256     local out,lo,hi,gap = {}
257     lo = math.min(i:lo(), j:lo())
258     hi = math.max(i:hi(), j:hi())
259     gap = (hi-lo)/the.bins
260     for b=1,the.bins do
261         here = lo + (b-1)*gap
262         out[b] = RANGE(i, here, here+gap, (yklass or SYM)()) end
263     for _,x in pairs(i:_has.all) do out[(x-lo)/gap]:add(x,"best") end
264     for _,x in pairs(j:_has.all) do out[(x-lo)/gap]:add(x,"rest") end
265     out[1].lo = -math.huge
266     out[#out].hi = math.huge
267     return out end
268
269 NB=class"NB"
270 function NB.new() return as(NB, {k=1,m=2,names=BAG(),n, hs=0,h={}, f={}}) end
271
272 function NB.read(i, file)
273     for row in csv(file) do if row then i:add(n,row) end end end
274
275 function NB.add(i, n,row, k,klass)
276     if n==0 then i.names=row else
277         k=#row
278         if n > 5 then print(row[k], i:classify(row)) end
279         klass=row[k]
280         if not i.h[klass] then i.hs=i.hs+1; i.h[klass]=0 end
281         inc(i.h,row[k])
282         i.n=i.n+1
283         for col,x in pairs(row) do
284             if col~=k and x~="?" then
285                 inc(i.f, {col,x,klass}) end end end end
286
287 function NB.classify(i,row, best)
288     best=-1
289     for klass,nh in pairs(i.h) do
290         local prior = (nh+i.k)/(i.n + i.k*i.hs)
291         local tmp = prior
292         for col,x in pairs(row) do
293             if col ~= #row and x~="?" then
294                 tmp = tmp * ((i.f[{col,x,klass}] or 0) +i.m*prior)/(nh+i.m) end end
295             if tmp > best then best,out=tmp,klass end end
296         return klass end
297
298 --i:read("../data/weathernom.csv")
299 --print(o(i.h))
300
301 go={}
302 function go.copy( a,b)
303     a={1,2,3,{40,50}}; b=copy(a); b[4][1]=400
304     asserts(a[4][1]~b[4][1],"deep copy") end
305
306 function go.two() print(2) end
307
308 -- start up stuff
309 the = settings(help)
310 old = copy(the)
311 if the.h then
312     print(help)
313 else
314     failures = 0
315     for _,it in pairs(the.todo=="all" and slots(go) or {the.todo}) do
316         if go[it] then print(it); go[it](); the = old end end -- do, then reset
317     rogues(b4) end
318
319 os.exit(failures)

```