S. NO.	ANTENNA	PART NO.	DESCRIPTION	IMAGES
1	GSM INTERNAL ANTENNA 3DBI	ST0670103918	Frequency - $800-960/1880-1930$ Mhz Gain - 3 dbi VSWR - ≤ 2.0 Radiation - Omni Impedance - 50Ω Max Power - $50W$ Connector - UFL Female Cable - 1.13 mm Compliance - ROHS	
2	GSM STICKER ANTENNA 3DBI	ST0670203918	Frequency - $824^894/1710^2170$ Mhz Polarization - Linear VSWR - ≤ 2.0 Gain - 3dbi Max Power - $50W$ Impedance - 50Ω Cable - Rg-174 Connector - SMA Male	A 2
3	MAGNETIC BASE 3 MTR WITH SMA M	ST0670809825	Frequency - 800^2500 Mhz VSWR - ≤ 2.0 Impedance - 50Ω Max Power - $50W$ Cable RG-174 Connector - SMA Male Compliance - ROHS	
4	MAGNETIC BASE ANTENNA 3DBI 800- 2500Mhz 2 MTR	ST0670403825	Frequency - 850~900/1800~2100mhz Gain - 3dbi VSWR - ≤1.5 Radiation - Omni Directional Impedance - 50Ω Max Power - 50W Cable - RG-174 Connector - SMA Male Compliance - ROHS	
5	MAGNETIC BASE ANTENNA 3DBI 800- 2500Mhz 3 MTR	ST0670303825	Frequency - $850^{\circ}900/1800^{\circ}2100$ mhz Gain - 3dbi VSWR - \leq 1.5 Radiation - Omni Directional Impedance - 50Ω Max Power - $50W$ Cable - RG-174 Connector - SMA Male Compliance - ROHS	
6	MAGNETIC BASE ANTENNA 3DBI 800- 2500Mhz 5 MTR	ST0670603825	Frequency - 850~900/1800~2100mhz Gain - 3dbi VSWR - ≤1.5 Radiation - Omni Directional Impedance - 50Ω Max Power - 50W Cable - RG-174 Connector - SMA Male Compliance - ROHS	

			Frequency - 850~900/1800~2100mhz
7	MAGNETIC BASE ANTENNA 6DBI 800- 2500Mhz 3 MTR	ST0670703825	Gain - 6dbi VSWR - ≤1.5 Radiation - Omni Directional Impedance - 50Ω Max Power - 50W Cable - RG-174 Connector - SMA Male Compliance - ROHS
			Frequency - 850~900/1800~2100mhz
8	MAGNETIC BASE ANTENNA 8DBI 800- 2500Mhz	ST0670508825	Gain - 8-9dbi VSWR - ≤1.5 Radiation - Omni Directional Impedance - 50Ω Max Power - 50W Cable - RG-58 Connector - SMA Male Compliance - ROHS
			Frequency - CDMA
9	WHIP ANTENNA 12DBI CDMA	ST0631012850	Max Power - $50W$ Impedance - 50Ω
			Connector - TNC Male Compliance - ROHS
10	WHIP ANTENNA MOV 9DBI 800- 2500Mhz	ST0631109825	Frequency - 800-2500Mhz Gain - 9dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male Compliance - ROHS
11	WHIP ANTENNA RA FIX 2DBI 800- 2500Mhz	ST0630102825	Frequency - 800-2500Mhz Gain - 2dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male Compliance - ROHS
12	WHIP ANTENNA RA FIX 3DBI 800-2500 Mhz	ST0630203825	Frequency - 800-2500Mhz Gain - 3dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male Compliance - ROHS
13	WHIP ANTENNA RA MOV 3DBI 433Mhz	ST0630503433	Frequency - 433Mhz Gain - 3dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male

I			Compliance - ROHS	
14	WHIP ANTENNA RA MOV 3DBI 868Mhz	ST0630303868	Frequency - 868Mhz Gain - 3dbi VSWR - ≤1.5 Polarization - Vertical	<u> </u>
15	WHIP ANTENNA RA MOV 5DBI 800- 2500Mhz	ST0630605825	Frequency - 800-2500Mhz Gain - 5dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male Compliance - ROHS	
16	WHIP ANTENNA RA MOV 5DBI 868Mhz	ST0630705868	Frequency - 868Mhz Gain - 5dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male Compliance - ROHS	_
17	WHIP ANTENNA RP 9DBI 2.4GHz	ST0631109240	Frequency - 2400Mhz Gain - 9dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male RP Compliance - ROHS	
18	WHIP ANTENNA RP MOV 3DBI 2.4/5.8 Ghz	ST0630403245	Frequency - 2400~5800Mhz Gain - 3dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - SMA Male RP Compliance - ROHS	
19	WHIP ANTENNA RP MOV 3DBI 2.4GHz	ST0630803240	Max Power - 50W Impedance - 50Ω Connector - SMA Male RP Compliance - ROHS	
20	WHIP ANTENNA RP MOV 3DBI WITH UFL	ST0631203240	Frequency - 2400Mhz Gain - 3dbi VSWR - ≤1.5 Polarization - Vertical Max Power - 50W Impedance - 50Ω Connector - UFL Female	

			Compliance - ROHS	
			Frequency - 2400Mhz	
			Gain - 5dbi	
			VSWR - ≤1.5	
21	WHIP ANTENNA RP MOV 5DBI 2.4GHz	ST0630905240	Polarization - Vertical	
			Max Power - 50W	
			Impedance - 50Ω	
			Connector - SMA Male RP	
			Compliance - ROHS	