

0.5~2.7GHz, 50W, Solid State Power Amplifier

FEATURES

- Instantaneous ultra broadband
- Built-in protection circuits
- High reliability and ruggedness
- Compact size and light weight

ELECTRICAL SPECIFICATIONS

Parameter	Min	Typ	Max	Unit
Frequency Range	0.5		2.7	GHz
Psat	50			W
Gain	48	50		dB
Gain Flatness			±2	dB
Harmonics		-15		dBc
Spurious		-60		dBc
VSWR			2:1	-
Input Power			10	dBm
DC Voltage	26	28	30	V

ENVIRONMENTAL SPECIFICATIONS

Parameter	Min	Typ	Max	Unit
Operating Temp.	-20		+60	°C
Storage Temp.	-40		+85	°C

MECHANICAL SPECIFICATIONS

Parameter	Value	Unit
Dimensions	180 × 100 × 27	mm
Weight	2.0	Kg
RF I/O Connectors	SMA female	-
Interface Connector	9-Pin Male D-Sub	-
Cooling	External Heatsink	-

Control CONNECTOR		
Pin #	Description	Specification
A1	Vcc	+28V
A2	GND	+28V-GND
1~3	N/C	N/C
4	TEMP MONITOR	Analog voltage relative to Module's Temperature @ 10 mV/ °C
5	CURRENT MONITOR	Analog voltage relative to IDD @ 100mV per Ampere
6	N/C	N/C
7	Enable	Amplifier Enable: TTL Logic High (3.3V) (Internally Pulled-Low)
8	GND	GND
9~15	N/C	N/C

OUTLINE DRAWING

