



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: TNC (F)-TNC (F) ADAPTOR


Page No.

1 of 1

STK-571688321228

TNC (F)-TNC (F) ADAPTOR

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-11 GHz
VSWR	1.44 + 0.000 x F(GHz) Maxi
Insertion loss	0.06 $\sqrt{F}$ (GHz) dB Maxi
RF leakage	- (57 - F(GHz)) dB Maxi
Voltage rating	500 Veff Maxi
Dielectric withstanding voltage	1500 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65°C to +165°C
-----------------------	-----------------

MECHANICAL INFORMATION

Mating end	18 N mini
Opposite end	18 N mini
Torque	2.8 N.cm mini
Mating life	500 Cycles mini
Weight	10.371 g

MATERIAL INFORMATION

COMPONENTS		MATERIAL		PLATING			
BODY		BRASS		NICKEL 2			
CENTER CONTACT		BERYLLIUM COPPER		GOLD 0.5 OVER NICKEL 2			
INSULATOR		PTFE					
OTHERS PARTS				NICKEL 2			
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

ST
Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in