



ST- Series Semi-Flexible Cable

ST-26

Structure Drawing



Structure Characteristics

Structure	Item	Standard Value
Inner Conductor	Material	Silver Plated Copper
	Construction (mm)	1/0.52
	Nom.Dia(mm)	0.52
Insulation	Material	PTFE
	Nom.Dia(mm)	1.65
Out Conductor	Material	Tinned Copper Wire Braid+Tin Soaked
	Nom.Dia(mm)	2.15

Electrical Characteristics

Item	Standard Value	Attenuation (@25°C&Sea Level) and Power handing@ (@40°C&Sea Level)		
Impedance (Ω)	50	(MHz) Frequency	(dB/100m) Attenuation	(W) Power handing
Capacitance (pF/m)	95	500	46.55	229
		1000	66.98	159
Velocity of Propagation	70%	2000	97.05	110
		4000	141.87	75
Max Operating Frequency (GHz)	61	6000	178.11	60
		8000	209.90	51
Screening Effectiveness (dB)	> 100	10000	238.85	45
		16000	315.37	34
Dielectric Withstanding Voltage(V@DC)	1000	18000	338.57	31
		26500	429.23	25
Phase Change VS Bending (°/GHz)	N/A	40000	556.77	19
		K1	1.993226	
Phase Change VS Temperature@ (-45~+85) °C	N/A	K2	0.003953	
		: IL=K1*√FMHz+K2*FMHz		

Mechanical & Environmental Characteristics

Replaceable Type

Min Bending Radius (Static)	11.0mm		
Min Bending Radius (Dynamic)	22.0mm		
Weight	0.019kg/m		
Operating Temperature (°C)	-55 ~ +125		