

Product Specification Of Ultra Low Loss Phase Stable Cable

ST-260

Structure Drawing



Structure Characteristics

Structure	Item	Standard Value
Inner Conductor	Material	Silver Plated Copper
	Construction (mm)	1/2.43
	Nom.Dia (mm)	2.43
Insulation	Material	LD-PTFE
	Nom.Dia (mm)	6.45
Inner shield	Material	Flat Silver Plated Copper Wrapped Strip
	Nom.Dia (mm)	6.75
Outer shield	Material	Round Silver Plated Copper Braided Wire
	Nom.Dia (mm)	7.35
Jacket	Material	Gray FEP
	Nom.Dia (mm)	8.10

Electrical Characteristics

Item	Standard Value	Attenuation and Power handing@25℃&Sea Level		
Impedance（Ω）	50	Frequency (MHz)	Attenuation (dB/100m)	Power handing (W)
Capacitance（pF/m）	80	500	9.29	3466
		1000	13.23	2433
Velocity of Propagation	84%	2000	18.91	1703
		3000	23.34	1379
Max Operating Frequency（GHz）	18	4000	27.12	1187
		5000	30.50	1056
Screening Effectiveness（dB）	>90	6000	33.58	959
		8000	39.13	823
Dielectric Withstanding Voltage（V@DC）	3000	10000	44.10	730
		12400	49.52	650
Phase Change VS Bending（°/GHz）	±0.3	18000	60.68	531
		K1	0.40800	
Phase Change VS Temperature@（-45~+85）℃	≤750 PPM	K2	0.00033	
		IL=K1*√FMHz+K2*FMHz		

Mechanical & Environmental Characteristics

Replaceable Type

Min Bending Radius (Static)	40.5 mm	GORE	CXN3508
Min Bending Radius (Dynamic)	81.0 mm		
Weight	0.146 kg/m		
Operating Temperature	-55~+165°C		