



	Model	Photo	Description	Wholesale Price
Repeater Controller	SR-112		• 3 of message box for record • Auto Message send out at 15/30/45mins • Up to 180 seconds total recording time • DTMF remote control for all functions	10,014
	SR-328		• Multi- LED display 2 radio status • Real time duplex repeater with link radio • Allows user to change the DTMF remote control password by radio • build-in Li-ion battery 72 hours long	10,068
	SR-628		• Multi- LED display 2 radio status • Real time duplex repeater with link radio • Allows user to change the DTMF remote control password by radio • build-in Li-ion battery 72 hours long	9,663
	SR-629		• Multi- LED display 2 radio status • Real time duplex repeater with link radio • Allows user to change the DTMF remote control password by radio • Two mode select	6,819
Frequency Counter	SF-401plus		• Frequency range: 27Mhz-3000Mhz • CTCSS/DCS Decoder • Frequency counter for DMR radio • Frequency digital 0.000 or 0.0000 • Frequency Response time: 0.2-0.5sec	8,715
	SF-103		• Frequency range two select : 2MHz-200MHz / 27MHz -2800MHz • CTCSS/DCS Decoder • Digital mode for DMR radio • Frequency Response time: 0.2-0.5sec	10,800
			• Measurement Frequency: 125-525MHz	
	SW102 (N/S)		• Power Input:120W	10,149
			• Display: LCD	
			• Accuracy : +- 5%	
			• Port SWR: < 1.1	



Power Meter	SW102HF		• Measurement Frequency: 1.5-70MHz • Power Input:120W • Display: LCD • Accuracy : +- 5% • Port SWR: < 1.1	10,800
	SW-33MarkII		• Measurement Frequency: 125-525MHz • Power Input:100W • Accuracy : +- 5% • Port SWR: < 1.1 • Input connect: SMA female	6,198
	SW-33Plus		• Measurement Frequency: 125-525MHz • Power Input:100W • Display: LCD • Accuracy : +- 5% • Port SWR: < 1.1	6,957
	SF-20		• Measurement Frequency: 100-525MHz • Power Input: 20W • Frequency Counter:20-999MHz • Accuracy : +- 5% • Port SWR: < 1.1	6,738
	SW-114		• Measurement Frequency: 27-30MHz • Power Input:100W • 2 separate windows • Input connect: SO239 • Size: 120mm x 60mm x 65mm • Weight: 410 grams	5,000
	SW-111		• Measurement Frequency: 27-30MHz • Power Input:100W • Input connect: SO239 • Size: 84mm x 59mm x 52mm • Weight: 260 grams	3,735
Field Strength Meter	SS10		• Frequency Range: 100KHz -3GHz • Size without Socket : 75 x 100 x 64mm • Antenna (in) Interface: SMA Female • The pointer amplitude can be adjusted	4,845
	SS11		• Frequency Range: 100KHz -3GHz • Size without Socket : 75 x 100 x 64mm • Antenna (in) Interface: SMA Female • The pointer amplitude can be adjusted	6,063



Antenna Analyzer	SA-160		• Measurement Frequency: 132-173 / 200-260 / 400-519MHz • Display: 2.2 inch TFT (320 x240) • RF Output: 1-1.15V (± 5-10db) • Span width: 0.54MHz /1.35MHz /2.7MHz /5.4MHz /10.8MHz /27MHz / 54MHz / 108MHz / 216MHz / 432MHz	27,069
	SA-250		• Measurement Frequency: 132-173 / 200-260 / 400-519MHz • Display: 2.2 inch TFT (320 x240) • RF Output: 1-1.15V (± 5-10db) • Span width: 0.54MHz /1.35MHz /2.7MHz /5.4MHz /10.8MHz /27MHz / 54MHz / 108MHz / 216MHz / 432MHz	32,484