



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CONNECTOR RF50 SMA SQFL RP 4HOLE 12.7MM




Page No.

1 of 1

STK-571127861533

CONNECTOR RF50 SMA SQFL RP 4HOLE 12.7MM

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency Range	DC to 26 GHz
Insertion loss	3-27 straight 0.03 f(Ghz) right angle 0.05 f(Ghz)
RF leakage	3-26 -60db min between 2 to 3Gh
Insulation resistance	3-11 5000 megohma min

V.S.W.R upto 18 Ghz

CABLE	STRAIGHT	RIGHT ANGLE
2.6/50	1,15 + 0.02 F (Ghz)	1,15 + 0.03 F(Ghz)
5/50	1,15 + 0.01 F (Ghz)	1,157+0.02 F(Ghz)
0.085	1,07 + 0.01 F (Ghz)	1,10+0.01 F(Ghz)
0.141	1,05 + 0.01 F (Ghz)	1,10+0.01 F(Ghz)

MECHANICAL INFORMATION

Life	3-15	500 mating
Force to engage and diswngage	3-5-1	torque 2 inch-pounds 23 N.cm
Mating torque		7 to 10 inc-pound 80-115 N.cm
Coupling nut rentention force	3-25	15 inc-pound 170 N .cm
Cable retention force	3-24	2.6/50 cable 25lbs
Contact captivation		axial force 6lbf-27 N-torque

ENVIRONMENTAL

operating temperature range	standard models	-65°C + 165°C
	hermetic	-65°C+165°C
Temperature cycling	3-20	MIL-STD-202 METHOD 102
Hight temperature test	3-13	MIL-STD-202 METHOD 107
Corrosion (salt spray)	3-18	MIL-STD-202 METHOD 101
Stock	3-19	MIL-STD-202 METHOD 213

Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	27.10.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd, WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-
				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in