



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CON RF 50 MMCX PL RT



Page No.

1 of 1

STK-571188191362

CON RF 50 MMCX PL RT

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-6 GHz
VSWR	$1.15 + 0,0000 \times F(\text{GHz})$ Maxi
Insertion loss	$\sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	- (- F(GHz)) dB Maxi
Voltage rating	335 Veff Maxi
Dielectric with standing voltage	750 Veff mini
Insulation resistance	1000 M Ω mini

MECHANICAL INFORMATION

Axial force – Mating end	10 N mini
Axial force – Opposite end	10 N mini
Torque	NA N.cm
Mating	NA.cm
Panel nut	NA.cm
Mating life	500 Cycles mini
Weight	0.800 g

ENVIRONMENTAL

Operating temperature	-55/+155 ° C							
Hermetic seal	NA							
Panel leakage	NA							
DIMENSIONS								
COMPONENTS	MATERIALS	PLATINGS (mm)	 Synergy Telecom Pvt Ltd Defence & Aerospace Division					
BODY	BRASS	GOLD 0.2 OVER NICKEL 2						
CENTER CONTACT	BRASS	GOLD 1.3 OVER NICKEL 2						
OUTER CONTACT	-	-						
INSULATOR	PTFE	-						
GASKET	-	-						
OTHERS PARTS	-	-						
Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	01.11.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd, WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
				-	-	-	-	Email: sales.blr@rfconnector.in
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division . This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.								
www.rfconnector.in								