


Technical Data	STK SERIES ANTENNA	
-----------------------	---------------------------	---

Nomenclature: omni antenna 800-2700 6dBi	Page No.
	1 of 1

STK-587882821301	omni antenna 800-2700 6dBi
-------------------------	----------------------------

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

FREQUENCY RANGE,dBi	860-960	1710-2500	2500-2700
GAIN	5 dBi		
VSWR	<1.8	<2.0	<2.5
POLARIZATION	VERTICAL		
HORIZONTAL BEAMWIDTH	360°		
VERTICAL BEAMWIDTH	16°		
INPUT IMPEDANCE	50Ω		
MAX. POWER	100 W		
LIGHTNING PROTECTION	DC GROUND		

MECHANICAL INFORMATION

CONNECTOR	N- FEMALE
DIMENSIONS	Ø63x710 mm
WEIGHT	2.0 kg
REFLECTOR MATERIAL	COPPER
RADOME MATERIAL	UV-PVC
OPERATING TEMPERATURE	-40°C TO +65°C
MOUNTING POLE	Ø38-Ø52 mm
RATED WIND VELOCITY	210km/h

Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	27.10.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and all it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in