

 Technical Data	STK SERIES CONNECTOR	 www.rfconnector.in						
Nomenclature:CONNECTOR RF50 SMP M THDIN RPFULLDETENT			Page No. 1 of 1					
STK-571127361595	CONNECTOR RF50 SMP M THDIN RPFULLDETENT							
OUTLINE DRAWING								
								
TECHNICAL DATA								
ELECTRICAL DATA								
Impedance	50 Ω							
Frequency Range	12 GHz							
Insulation Resistance	5 Gohms							
ENVIRONMENTAL INFORMATION								
Operation temperature	-65°C ~ 165°C							
MECHANICAL INFORMATION								
Weight	NA							
Voltage Rating	335V							
MATERIAL INFORMATION								
COMPONENTS		MATERIAL		PLATING				
BODY		Stainless Steel		Gold				
Center Contact Plating		-		-				
Dielectric Material		-		-				
Originated	Date	Approved	Date	Rev	Amend	Name	Date	
Sang	01.12.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	Email: sales.blr@rfconnector.in
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand. www.rfconnector.in								