



SYNERGY TELECOM PVT LTD

SYNERGY TELECOM PVT LTD		 Technical Data Sheet	T.D.S. No.	GPI/TDS/152
WZ-47 BUDELLA, VIKAS PURI			Issue No & Date	25.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	GPI/CR/.../25-26 dtd
https://www.rfconnector.in			Cust. Enq./PO No.	
Item Name	1C X 10 Sqmm Data Sheet Automotive Cable			
Description	1C X 10 Sqmm ABC , PVC Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.40 ± 0.02
		No of Strand	Nos	80 ± 4
2	Insulation	Material	-	PVC " HR "
		Ins. Thickness	mm(Nom)	1.0 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	6.5 ± 0.5
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	1.82
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN