



Item Name	2C X 16 Sqmm XCMK Screened Cable Data Sheet
Description	2 Core X 16 Sqmm XCMK EMC-Screened Cable, Flexible Cu, XLPE Insulated, Cu Wire+Tape Screen, PVC FRLS Sheathed
Spec. Ref.	IS:8130 (Class-5), IS:7098 (Pt-1), XCMK 0.6/1 kV Screened
Customer Name	

Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor (Class-5)	Material	-	Annealed Bare Copper, Flexible
		No. of Strand / Size	Nos/mm	126 / 0.382 ± 0.02
		Shape	-	D-Shaped
		Dia of Conductor	mm	5.0 ± 0.5
2	Conductor Constant	Resistance (max) at 20°C	Ω/Km	1.21
3	Insulation	Material	-	XLPE
		Thickness	mm (Nom)	0.7
		Core Colour	-	Blue, Brown
4	Laying	No. of Core	Nos	2 Core
		Dia Over Laid-up Cores	mm	12 ± 1
5	Inner Tape (Bedding)	Material	-	PVC Tape
		Thickness / Width	mm	0.3 x 40
6	EMC Shielding	Wire Material / Size	-	Bare Copper, 16 x 0.39 mm
		Copper Tape	mm	13 x 0.04
		Coverage	%	>85
7	Taping	Material	-	Polyester Tape
		Size / Thickness	mm	40 x 0.025
8	Outer Sheath	Material	-	PVC "ST1" FRLS
		Thickness	mm (Nom)	1.24 ± 0.2
		Overall Diameter	mm	16 ± 2
		Colour	-	Black
9	Electrical / General	HV Test (5 min)	kV AC	3.5
		Insulation Resistance (min)	MΩ-km	100
		Voltage Grade	V	600/1000
		Temperature Rating	°C	90 (XLPE)
		Packing	-	As Per PO