

## 18~26.5GHz, 20W, Solid State Power Amplifier

### FEATURES

- Instantaneous ultra broadband
- Built-in protection circuits
- High reliability and ruggedness
- Compact size and light weight

### ELECTRICAL SPECIFICATIONS

| Parameter       | Min | Typ | Max  | Unit |
|-----------------|-----|-----|------|------|
| Frequency Range | 18  |     | 26.5 | GHz  |
| Psat            | 20  |     |      | W    |
| Gain            | 40  | 45  |      | dB   |
| Gain Flatness   |     | ±5  |      | dB   |
| Harmonics       |     | -15 |      | dBc  |
| Spurious        |     | -60 |      | dBc  |
| VSWR            |     |     | 2:1  | -    |
| Input Power     |     | 0   |      | dBm  |
| DC Voltage      |     | 28  | 30   | V    |

### ENVIRONMENTAL SPECIFICATIONS

| Parameter       | Min | Typ | Max | Unit |
|-----------------|-----|-----|-----|------|
| Operating Temp. | -20 |     | +70 | °C   |
| Storage Temp.   | -40 |     | +85 | °C   |

### MECHANICAL SPECIFICATIONS

| Parameter           | Value              | Unit |
|---------------------|--------------------|------|
| Dimensions          | 150×125×30         | mm   |
| Weight              | 2.0                | Kg   |
| RF I/O Connectors   | 2.92mm-Female/WR42 | -    |
| Interface Connector | 15-Pin Male D-Sub  | -    |
| Cooling             | External Heatsink  | -    |