



www.rfconnector.in




1 of 1

Nomenclature: CONN RF50 SMA EDG ST PCB

STK-571131971326

CONN RF50 SMA EDG ST PCB

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-26.5 GHz
VSWR	1.05+ .02F(GHz) maximum 18-26.5 GHz
Insulation resistance	1000 Megohms minimum

ENVIRONMENTAL INFORMATION

Operation temperature	- 65°C to + 165°C
-----------------------	-------------------

MECHANICAL INFORMATION

Durability	500 Cycles minimum
------------	--------------------

MATERIAL INFORMATION

COMPONENTS		MATERIAL		PLATING				
BODY		BRASS		GOLD				
CONTACT		BERYLLIUM COPPER		GOLD				
DIELECTRIC		PTFE		-				
Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	01.12.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
								Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.