



STK SERIES CONNECTOR





Nomenclature: RIGHT ANGLE

Page No.
1 of 1

STK-5711- UD-RF400-827N-SB-E

RIGHT ANGLE

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Voltage rating	500V
Frequency range	DC to 3 Ghz
Dielectric voltage	2500V
Center contact	≤ 0.8
Outer contact	≤ 0.2
Insulation resistance	$\geq 1000M$
RF leakage	NA
VSWR	≤ 1.15 DC-3Ghz

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)
BODY	BRASS	COPPER
CONTACT PIN	SPRING COPPER	
INSULATOR	TEFLON	
FERRULE	COPPER	COPPER
GASKET	SILICON	RED OR BLACK

ENVIRONMENTAL INFORMATION

Temperature range	-55°C~+155°C
-------------------	--------------

MECHANICAL INFORMATION

Force to engage and disengage	25N MAX
Center contact retention force	NA
Coupling nut retention force	1000 N MAX
Cable retention force	400 N MAX
Durability	≥ 500 cycles

Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.11.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-


Synergy Telecom Pvt Ltd
Defence & Aerospace Division
Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.
www.rfconnector.in