



STK SERIES CONNECTOR



Nomenclature: STRAIGHT PLUG


Page No.

1 of 1

STK-5711- F26-RF400-827N-Y

STRAIGHT PLUG

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency range	DC to 6 Ghz
Outer conductor	≤ 0.2
Inner conductor	≤ 0.8
Proof Voltage	2500
Insulation resistance	≥ 10000
Insert loss	$\leq 0.05(0-3G)$
VSWR	≤ 1.30

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)
Inner conductor	spring cipper	Ag 200
Outer conductor	Brass	Copper (Albaloy)
Ferrule	copper	Copper (Albaloy)
Nut	Brass	Copper (Albaloy)
Insulator	PTFE	
Ring	Silicone rubber	

ENVIRONMENTAL INFORMATION

Temperature range	-40°C~+85°C
Waterproofing standard	IP67

MECHANICAL INFORMATION

Pin torque	25N.m
(Nut) whorl pull	1000N
Tensile force	400N
Torsion	2N.m

Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.11.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-



Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in