



www.rfconnector.in



1 of 2

RIGHT ANGLE

Technical drawing of a mechanical assembly showing a cross-section of a component. The drawing includes the following dimensions and features:

- Overall height: 1.41 REF.
- Top section width: .625 ACROSS 2 FLATS REF.
- Bottom section width: 2.02 REF.
- Bottom section diameter: $\phi .78$ REF.
- Internal diameter: $\phi 4.15$
- Outer diameter: $\phi 4.75$
- Stamp: "TC-400-NMC RA (A)"

Impedance	50 Ω
Voltage rating	1000 vrms
Insulation resistance	0.15 x $\sqrt{f}$ ghz
VSWR	<1.25 (DC-2Ghz)

COMPONENTS	MATERIALS	PLATINGS (mm)
Central contact	Beryllium	Gold
Outer contact	Brass	Alballoy
Coupling nut	Brass	Alballoy
Body	Brass	Alballoy
Dielectric	PTFE	
Gasket	Silicone rubber	-

Temperature range	-55°C~+155°C
Weather standard	IEC 60068 55/155/56

Force to engage and disengage	-
Center contact	-



Sang	01.11.25	Krishnamurthy	-	0	-	-	-	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
This document is the property of Synergy Telecom P Ltd - New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division . This document and al it copies shall be returned to Synergy Telecom P Ltd on demand. www.rfconnector.in								Email: sales.blr@rfconnector.in