



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: MALE STRAIGHT RECEPTACLE SMT TYPE - CATCHER'S MITT



Page No.

1 of 1

STK-571129881267

MALE STRAIGHT RECEPTACLE SMT TYPE - CATCHER'S MITT

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-18* GHz
VSWR	1.15* + 0.0000 x F(GHz) Maxi
Insertion loss	0.10 $\sqrt{F}$ (GHz) dB Maxi
RF leakage	- (N/A - F(GHz)) dB Max
Voltage rating	335 Veff Maxi
Dielectric withstanding voltage	500 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Mating End	6.8 N mini
Opposite end	6.8 N mini
Torque	NA N.cm mini
Mating life	1000 Cycles mini
Weight	0,4600 g

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)
Body	STAINLESS STEEL + BRASS	PASSIVATED + GOLD 0.5 OVER
Center contact	BERYLLIUM COPPER	GOLD OVER NICKEL
Insulator	PTFE	-
Gasket	-	-
Others parts		
Originated	Date	Approved
Sang	01.12.25	Krishnamurthy
Synergy Telecom P Ltd,		
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India		

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in