



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature:FEMALE - FEMALE ADAPTATOR


Page No.

1 of 1

STK-571156751237

FEMALE - FEMALE ADAPTATOR

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-40* GHz
VSWR	$1.5^* + 0.0000 \times F(\text{GHz})$ Maxi
Insertion loss	0.12 $\sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	- (N/A - F(GHz)) dB Max
Voltage rating	335 Veff Maxi
Dielectric withstanding voltage	500 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Mating End	6.7 N mini
Opposite end	6.7 N mini
Panel nut	NA N.cm
Mating life	100 Cycles mini
Weight	0.3700 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
Body		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL 2		
Center contact		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL 2		
Insulator		PTFE			-		
Gasket		-			-		
Others parts							
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in