



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CONN.RF 50 N PL ST M RG142


Page No.

1 of 1

STK-571182391244

CON RF50 SMB RP ST F PCB

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-4 GHz
VSWR	1.05 + 0,0080 x F(GHz) Maxi
Insertion loss	0.03* $\sqrt{F}$ (GHz) dB Maxi
RF leakage	- (57 - F(GHz)) dB Maxi
Voltage rating	500 Veff Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	1000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Mating end	10 N Mini
Opposite end	10 N Mini
Torque	NA
Mating Life	500 Cycles mini
Weight	0,0000 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
BODY		BRASS			GOLD 0.2 OVER NICKEL 2		
CENTER CONTACT		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL2		
INSULATOR		PTFE			-		
OTHERS PARTS		-			-		
GASKET		-			-		
OUTER CONTACT		BERYLLIUM COPPER			GOLD 0.5 OVER NICKEL 2		
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-



Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in