



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature:FEMALE - FEMALE ADAPTATOR SPRING LOADED

Page No.

1 of 1


STK-571653361264

FEMALE - FEMALE ADAPTATOR SPRING LOADED

OUTLINE DRAWING



Unslotted side :
To be mated to
SMOOTH BORE
only



Slotted side :
To be mated to
FULL or
LIMITED DETENT

TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-18* GHz
VSWR	1.35* + 0.0000 x F(GHz) Maxi
Insertion loss	0.12 $\sqrt{F}$ (GHz) dB Maxi
RF leakage	- (N/A - F(GHz)) dB Max
Voltage rating	350 Veff Maxi
Dielectric withstanding voltage	500 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+85 ° C
-----------------------	-------------

MECHANICAL INFORMATION

Mating End	6.7 N mini
Opposite end	6.7 N mini
Panel nut	NA N.cm
Mating life	1000 Cycles mini
Weight	1,3000 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
Body		BRONZE			NPGR		
Center contact		BERYLLIUM COPPER			GOLD 1.27 OVER NICKEL 1.27		
Insulator		PEI + PTFE					
Outer contact		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL 2		
SPRING					PASSIVATED		
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in