



SYNERGY TELECOM PVT LTD

SYNERGY TELECOM PVT LTD		 Technical Data Sheet	T.D.S. No.	GPI/TDS/153
WZ-47, BODELLA, VIKAS PURI			Issue No & Date	25.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	GPI/CR/.../25-26 dtd
https://www.rfconnector.in/			Cust. Enq./PO No.	
Item Name	1C X 0.35 Sqmm Data Sheet Automotive Cable			
Description	1C X 0.35 Sqmm ABC , PVC HR FR Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.26 ± 0.02
		No of Strand	Nos	7
2	Insulation	Material	-	PVC "HR FR"
		Ins. Thickness	mm(Nom)	0.25 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	1.4 ± 0.2
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	54.40
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength (Insulation)	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN