



Guaranteed Technical Particular

S.NO	DESCRIPTION	UNIT	RG-6 Coaxial cable Cu finished
1	Name of the Manufacturer		Relemac Cables
2	Place of Manufacture		Kundli sonipat Haryana
3	Brand		Microtek
4	Conductor		
a)	Material		Annealed Bare Copper wire
b)	Diameter of Copper wire	mm	0.98
c)	Shape of conductor		Solid circular
d)	Min. no. of strands		1
5	Insulation		
a)	Material		Gas Injected Physical Foamed Polyethylene
b)	O.D.	mm	4.60
6	Shielding		with Al. Bonded tape
7	Braiding		Braiding with Aluminium Alloy wires with coverages 85% min.
8	Outer Jacket		Black PVC
a)	Over all Dia	mm	7.0
9	Electrical characteristics		
a)	Conductor Resistance at 20°C	Ohm/km.	19.5
b)	Nominal capacitance	pF	53
c)	Nominal Impedance	Ohm	75
d)	Attenuation at 55 MHz	dB/100	5.2
e)	Marking		Progressive Sequential Length marking on every meter

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN



Guaranteed Technical Particular

S.NO	DESCRIPTION	UNIT	RG-6 Coaxial cable CU finished
1	Name of the Manufacturer		Relemac Technologies
2	Place of Manufacture		Kundli sonipat Haryana
3	Brand		Relemac Cables
4	Conductor		
a)	Material		Bare Copper
b)	Diameter of Copper wire	mm	1.0±0.02
c)	Shape of conductor		Solid circular
d)	Min. no. of strands		1
5	Insulation		
a)	Material		Gas Injected Physical Foamed Polyethylene
b)	O.D.	mm	4.6±0.2
6	Shielding		with Al. Bonded tape
7	Braiding		Braiding with Aluminium Alloy wires with coverages 65% min.
8	Outer Jacket		Black PVC
a)	Over all Dia	mm	6.5±0.2
9	Electrical characteristics		
a)	Conductor Resistance at 20°C	Ohm/km.	20.5
b)	Nominal capacitance	pF	53
c)	Nominal Impedance	Ohm	75
d)	Attenuation at 55 MHz	dB/100	5.2
e)	Marking		Progressive Sequential Length marking on every meter



Guaranteed Technical Particular

S.NO	DESCRIPTION	UNIT	RG-6 Coaxial cable Cu finished
1	Name of the Manufacturer		Relemac Cables
2	Place of Manufacture		Kundli sonipat Haryana
3	Brand		Microtek
4	Conductor		
a)	Material		Annealed Bare Copper wire
b)	Diameter of Copper wire	mm	0.98
c)	Shape of conductor		Solid circular
d)	Min. no. of strands		1
5	Insulation		
a)	Material		Gas Injected Physical Foamed Polyethylene
b)	O.D.	mm	4.60
6	Shielding		with Al. Bonded tape
7	Braiding		Braiding with Aluminium Alloy wires with coverages 85% min.
8	Outer Jacket		Black PVC
a)	Over all Dia	mm	7.0
9	Electrical characteristics		
a)	Conductor Resistance at 20°C	Ohm/km.	19.5
b)	Nominal capacitance	pF	53
c)	Nominal Impedance	Ohm	75
d)	Attenuation at 55 MHz	dB/100	5.2
e)	Marking		Progressive Sequential Length marking on every meter

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN