



50Ω TRIAX RG-58A/U

S.NO.	Description	Specification	Complies (Yes/No)
1.0	<u>Conductor</u>		
1.1	Material	Tinned Plated Copper	Yes
1.2	No. of Strands	7	Yes
1.3	Dia of each Strand	0.32 mm ± 0.005 mm	Yes
1.4	Dia of Conductor	0.96 mm ± 0.02 mm	Yes
2.0	<u>Insulation</u>		
2.1	Material	Extruded PE	Yes
2.2	Thickness of Insulation (Nom.)	1.0 mm	Yes
2.3	Single Core Dia with insulation	3.00 mm ± 0.10 mm	Yes
2.4	Color	White	Yes
3.0	<u>Coax- Shield</u>		
3.1	Material	TPC Wire Braiding	Yes
3.2	Coverage	>95%	Yes
4.0	<u>Inner Jacket</u>		
4.1	Material	Extruded PE	Yes
4.2	Thickness of Jacket (Nom.)	0.50 mm	Yes
4.3	Color	White	Yes
5.0	<u>Triax- Shield</u>		
5.1	Material	TPC Wire Braiding	Yes
5.2	Coverage	>95%	Yes
6.0	<u>Outer Jacket</u>		
6.1	Material	Extruded PVC	Yes
6.2	Thickness of Jacket (Nom.)	0.6 mm	Yes
6.3	Color	Yellow	Yes
7.0	<u>Finished Cable Dia</u>	6.20 mm ± 0.30 mm	Yes
CHARACTERISTIC			
8.0	Conductor Resistance	Max. 32.0 Ω/km @ 20 °C	Yes
9.0	Impedance	50 ± 3 Ω	Yes
10.0	Capacitance	101 pf/m	Yes
11.0	Velocity of Propagation	70%	Yes
12.0	Attenuation	0.5 dB/100 ft. @ 1 MHz 24 dB/100 ft. @ 1000 MHz	Yes
13.0	Max. Voltage Rating	1400V rms	Yes
14.0	Max. Operating Temp.	-20 °C to +70 °C	Yes