



WA-770 RF CABLE

Type		P/N:50222		V0
Structure drawing				
Structure characteristics				
Structure	Item		Standard value	
Inner conductor	Material		Silverplated copper wire	
	Makeup:total / O.D. of every wire(mm)		1/2.40	
	(Intertwist)NOM.O.D.(mm)		2.40±0.02	
Insulation	Material		Microporous PTFE	
	Color		Natural	
	NOM.O.D.(mm)		6.45±0.05	
First outer conductor	Material		Silverplated copper tape	
	NOM.O.D.(mm)		6.70±0.05	
	Coverage ratio(%)		100	
Second outer conductor	Material		Silverplated copper wire	
	NOM.O.D.(mm)		7.10±0.05	
	Coverage ratio(%)		≥90	
Jacket	Material		FEP	
	Color		Green	
	NOM.O.D.(mm)		7.70±0.20	
Electrical characteristics				
Item	Standard value	Item	Frequency	Standard value Unit:dB/m
Capacitance(pF/m)	78±3	Attenuation	1GHz	≤0.21
Velocity(%)	84±4		6GHz	≤0.43
Stability of IL manual	≤0.2dB@0.05~18GHz		10GHz	≤0.62
Impedance(Ω)	50±2		18GHz	≤0.88
Screening effectiveness	<-100dB@1GHz			
Dielectric withstand voltage(V)	3000			
Stability of IL manual range(4m subassembly)	≤0.2dB@0.05~18GHz			
Stability of temperature- phase(-55~+75℃)	△η max≤1000PPM			
VSWR(2.5m subassembly)	S≤1.10@0.05~2GHz S≤1.25@2~6GHz S≤1.35@6~18GHz			
Dependability				
Item		Unit	Standard value	
Min.bending radius static		mm	40	
Min.bending radius repeated		mm	—	
Operating temperature		℃	-55~+165	