



Flexible Seamless Waveguide

Part No: ST120 WEL1000PMC

1.0 Mechanical Specifications	
1.1 Waveguide Type	WR75
1.2 Flange Type	FBP120(Cover)/FBM120(Grooved)
1.3 Material	Copper
1.4 Inside Finish	Silver plating
1.5 Jacket Material	Black polysulfide rubber
1.6 Minimum Bend Radius (E Plane)	64 mm
1.7 Minimum Bend Radius (H Plane)	120 mm
1.8 Pressure	0.2 Mpa
1.9 Length	L=1000 mm
1.10 Accessory	Gasket mated with FBM120 flange
2.0 Electrical Specifications	
2.1 Frequency Range	10-15 GHz
2.2 VSWR (Max)	1.10
2.3 Insertion Loss (Max)	0.7 dB/m
2.4 Power Handling	1.5 kW (CW), 1500 kW (Peak)
3.0 Outline Drawings	

Revision History

Date	Revision	Changes
07-April-2009	1	First release

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN