



Flexible-Twistable Waveguide

Part No:ST-70WEL1000PM

1.0	Mechanical Specifications	
1.1	Waveguide Type	WR137
1.2	Flange Type	CPR137(F)/CPR137(G)
1.3	Body Material	Copper
1.4	Flange Material	Brass
1.5	Jacket	Black Neoprene Jacket
1.6	Maximum Twist	262 deg/m
1.7	Minimum Bend Radius (E Plane)	100 mm
1.8	Minimum Bend Radius (H Plane)	200 mm
1.9	Length	L=1000mm
2.0	Attachment	include fixing kit: O-Ring 1pcs Screw and nut M5 16sets Spring washer and plane washer 16sets
2.0	Electrical Specifications	
2.1	Frequency Range	5.85~8.2 GHz
2.2	VSWR (Max)	1.15
2.3	Attenuation (Max.)	0.25dB/m
2.4	Power handling	2 KW (CW)
3.0	Outline Drawings	



Part No: S.T-70WEL2000PM

1.0	Mechanical Specifications	
1.1	Waveguide Type	WR137
1.2	Flange Type	CPR137(F)/CPR137(G)
1.3	Body Material	Copper
1.4	Flange Material	Brass
1.5	Jacket	Black Neoprene Jacket
1.6	Maximum Twist	262 deg/m
1.7	Minimum Bend Radius (E Plane)	100 mm
1.8	Minimum Bend Radius (H Plane)	200 mm
1.9	Length	L=2000mm
2.0	Attachment	include fixing kit: O-Ring 1pcs Screw and nut M5 16sets Spring washer and plane washer 16sets
2.0	Electrical Specifications	
2.1	Frequency Range	5.85~8.2 GHz
2.2	VSWR (Max)	1.15
2.3	Attenuation (Max.)	0.25dB/m
2.4	Power handling	2 KW (CW)
3.0	Outline Drawings	
		
		