




 MAKE IN INDIA Technical Data	STK SERIES CONNECTOR	 www.rfconnector.in	 QUALITY PRODUCT of INDIA					
Nomenclature: RIGHT ANGLE			Page No. 1 of 1					
STK-5711- F26-RF400-CN-SB-Y	RIGHT ANGLE							
OUTLINE DRAWING								
    CABLE PREP. USE CST-400 (3192-004) .429" HEX.								
TECHNICAL DATA								
ELECTRICAL DATA								
Impedance	50 Ω							
Frequency range	DC to 4 Ghz							
Outer conductor	≤0.4							
Inner conductor	≤1.5							
Voltage	1500							
Insulation resistance	≥5000							
Insert loss	≤0.1							
VSWR	≤1.35							
MATERIAL INFORMATION								
COMPONENTS	MATERIALS	PLATINGS (mm)						
Inner conductor	spring cipper	Ag 200						
Outer conductor	Brass	Copper (Albaloy)						
Insulator	PTFE							
Ring	Silicone rubber							
ENVIRONMENTAL INFORMATION								
Temperature range	-55°c~+155°c							
Waterproofing standard	IEC 60068							
MECHANICAL INFORMATION								
Tensile force		400N						
Torsion		2N.m						
Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	01.11.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.								
www.rfconnector.in								