

 Technical Data	STK SERIES CONNECTOR	 www.rfconnector.in	
Nomenclature: STRAIGHT JACK			Page No. 1 of 1
STK-5711-F26-240-UG-Y	STRAIGHT JACK		
OUTLINE DRAWING			
			
TECHNICAL DATA			
ELECTRICAL DATA			
Impedance	50 Ω		
Frequency range	DC to 6 Ghz		
VRMS	≤1.30		
Working Voltage	1500		
Insulation Resistance	≥5000		
MATERIAL INFORMATION			
COMPONENTS	MATERIALS	PLATINGS (mm)	
BODY	BRASS	ALBALOY	
CONTACT PIN	QBe2	gold	
FERRULE	BRASS	ALBALOY	
INSULATOR	PTFE		
ENVIRONMENTAL INFORMATION			
Temperature range	-55°C~+155°C		
Thermal Shock	MIL-STD 202G		
MECHANICAL INFORMATION			
CENTER CONT	CAPTIVE		
COUPLING NUT TORQUE	N/A		
RETENTION FORCE	200		
DURABILITY	500		
QUTER CONT	CRIMP		
Originated	Date	Approved	Date
Sang	01.11.25	Krishnamurthy	-
This document is the property of Synergy Telecom P Ltd - New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division . This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.			