



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature:CONNECTOR RF50 SMA RP ST ADJ SQ FL JACK




Page No.

1 of 1

STK-571127431241

CONNECTOR RF50 SMA RP ST ADJ SQ FL JACK

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-26 GHz
VSWR	$1.06 + 0.002 \times F(\text{GHz})$ Maxi
Insertion loss	$0.07 \times \sqrt{F(\text{GHz})}$ dB Maxi
Voltage rating	500 Veff Maxi
RF leakage	$-(60 - F(\text{GHz}))$ dB Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	5000 M Ω mini

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)
BODY	STAINLESS STEEL	GOLD0.5 OVERNICKEL2
CENTERCONTACT	BERYLLIUMCOPPER	GOLD1.3 OVERNICKEL2
OUTERCONTACT	-	-
INSULATOR	PTFE	-

ENVIRONMENTAL INFORMATION

Temperature range	-65/+165 $^{\circ}\text{C}$
Hermeticseal	NA Atm.cm3/s

MECHANICAL INFORMATION

Axial force— Mating end	27 Nmin
Axial force— Opposite end	27 Nmini
Torque	2.8 N.cm mini
Mating life	500 Cycles mini
Weight	2.685 g

Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.
www.rfconnector.in