



STK SERIES CONNECTOR



Nomenclature: CONN RF50 SMA RP SQ FL CONT Φ-1.28 L-18.


Page No.

1 of 1

STK-571127431629

CONN RF50 SMA RP SQ FL CONT Φ-1.28 L-18.

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-18 GHz
VSWR	1.06 + 0.002 xF(GHz) Maxi
Insertion loss	0.07* √F(GHz) dB Maxi
Voltage rating	500 Veff Maxi
RF leakage	-(60-F(GHz)) dB Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	5000 MΩmini

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)
BODY	STAINLESS STEEL	PASSIVATED
CENTERCONTACT	BERYLLIUMCOPPER	GOLD1.3 OVERNICKEL2
OUTERCONTACT	-	-
INSULATOR	PTFE	-

ENVIRONMENTAL INFORMATION

Temperature range	-65/+165 °C
Hermeticseal	NA Atm.cm3/s

MECHANICAL INFORMATION

Axial force— Mating end	27 Nmin
Axial force— Opposite end	27 Nmini
Torque	2.8 N.cm mini
Mating life	500 Cycles mini
Weight	0.000 g

Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-



Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and all it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in