



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CONN RF50 BMA FL 2H M RP EXT DIEL




Page No.

1 of 1

STK-571128561291

CONN RF50 BMA FL 2H M RP EXT DIEL

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency Range (GHz)	0-22 GHz
Dielectric Withstanding Voltage (V)	1500 Veff mini
VSWR	1.25 + 0.000 xF(GHz) Maxi
Voltage rating	500 Veff Maxi
RF leakage	-(NA-F(GHz)) dBMaxi
Insertion Loss(dB, f/GHz)	0.07 $\sqrt{F}$ (GHz) dB Maxi
Insulation Resistance (M Ω)	5000 M Ω Mini

MECHANICAL INFORMATION

Axial force– Mating end	27 Nmini
Axial force– Opposite end	27 Nmini
Torque	NA N.cmmini
Mating	NA N.cm
Panel nut	NA N.cm
Mating life	1000 Cycles mini
Weight	0.000 g

ENVIRONMENTAL

Operatingtemperature	-65/+125 °C
Hermeticseal	NA Atm.cm3/s
Panelleakage	NA

MATERIAL INFORMATION

COMPONENTS	MATERIALS	PLATINGS (mm)	
Centre contact	BERYLLIUMCOPPER	GOLD1.3 OVERNICKEL2	
Outer contact	-	-	
GASKET	SILICONE RUBBER	-	
Body	STAINLESS STEEL	PASSIVATED.	
Insulator	PTFE	-	

Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	01.11.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd, WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
				-	-	-	-	Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in