

 Technical Data	STK SERIES CONNECTOR	 www.rfconnector.in						
Nomenclature: CONN RF50 SMA RA W/CABLE			Page No. 1 of 1					
STK-571131521246	CONN RF50 SMA RA W/CABLE							
OUTLINE DRAWING								
								
TECHNICAL DATA								
ELECTRICAL DATA								
Impedance	50 Ω							
Frequency range	26.5 GHz							
MATERIAL INFORMATION								
COMPONENTS	MATERIALS	PLATINGS (mm)						
Body	Stainless Steel	Passivated						
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)						
Outer conductor	Stainless Steel	Passivated						
Insulator	PFA / PTFE	-						
Coupling nut	Stainless Steel	Passivated						
ENVIRONMENTAL INFORMATION								
Temperature range	-65 °C 165°C							
MECHANICAL INFORMATION								
Weight	0.0056 kg							
Mating cycles	500							
Cable entry centre contact	plugged							
Cable entry outer contact	soldered							
Originated	Date	Approved	Date	Rev	Amend	Name	Date	
Sang	01.12.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	Email: sales.blr@rfconnector.in
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand. www.rfconnector.in								